

Package ‘procs’

July 27, 2025

Type Package

Title Recreates Some 'SAS®' Procedures in 'R'

Version 1.0.7

Maintainer David Bosak <dbosak01@gmail.com>

Description Contains functions to simulate the most commonly used 'SAS®' procedures. Specifically, the package aims to simulate the functionality of 'proc freq', 'proc means', 'proc ttest', 'proc reg', 'proc transpose', 'proc sort', and 'proc print'. The simulation will include recreating all statistics with the highest fidelity possible.

License CC0

Encoding UTF-8

URL <https://procs.r-sassy.org>, <https://github.com/dbosak01/procs>

BugReports <https://github.com/dbosak01/procs/issues>

Depends R (>= 3.6.0), common

Suggests knitr, rmarkdown, testthat (>= 3.0.0), covr, logr

Imports utils, fmtr, reporter, stats, tibble, sasLM (>= 0.9.9)

VignetteBuilder knitr

RoxygenNote 7.3.2

Config/testthat/edition 3

NeedsCompilation no

Author David Bosak [aut, cre],
Kevin Kramer [ctb],
Brian Varney [ctb],
Duong Tran [ctb],
Yifei Chen [ctb]

Repository CRAN

Date/Publication 2025-07-27 05:30:02 UTC

Contents

proc_freq	2
proc_means	9
proc_print	14
proc_reg	15
proc_sort	21
proc_transpose	24
proc_ttest	27

Index	34
--------------	-----------

proc_freq	<i>Generates Frequency Statistics</i>
-----------	---------------------------------------

Description

The proc_freq function generates frequency statistics. It is both an interactive function that can be used for data exploration, and can produce dataset output for further analysis. The function can perform one and two-way frequencies. Two-way frequencies are produced as a cross-tabulation by default. There are many options to control the generated tables. The function will return requested tables in a named list.

Usage

```
proc_freq(  
  data,  
  tables = NULL,  
  output = NULL,  
  by = NULL,  
  weight = NULL,  
  options = NULL,  
  titles = NULL  
)
```

Arguments

data	The input data frame to perform frequency calculations on. Input data as the first parameter makes this function pipe-friendly.
tables	The variable or variables to perform frequency counts on. The table specifications are passed as a vector of strings. For one-way frequencies, simply pass the variable name. For two-way tables, pass the desired combination of variables separated by a star (*) operator. The parameter does not accept SAS® style grouping syntax. All cross combinations should be listed explicitly. If the table request is named, the name will be used as the list item name on the return list of tables. See "Example 3" for an illustration on how to name an output table.

output	Whether or not to return datasets from the function. Valid values are "out", "none", and "report". Default is "out". This parameter also accepts the data shaping options "long", "stacked", and "wide". See the Data Shaping section for a description of these options. Multiple output keywords may be passed on a character vector. For example, to produce both a report dataset and a "long" output dataset, use the parameter <code>output = c("report", "out", "long")</code> .
by	An optional by group. Parameter accepts a vector of one or more variable names. When this parameter is set, data will be subset for each by group, and tables will be generated for each subset.
weight	An optional weight parameter. This parameter is passed as a variable name to use for the weight. If a weight variable is indicated, the weighted value will be summed to calculate the frequency counts.
options	The options desired for the function. Options are passed to the parameter as a vector of quoted strings. You may also use the <code>v()</code> function to pass unquoted strings. The following options are available: "chisq", "crosstab", "fisher", "list", "missing", "nlevels", "nocol", "nocum", "nofreq", "nopercent", "noprint", "nonobs", "norow", "nosparse", "notable", "outcum". See the Options section for a description of these options.
titles	A vector of titles to assign to the interactive report.

Details

The `proc_freq` function generates frequency statistics for one-way and two-way tables. Data is passed in on the `data` parameter. The desired frequencies are specified on the `tables` parameter.

Value

The function will return all requested datasets by default. This is equivalent to the `output = "out"` option. To return the datasets as created for the interactive report, pass the "report" output option. If no output datasets are desired, pass the "none" output option. If a single dataset is requested, the function will return a single dataset. If multiple datasets are requested, the function will return a list of datasets. The type of data frame returned will correspond to the type of data frame passed in on the `data` parameter. If the input data is a tibble, the output data will be a tibble. If the input data is a Base R data frame, the output data will be a Base R data frame.

Report Output

By default, `proc_freq` results will be immediately sent to the viewer as an HTML report. This functionality makes it easy to get a quick analysis of your data with very little effort. To turn off the interactive report, pass the "noprint" keyword to the `options` parameter or set `options("procs.print" = FALSE)`.

The `titles` parameter allows you to set one or more titles for your report. Pass these titles as a vector of strings.

If the frequency variables have a label assigned, that label will be used in the report output. This feature gives you some control over the column headers in the final report.

The exact datasets used for the interactive output can be returned as a list. To return these datasets as a list, pass the "report" keyword on the `output` parameter. This list may in turn be passed to `proc_print` to write the report to a file.

Data Frame Output

The `proc_freq` function returns output datasets. If you are requesting only one table, a single data frame will be returned. If you request multiple tables, a list of data frames will be returned.

By default, the list items are named according to the strings specified on the `tables` parameter. You may control the names of the returned results by using a named vector on the `tables` parameter.

The standard output datasets are optimized for data manipulation. Column names have been standardized, and additional variables may be present to help with data manipulation. For instance, the `by` variable will always be named "BY", and the frequency category will always be named "CAT". In addition, data values in the output datasets are not rounded or formatted to give you the most accurate statistical results.

Frequency Weight

Normally the `proc_freq` function counts each row in the input data equally. In some cases, however, each row in the data can represent multiple observations, and rows should not be treated equally. In these cases, use the `weight` parameter. The parameter accepts a variable/column name to use as the weighted value. If the `weight` parameter is used, the function will sum the weighted values instead of counting rows.

By Groups

You may request that frequencies be separated into by groups using the `by` parameter. The parameter accepts one or more variable names from the input dataset. When this parameter is assigned, the data will be subset by the "by" variable(s) before frequency counts are calculated. On the interactive report, the by groups will appear in separate tables. On the output dataset, the by groups will be identified by additional columns.

Options

The `options` parameter accepts a vector of options. Normally, these options must be quoted. But you may pass them unquoted using the `v()` function. For example, you can request the number of category levels and the Chi-Square statistic like this: `options = v(nlevels, chisq)`.

Below are all the available options and a description of each:

- **crosstab**: Two-way output tables are a list style by default. If you want a crosstab style, pass the "crosstab" option.
- **list**: Two-way interactive tables are a crosstab style by default. If you want a list style two-way table, pass the "list" option.
- **missing**: Normally, missing values are not counted and not shown on frequency tables. The "missing" option allows you to treat missing (NA) values as normal values, so that they are counted and shown on the frequency table. Missing levels will appear on the table as a single dot (".").
- **nlevels**: The "nlevels" option will display the number of unique values for each variable in the frequency table. These levels are generated as a separate table that appears on the report, and will also be output from the function as a separate dataset.
- **nocol**: Two-way cross tabulation tables include column percents by default. To turn them off, pass the "nocol" option.

- **nocum**: Whether to include the cumulative frequency and percent columns on one-way, interactive tables. These columns are included by default. To turn them off, pass the "nocum" option.
- **nofreq**: The "nofreq" option will remove the frequency column from one-way and two-way tables.
- **nopercent**: The "nopercent" option will remove the percent column from one-way and two-way tables.
- **noprint**: Whether to print the interactive report to the viewer. By default, the report is printed to the viewer. The "noprint" option will inhibit printing.
- **nonobs**: Whether to include the number of observations "N" column on the output and interactive tables. By default, the N column will be included. The "nonobs" option turns it off.
- **norow**: Whether to include the row percentages on two-way crosstab tables. The "norow" option will turn them off.
- **nosparse/sparse**: Whether to include categories for which there are no frequency counts. Zero-count categories will be included by default, which is the "sparse" option. If the "nosparse" option is present, zero-count categories will be removed.
- **notable**: Whether to include the frequency table in the output dataset list. Normally, the frequency table is included. You may want to exclude the frequency table in some cases, for instance, if you only want the Chi-Square statistic.
- **outcum**: Whether to include the cumulative frequency and percent on output frequency tables. By default, these columns are not included. The "outcum" option will include them.

Statistics Options

In addition to the above options, the options parameter accepts some statistics options. The following keywords will generate an additional tables of specialized statistics. These statistics options are only available on two-way tables:

- **chisq**: Requests that the Chi-square statistics be produced.
- **fisher**: Requests that the Fisher's exact statistics be produced.

Using Factors

There are some occasions when you may want to define the tables variable or by variables as a factor. One occasion is for sorting/ordering, and the other is for obtaining zero-counts on sparse data.

To order the frequency categories in the frequency output, define the tables variable as a factor in the desired order. The function will then retain that order for the frequency categories in the output dataset and report.

You may also wish to define the tables variable as a factor if you are dealing with sparse data and some of the frequency categories are not present in the data. To ensure these categories are displayed with zero-counts, define the tables variable or by variable as a factor and use the "sparse" option. Note that the "sparse" option is actually the default.

If you do not want to show the zero-count categories on a variable that is defined as a factor, pass the "nosparse" keyword on the options parameter.

Data Shaping

By default, the `proc_freq` function returns an output dataset of frequency results. If running interactively, the function also prints the frequency results to the viewer. As described above, the output dataset can be somewhat different than the dataset sent to the viewer. The output parameter allows you to choose which datasets to return. There are three choices: "out", "report", and "none". The "out" keyword returns the default output dataset. The "report" keyword returns the dataset(s) sent to the viewer. You may also pass "none" if you don't want any datasets returned from the function.

In addition, the output dataset produced by the "out" keyword can be shaped in different ways. These shaping options allow you to decide whether the data should be returned long and skinny, or short and wide. The shaping options can reduce the amount of data manipulation necessary to get the frequencies into the desired form. The shaping options are as follows:

- **long:** Transposes the output datasets so that statistics are in rows and frequency categories are in columns.
- **stacked:** Requests that output datasets be returned in "stacked" form, such that both statistics and frequency categories are in rows.
- **wide:** Requests that output datasets be returned in "wide" form, such that statistics are across the top in columns, and frequency categories are in rows. This shaping option is the default.

See Also

For summary statistics, see [proc_means](#). To pivot or transpose the data coming from `proc_freq`, see [proc_transpose](#).

Examples

```
library(procs)

# Turn off printing for CRAN checks
options("procs.print" = FALSE)

# Create sample data
df <- as.data.frame(HairEyeColor, stringsAsFactors = FALSE)

# Assign labels
labels(df) <- list(Hair = "Hair Color",
                   Eye = "Eye Color",
                   Sex = "Sex at Birth")

# Example #1: One way frequencies on Hair and Eye color with weight option.
res <- proc_freq(df,
                 tables = v(Hair, Eye),
                 options = outcum,
                 weight = Freq)

# View result data
res
# $Hair
#   VAR   CAT   N CNT      PCT CUMSUM  CUMPCT
# 1 Hair Black 592 108 18.24324    108 18.24324
```

```
# 2 Hair Blond 592 127 21.45270    235 39.69595
# 3 Hair Brown 592 286 48.31081    521 88.00676
# 4 Hair Red 592 71 11.99324    592 100.00000
```

```
#
# $Eye
#   VAR   CAT   N CNT      PCT CUMSUM   CUMPCT
# 1 Eye Blue 592 215 36.31757    215 36.31757
# 2 Eye Brown 592 220 37.16216    435 73.47973
# 3 Eye Green 592 64 10.81081    499 84.29054
# 4 Eye Hazel 592 93 15.70946    592 100.00000
```

```
# Example #2: 2 x 2 Crosstabulation table with Chi-Square statistic
```

```
res <- proc_freq(df, tables = Hair * Eye,
                 weight = Freq,
                 options = v(crosstab, chisq))
```

```
# View result data
```

```
res
```

```
# $`Hair * Eye`
```

#	Category	Statistic	Blue	Brown	Green	Hazel	Total
#1	Black	Frequency	20.000000	68.000000	5.000000	15.000000	108.00000
#2	Black	Percent	3.378378	11.486486	0.8445946	2.533784	18.24324
#3	Black	Row Pct	18.518519	62.962963	4.6296296	13.888889	NA
#4	Black	Col Pct	9.302326	30.909091	7.8125000	16.129032	NA
#5	Blond	Frequency	94.000000	7.000000	16.000000	10.000000	127.00000
#6	Blond	Percent	15.878378	1.182432	2.7027027	1.689189	21.45270
#7	Blond	Row Pct	74.015748	5.511811	12.5984252	7.874016	NA
#8	Blond	Col Pct	43.720930	3.181818	25.000000	10.752688	NA
#9	Brown	Frequency	84.000000	119.000000	29.000000	54.000000	286.00000
#10	Brown	Percent	14.189189	20.101351	4.8986486	9.121622	48.31081
#11	Brown	Row Pct	29.370629	41.608392	10.1398601	18.881119	NA
#12	Brown	Col Pct	39.069767	54.090909	45.3125000	58.064516	NA
#13	Red	Frequency	17.000000	26.000000	14.000000	14.000000	71.00000
#14	Red	Percent	2.871622	4.391892	2.3648649	2.364865	11.99324
#15	Red	Row Pct	23.943662	36.619718	19.7183099	19.718310	NA
#16	Red	Col Pct	7.906977	11.818182	21.8750000	15.053763	NA
#17	Total	Frequency	215.000000	220.000000	64.000000	93.000000	592.00000
#18	Total	Percent	36.317568	37.162162	10.8108108	15.709459	100.00000

```
# $`chisq:Hair * Eye`
```

#		STAT	DF	VAL	PROB
# 1	Chi-Square	9	138.2898	2.325287e-25	
# 2	Continuity Adj. Chi-Square	9	138.2898	2.325287e-25	

```
#' # Example #3: By variable with named table request
```

```
res <- proc_freq(df, tables = v(Hair, Eye, Cross = Hair * Eye),
                 by = Sex,
                 weight = Freq)
```

```
# View result data
```

```
res
```

```
# $Hair
```

#	BY	VAR	CAT	N CNT	PCT
---	----	-----	-----	-------	-----

```

# 1 Female Hair Black 313 52 16.61342
# 2 Female Hair Blond 313 81 25.87859
# 3 Female Hair Brown 313 143 45.68690
# 4 Female Hair Red 313 37 11.82109
# 5 Male Hair Black 279 56 20.07168
# 6 Male Hair Blond 279 46 16.48746
# 7 Male Hair Brown 279 143 51.25448
# 8 Male Hair Red 279 34 12.18638
#
# $Eye
# BY VAR CAT N CNT PCT
# 1 Female Eye Blue 313 114 36.421725
# 2 Female Eye Brown 313 122 38.977636
# 3 Female Eye Green 313 31 9.904153
# 4 Female Eye Hazel 313 46 14.696486
# 5 Male Eye Blue 279 101 36.200717
# 6 Male Eye Brown 279 98 35.125448
# 7 Male Eye Green 279 33 11.827957
# 8 Male Eye Hazel 279 47 16.845878
#
# $Cross
# BY VAR1 VAR2 CAT1 CAT2 N CNT PCT
# 1 Female Hair Eye Black Blue 313 9 2.8753994
# 2 Female Hair Eye Black Brown 313 36 11.5015974
# 3 Female Hair Eye Black Green 313 2 0.6389776
# 4 Female Hair Eye Black Hazel 313 5 1.5974441
# 5 Female Hair Eye Blond Blue 313 64 20.4472843
# 6 Female Hair Eye Blond Brown 313 4 1.2779553
# 7 Female Hair Eye Blond Green 313 8 2.5559105
# 8 Female Hair Eye Blond Hazel 313 5 1.5974441
# 9 Female Hair Eye Brown Blue 313 34 10.8626198
# 10 Female Hair Eye Brown Brown 313 66 21.0862620
# 11 Female Hair Eye Brown Green 313 14 4.4728435
# 12 Female Hair Eye Brown Hazel 313 29 9.2651757
# 13 Female Hair Eye Red Blue 313 7 2.2364217
# 14 Female Hair Eye Red Brown 313 16 5.1118211
# 15 Female Hair Eye Red Green 313 7 2.2364217
# 16 Female Hair Eye Red Hazel 313 7 2.2364217
# 17 Male Hair Eye Black Blue 279 11 3.9426523
# 18 Male Hair Eye Black Brown 279 32 11.4695341
# 19 Male Hair Eye Black Green 279 3 1.0752688
# 20 Male Hair Eye Black Hazel 279 10 3.5842294
# 21 Male Hair Eye Blond Blue 279 30 10.7526882
# 22 Male Hair Eye Blond Brown 279 3 1.0752688
# 23 Male Hair Eye Blond Green 279 8 2.8673835
# 24 Male Hair Eye Blond Hazel 279 5 1.7921147
# 25 Male Hair Eye Brown Blue 279 50 17.9211470
# 26 Male Hair Eye Brown Brown 279 53 18.9964158
# 27 Male Hair Eye Brown Green 279 15 5.3763441
# 28 Male Hair Eye Brown Hazel 279 25 8.9605735
# 29 Male Hair Eye Red Blue 279 10 3.5842294
# 30 Male Hair Eye Red Brown 279 10 3.5842294
# 31 Male Hair Eye Red Green 279 7 2.5089606

```



```
# 32   Male Hair   Eye   Red Hazel 279   7   2.5089606
```

proc_means

Calculates Summary Statistics

Description

The `proc_means` function generates summary statistics for selected variables on the input dataset. The variables are identified on the `var` parameter. The statistics to perform are identified on the `stats` parameter. Results are displayed in the viewer interactively and returned from the function.

Usage

```
proc_means(
  data,
  var = NULL,
  stats = c("n", "mean", "std", "min", "max"),
  output = NULL,
  by = NULL,
  class = NULL,
  options = NULL,
  titles = NULL
)
```

Arguments

<code>data</code>	The input data frame for which to calculate summary statistics. This parameter is required.
<code>var</code>	The variable(s) to calculate summary statistics for. If no variables are specified, summary statistics will be generated for all numeric variables on the input data frame.
<code>stats</code>	A vector of summary statistics keywords. Valid keywords are: "css", "clm", "cv", "kurt", "kurtosis", "lclm", "mean", "median", "mode", "min", "max", "n", "nmiss", "nobs", "p1", "p5", "p10", "p20", "p25", "p30", "p40", "p50", "p60", "p70", "p75", "p80", "p90", "p95", "p99", "q1", "q3", "qrange", "range", "skew", "skewness", "std", "stddev", "stderr", "sum", "uclm", "uss", and "vari". For hypothesis testing, the function supports "t", "prt", "probt", and "df". Default statistics are: "n", "mean", "std", "min", and "max".
<code>output</code>	Whether or not to return datasets from the function. Valid values are "out", "none", and "report". Default is "out", and will produce dataset output specifically designed for programmatic use. The "none" option will return a NULL instead of a dataset or list of datasets. The "report" keyword returns the datasets from the interactive report, which may be different from the standard output. The output parameter also accepts data shaping keywords "long", "stacked", and "wide". The shaping keywords control the structure of the output data. See the Data Shaping section for additional details. Note that multiple output keywords

	may be passed on a character vector. For example, to produce both a report dataset and a "long" output dataset, use the parameter <code>output = c("report", "out", "long")</code> .
by	An optional by group. If you specify a by group, the input data will be subset on the by variable(s) prior to performing any statistics.
class	The class parameter is similar to the by parameter, but the output is different. By groups will create completely separate tables, while class groups will be continued in the same table. When a by and a class are both specified, the class will be nested in the by.
options	A vector of optional keywords. Valid values are: "alpha =", "completetypes", "maxdec =", "noprint", "notype", "nofreq", "nonobs", "nway". The "notype", "nofreq", and "nonobs" keywords will turn off columns on the output datasets. The "alpha =" option will set the alpha value for confidence limit statistics. The default is 95% (alpha = 0.05). The "maxdec =" option sets the maximum number of decimal places displayed on report output. The "nway" option returns only the highest type values.
titles	A vector of one or more titles to use for the report output.

Details

The `proc_means` function is for analysis of continuous variables. Data is passed in on the data parameter. The desired statistics are specified using keywords on the stats parameter. The function can segregate data into groups using the by and class parameters. There are also options to determine whether and what results are returned.

Value

Normally, the requested summary statistics are shown interactively in the viewer, and output results are returned as a data frame. If the request produces multiple data frames, they will be returned in a list. You may then access individual datasets from the list. The interactive report can be turned off using the "noprint" option, and the output datasets can be turned off using the "none" keyword on the output parameter.

Interactive Output

By default, `proc_freq` results will be immediately sent to the viewer as an HTML report. This functionality makes it easy to get a quick analysis of your data. To turn off the interactive report, pass the "noprint" keyword to the options parameter.

The titles parameter allows you to set one or more titles for your report. Pass these titles as a vector of strings.

The exact datasets used for the interactive report can be returned as a list. To return these datasets as a list, pass the "report" keyword on the output parameter. This list may in turn be passed to [proc_print](#) to write the report to a file.

Dataset Output

Dataset results are also returned from the function by default. If the results are a single dataset, a single data frame will be returned. If there are multiple results, a list of data frames will be returned.

The output datasets generated are optimized for data manipulation. The column names have been standardized, and additional variables may be present to help with data manipulation. For example, the by variable will always be named "BY", and the class variable will always be named "CLASS". In addition, data values in the output datasets are intentionally not rounded or formatted to give you the most accurate statistical results.

Statistics Keywords

The following statistics keywords can be passed on the `stats` parameter. Normally, each statistic will be contained in a separate column and the column name will be the same as the statistic keyword. You may pass statistic keywords as a quoted vector of strings, or an unquoted vector using the `v()` function.

- **css**: Corrected Sum of Squares.
- **clm, lclm, uclm**: Upper and lower confidence limits.
- **cv**: Coefficient of Variation.
- **kurt/kurtosis**: The Kurtosis is a description of the distribution tails. It requires at least 4 complete observations.
- **mean**: The arithmetic mean.
- **median**: The median.
- **mode**: The mode of the target variable.
- **min, max**: The minimum and maximum values of the target variable.
- **n**: The number of non-missing observations.
- **nmiss**: The number of missing observations.
- **nobs**: The number of observations, whether missing or non-missing.
- **p1 - p99**: Percentile ranges from p1 to p99, in increments of 5.
- **qrange, q1, q3**: Quantile ranges for the first and third quantiles.
- **range**: Difference between the minimum and maximum values.
- **skew/skewness**: A measure of distribution skewness. It requires at least 3 complete observations.
- **std/stddev**: Standard deviation.
- **stderr**: Standard error.
- **sum**: The sum of variable values.
- **uss**: Uncorrected sum of squares.
- **vari**: The variance.

The function supports the following keywords to perform hypothesis testing:

- **t**: Student's t statistic.
- **prrt/probt**: A two-tailed p-value for the Student's t statistic.
- **df**: Degrees of freedom for the Student's t statistic.

Options

The `proc_means` function recognizes the following options. Options may be passed as a quoted vector of strings, or an unquoted vector using the `v()` function.

- **alpha = :** The "alpha = " option will set the alpha value for confidence limit statistics. Set the alpha as a decimal value between 0 and 1. For example, you can set a 90% confidence limit as `alpha = 0.1`.
- **completetypes:** The "completetypes" option will generate all combinations of the class variable, even if there is no data present for a particular level. Combinations will be distinguished by the TYPE variable. To use the "completetypes" option, define the class variable(s) as a factor.
- **maxdec = :** The "maxdec = " option will set the maximum of decimal places displayed on report output. For example, you can set 4 decimal places as follows: `maxdec = 4`. Default is 7 decimal places. This option will not round any values on the output dataset.
- **nofreq, nonobs:** Turns off the FREQ column on the output datasets.
- **noprint:** Whether to print the interactive report to the viewer. By default, the report is printed to the viewer. The "noprint" option will inhibit printing.
- **notype:** Turns off the TYPE column on the output dataset.
- **nway:** Returns only the highest level TYPE combination. By default, the function returns all TYPE combinations.

TYPE and FREQ Variables

The TYPE and FREQ variables appear on the output dataset by default.

The FREQ variable contains a count of the number of input rows/observations that were included in the statistics for that output row. The FREQ count can be different from the N statistic. The FREQ count is a count of the number of rows/observations, while the N statistic is a count of non-missing values. These counts can be different if you have missing values in your data. If you want to remove the FREQ column from the output dataset, use the "nofreq" option.

The TYPE variable identifies combinations of class categories, and produces summary statistics for each of those combinations. For example, the output dataset normally produces statistics for TYPE 0, which is all class categories, and a TYPE 1 which is each class category. If there are multiple classes, there will be multiple TYPE values for each level of class combinations. If you do not want to show the various type combinations, use the "nway" option. If you want to remove the TYPE column from the output dataset, use the "notype" option.

Using Factors

There are some occasions when you may want to define the class variable(s) as a factor. One occasion is for sorting/ordering, and the other is for obtaining zero-counts on sparse data.

To order the class categories in the means output, define the class variable as a factor in the desired order. The function will then retain that order for the class categories in the output dataset and report.

You may also wish to define the class variable as a factor if you are dealing with sparse data and some of the class categories are not present in the data. To ensure these categories are displayed with zero-counts, define the class variable as a factor and use the "completetypes" option.

Data Shaping

The output dataset produced by the "out" keyword can be shaped in different ways. These shaping options allow you to decide whether the data should be returned long and skinny, or short and wide. The shaping options can reduce the amount of data manipulation necessary to get the frequencies into the desired form. The shaping options are as follows:

- **long**: Transposes the output datasets so that statistics are in rows and variables are in columns.
- **stacked**: Requests that output datasets be returned in "stacked" form, such that both statistics and variables are in rows.
- **wide**: Requests that output datasets be returned in "wide" form, such that statistics are across the top in columns, and variables are in rows. This shaping option is the default.

Examples

```
# Turn off printing for CRAN checks
options("procs.print" = FALSE)

# Default statistics on iris
res1 <- proc_means(iris)

# View results
res1
```

#	TYPE	FREQ	VAR	N	MEAN	STD	MIN	MAX
# 1	0	150	Sepal.Length	150	5.843333	0.8280661	4.3	7.9
# 2	0	150	Sepal.Width	150	3.057333	0.4358663	2.0	4.4
# 3	0	150	Petal.Length	150	3.758000	1.7652982	1.0	6.9
# 4	0	150	Petal.Width	150	1.199333	0.7622377	0.1	2.5

```
# Defaults statistics with by
res2 <- proc_means(iris,
                    by = Species)

# View results
res2
```

#	BY	TYPE	FREQ	VAR	N	MEAN	STD	MIN	MAX
# 1	setosa	0	50	Sepal.Length	50	5.006	0.3524897	4.3	5.8
# 2	setosa	0	50	Sepal.Width	50	3.428	0.3790644	2.3	4.4
# 3	setosa	0	50	Petal.Length	50	1.462	0.1736640	1.0	1.9
# 4	setosa	0	50	Petal.Width	50	0.246	0.1053856	0.1	0.6
# 5	versicolor	0	50	Sepal.Length	50	5.936	0.5161711	4.9	7.0
# 6	versicolor	0	50	Sepal.Width	50	2.770	0.3137983	2.0	3.4
# 7	versicolor	0	50	Petal.Length	50	4.260	0.4699110	3.0	5.1
# 8	versicolor	0	50	Petal.Width	50	1.326	0.1977527	1.0	1.8
# 9	virginica	0	50	Sepal.Length	50	6.588	0.6358796	4.9	7.9
# 10	virginica	0	50	Sepal.Width	50	2.974	0.3224966	2.2	3.8
# 11	virginica	0	50	Petal.Length	50	5.552	0.5518947	4.5	6.9
# 12	virginica	0	50	Petal.Width	50	2.026	0.2746501	1.4	2.5

```
# Specified variables, statistics, and options
res3 <- proc_means(iris,
                    var = v(Petal.Length, Petal.Width),
                    class = Species,
```

```

stats = v(n, mean, std, median, qrange, clm),
options = nofreq,
output = long)

# View results
res3
#      CLASS TYPE  STAT Petal.Length Petal.Width
# 1      <NA>    0     N   150.0000000 150.0000000
# 2      <NA>    0  MEAN    3.7580000  1.1993333
# 3      <NA>    0   STD    1.7652982  0.7622377
# 4      <NA>    0 MEDIAN    4.3500000  1.3000000
# 5      <NA>    0 QRANGE    3.5000000  1.5000000
# 6      <NA>    0  LCLM    3.4731854  1.0763533
# 7      <NA>    0  UCLM    4.0428146  1.3223134
# 8   setosa    1     N    50.0000000  50.0000000
# 9   setosa    1  MEAN    1.4620000  0.2460000
#10   setosa    1   STD    0.1736640  0.1053856
#11   setosa    1 MEDIAN    1.5000000  0.2000000
#12   setosa    1 QRANGE    0.2000000  0.1000000
#13   setosa    1  LCLM    1.4126452  0.2160497
#14   setosa    1  UCLM    1.5113548  0.2759503
#15 versicolor    1     N    50.0000000  50.0000000
#16 versicolor    1  MEAN    4.2600000  1.3260000
#17 versicolor    1   STD    0.4699110  0.1977527
#18 versicolor    1 MEDIAN    4.3500000  1.3000000
#19 versicolor    1 QRANGE    0.6000000  0.3000000
#20 versicolor    1  LCLM    4.1264528  1.2697993
#21 versicolor    1  UCLM    4.3935472  1.3822007
#22 virginica    1     N    50.0000000  50.0000000
#23 virginica    1  MEAN    5.5520000  2.0260000
#24 virginica    1   STD    0.5518947  0.2746501
#25 virginica    1 MEDIAN    5.5500000  2.0000000
#26 virginica    1 QRANGE    0.8000000  0.5000000
#27 virginica    1  LCLM    5.3951533  1.9479453
#28 virginica    1  UCLM    5.7088467  2.1040547

```

proc_print

Prints a dataset

Description

The `proc_print` function is used to print a dataset or datasets. To print multiple datasets, pass them to the `data` parameter in a list. By default, the function prints to the viewer. It may also be used to print to the file system using the `output_type` and `file_path` parameters. This print function has limited options, and is meant to quickly view your data or dump it out to a file. For more reporting options, use the **reporter** package.

Usage

```
proc_print(
```

```

    data,
    file_path = NULL,
    output_type = "HTML",
    titles = NULL,
    style = NULL,
    view = TRUE
  )

```

Arguments

data	The data to print. Can be either a single dataset, or a list of datasets.
file_path	The path of the report to print.
output_type	The type of report to create. Valid values are "TXT", "RTF", "PDF", "HTML", and "DOCX". Default is "HTML".
titles	A vector of titles.
style	A style object, as defined by the reporter package. See create_style for details.
view	Whether to send the print output to the viewer. Valid values are TRUE and FALSE. Default is TRUE.

Value

If a file report was produced, the full path of the report. Otherwise, a NULL. In either case, the value will be returned invisibly.

Examples

```

# Turn off printing to pass CRAN checks
options("procs.print" = FALSE)

# Print mtcars to the viewer
proc_print(mtcars)

# Print mtcars to an RTF
pth <- proc_print(mtcars,
  file_path = tempfile(fileext = ".rtf"),
  titles = "MTCARS Proc Print Example",
  output_type = "RTF", view = FALSE)

# View file
# file.show(pth)

```

Description

The `proc_reg` function performs a regression for one or more models. The model(s) are passed on the `model` parameter, and the input dataset is passed on the `data` parameter. The `stats` parameter allows you to request additional statistics, similar to the model options in SAS. The `by` parameter allows you to subset the data into groups and run the model on each group. The `weight` parameter let's you assign a weight to each observation in the dataset. The `output` and `options` parameters provide additional customization of the results.

Usage

```
proc_reg(
  data,
  model,
  by = NULL,
  stats = NULL,
  output = NULL,
  weight = NULL,
  options = NULL,
  titles = NULL
)
```

Arguments

<code>data</code>	The input data frame for which to perform the regression analysis. This parameter is required.
<code>model</code>	A model for the regression to be performed. The model can be specified using either R syntax or SAS syntax. <code>model = var1 ~ var2 + var3</code> is an example of R style model syntax. If you wish to pass multiple models using R syntax, pass them in a list. For SAS syntax, pass the model as a quoted string: <code>model = "var1 = var2 var3"</code> . To pass multiple models using SAS syntax, pass them as a vector of strings. By default, the models will be named "MODEL1", "MODEL2", etc. If you want to name your model, pass it as a named list or named vector.
<code>by</code>	An optional by group. If you specify a by group, the input data will be subset on the by variable(s) prior to performing the regression. For multiple by variables, pass them as a quoted vector of variable names. You may also pass them unquoted using the <code>v</code> function.
<code>stats</code>	Optional statistics keywords. Valid values are "adjrsq", "clb", "est", "edf", "hcc", "hccmethod", "mse", "p", "press", "rsquare", "sse", "spec", "seb", and "table". A single keyword may be passed with or without quotes. Pass multiple keywords either as a quoted vector, or unquoted vector using the <code>v()</code> function. These statistics keywords largely correspond to the options on the "model" statement in SAS. Most of them control which statistics are added to the interactive report. Some keywords control statistics on the output dataset. See the Statistics Keywords section for details on the purpose and target of each keyword.
<code>output</code>	Whether or not to return datasets from the function. Valid values are "out", "none", and "report". Default is "out", and will produce dataset output specifically designed for programmatic use. The "none" option will return a NULL

	instead of a dataset or list of datasets. The "report" keyword returns the datasets from the interactive report, which may be different from the standard output. Note that some statistics are only available on the interactive report. The output parameter also accepts data shaping keywords "long", "stacked", and "wide". These shaping keywords control the structure of the output data. See the Data Shaping section for additional details. Note that multiple output keywords may be passed on a character vector. For example, to produce both a report dataset and a "long" output dataset, use the parameter <code>output = c("report", "out", "long")</code>.
weight	The name of a variable to use as a weight for each observation. The weight is commonly provided as the inverse of each variance.
options	A vector of optional keywords. Valid values are: "alpha =", "edf", "noprint", "outest", "outseb", "press", "rsquare", and "tableout". The "alpha =" option will set the alpha value for confidence limit statistics. The default is 95% (alpha = 0.05). The "noprint" option turns off the interactive report. For other options, see the Options section for explanations of each.
titles	A vector of one or more titles to use for the report output.

Details

The `proc_reg` function is a general purpose regression function. It produces a dataset output by default, and, when working in RStudio, also produces an interactive report. The function has many convenient options for what statistics are produced and how the analysis is performed. All statistical output from `proc_reg` matches SAS.

A model may be specified using R model syntax or SAS model syntax. To use SAS syntax, the model statement must be quoted. To pass multiple models using R syntax, pass them to the `model` parameter in a list. To pass multiple models using SAS syntax, pass them to the `model` parameter as a vector of strings.

Value

Normally, the requested regression statistics are shown interactively in the viewer, and output results are returned as a data frame. If you request "report" datasets, they will be returned as a list. You may then access individual datasets from the list using dollar sign (\$) syntax. The interactive report can be turned off using the "noprint" option. The output dataset can be turned off using the "none" keyword on the output parameter. If the output dataset is turned off, the function will return a NULL.

Interactive Output

By default, `proc_reg` results will be sent to the viewer as an HTML report. This functionality makes it easy to get a quick analysis of your data. To turn off the interactive report, pass the "noprint" keyword to the `options` parameter.

The `titles` parameter allows you to set one or more titles for your report. Pass these titles as a vector of strings.

The exact datasets used for the interactive report can be returned as a list. To return these datasets, pass the "report" keyword on the output parameter. This list may in turn be passed to [proc_print](#) to write the report to a file.

Dataset Output

Dataset results are also returned from the function by default. `proc_reg` typically returns a single dataset. The columns and rows on this dataset can change depending on the keywords passed to the `stats` and `options` parameters.

The default output dataset is optimized for data manipulation. The column names have been standardized, and additional variables may be present to help with data manipulation. The data values in the output dataset are intentionally not rounded or formatted to give you the most accurate numeric results.

You may also request to return the datasets used in the interactive report. To request these datasets, pass the "report" option to the output parameter. Each report dataset will be named according to the category of statistical results. There are four standard categories: "NObs", "ANOVA", "Fit-Statistics", and "ParameterEstimates". When the "spec" statistics option is passed, the function will also return a "SpecTest" dataset containing the White's test results. If the "p" option is present, the "OutputStatistics" and "ResidualStatistics" tables will be included.

If you don't want any datasets returned, pass the "none" option on the output parameter.

Statistics Keywords

The following statistics keywords can be passed on the `stats` parameter. You may pass statistic keywords as a quoted vector of strings, or an unquoted vector using the `v()` function. An individual statistics keyword can be passed without quoting.

- **adjrsq**: Adds adjusted r-square value to the output dataset.
- **clb**: Requests confidence limits be added to the interactive report.
- **edf**: Includes the number of regressors, the error degrees of freedom, and the model r-square to the output dataset.
- **est**: Request an output dataset of parameter estimate and optional model fit summary statistics. This statistics option is the default.
- **hcc**: The "hcc" statistics keyword requests that heteroscedasticity-consistent standard errors of the parameter estimates be sent to the interactive report.
- **hccmethod=**: When the "hcc" option is present, the "hccmethod=" option specifies the type of method to use. Valid values are 0 and 3.
- **mse**: Computes the mean squared error for each model and adds to the output dataset.
- **p**: Computes predicted and residual values and sends to a separate table on the interactive report.
- **press**: Includes the predicted residual sum of squares (PRESS) statistic in the output dataset.
- **rsquare**: Include the r-square statistic in the output dataset. The "rsquare" option has the same effect as the "edf" option.
- **seb**: Outputs the standard errors of the parameter estimates to the output dataset. These values will be identified as type "SEB".
- **spec**: Adds the "White's test" table to the interactive output. This test determines whether the first and second moments of the model are correctly specified.
- **sse**: Adds the error sum of squares to the output dataset.

- **table:** The "table" keyword is used to send standard errors, t-statistics, p-values, and confidence limits to the output dataset. These additional statistics are identified by types "STDERR", "T", and "PVALUE". The confidence limits are identified by "LxxB" and "UxxB", where "xx" is the alpha value in percentage terms. The "table" keyword on the `stats` parameter performs the same functions as the "tableout" option on the `options` parameter.

Options

The `proc_reg` function recognizes the following options. Options may be passed as a quoted vector of strings, or an unquoted vector using the `v()` function.

- **alpha = :** The "alpha = " option will set the alpha value for confidence limit statistics. Set the alpha as a decimal value between 0 and 1. For example, you can set a 90% confidence limit as `alpha = 0.1`.
- **edf:** Includes the number of regressors, the error degrees of freedom, and the model r-square to the output dataset.
- **noprint:** Whether to print the interactive report to the viewer. By default, the report is printed to the viewer. The "noprint" option will inhibit printing. You may inhibit printing globally by setting the package print option to false: `options("procs.print" = FALSE)`.
- **outest:** The "outest" option is used to request the parameter estimates and model fit summary statistic be sent to the output dataset. The parameter estimates are identified as type "PARMS" on the output dataset. The "outest" dataset is the default output dataset, and this option does not normally need to be passed.
- **outseb:** The "outseb" option is used to request the standard errors be sent to the output dataset. The standard errors will be added as a new row identified by type "SEB". This request can also be made by passing the "seb" keyword to the `stats` parameter.
- **press:** Includes the predicted residual sum of squares (PRESS) statistic in the output dataset.
- **rsquare:** Include the r-square statistic in the output dataset. The "rsquare" option has the same effect as the "edf" option.
- **tableout:** The "tableout" option is used to send standard errors, t-statistics, p-values, and confidence limits to the output dataset. These additional statistics are identified by types "STDERR", "T", and "PVALUE". The confidence limits are identified by "LxxB" and "UxxB", where "xx" is the alpha value in percentage terms. The "tableout" option on the `options` parameter performs the same functions as the "table" keyword on the `stats` parameter.

Data Shaping

The output datasets produced by the function can be shaped in different ways. These shaping options allow you to decide whether the data should be returned long and skinny, or short and wide. The shaping options can reduce the amount of data manipulation necessary to get the data into the desired form. The shaping options are as follows:

- **long:** Transposes the output datasets so that statistics are in rows and variables are in columns.
- **stacked:** Requests that output datasets be returned in "stacked" form, such that both statistics and variables are in rows.
- **wide:** Requests that output datasets be returned in "wide" form, such that statistics are across the top in columns, and variables are in rows. This shaping option is the default.

These shaping options are passed on the output parameter. For example, to return the data in "long" form, use output = "long".

Examples

```
# Turn off printing for CRAN checks
options("procs.print" = FALSE)

# Prepare sample data
set.seed(123)
dat <- cars
samplecar <- sample(c(TRUE, FALSE), nrow(cars), replace=TRUE, prob=c(0.6, 0.4))
dat$group <- ifelse(samplecar %in% seq(1, nrow(cars)), "Group A", "Group B")

# Example 1: R Model Syntax
res1 <- proc_reg(dat, model = dist ~ speed)

# View Results
res1
#   MODEL TYPE DEPVAR      RMSE Intercept    speed dist
# 1 MODEL1 PARMS   dist 15.37959 -17.57909 3.932409   -1

# Example 2: SAS Model Syntax
res2 <- proc_reg(dat, model = "dist = speed")

# View Results
res2
#   MODEL TYPE DEPVAR      RMSE Intercept    speed dist
# 1 MODEL1 PARMS   dist 15.37959 -17.57909 3.932409   -1

# Example 3: Report Output
res3 <- proc_reg(dat, model = dist ~ speed, output = report)

# View Results
res3
# $NObs
#
#           LABEL NOBS
# 1 Number of Observations Read   50
# 2 Number of Observations Used   50
#
# $ANOVA
#
#           LABEL DF      SUMSQ      MEANSQ      FVAL      PROBF
# 1           Model  1 21185.46 21185.4589 89.56711 1.489919e-12
# 2           Error 48 11353.52  236.5317      NA      NA
# 3 Corrected Total 49 32538.98      NA      NA      NA
#
# $FitStatistics
# RMSE DEPMEAN COEFVAR      RSQ      ADJRSQ
# 1 15.37959   42.98 35.78312 0.6510794 0.6438102
#
# $ParameterEstimates
#
#           PARM DF      EST      STDERR      T      PROBT
# 1 Intercept  1 -17.579095 6.7584402 -2.601058 1.231882e-02
```

```
# 2      speed  1      3.932409 0.4155128  9.463990 1.489919e-12

# Example 4: By variable
res4 <- proc_reg(dat, model = dist ~ speed, by = group)

# View Results
res4
#      BY  MODEL  TYPE DEPVAR      RMSE  Intercept      speed dist
# 1 Group A MODEL1 PARMS   dist 15.35049 -24.888326 4.275357  -1
# 2 Group B MODEL1 PARMS   dist 15.53676  -8.705547 3.484381  -1

# Example 5: "tableout" Option
res5 <- proc_reg(dat, model = dist ~ speed, options = tableout)

# View Results
res5
#      MODEL  TYPE DEPVAR      RMSE  Intercept      speed dist
# 1 MODEL1  PARMS   dist 15.37959 -17.57909489 3.932409e+00  -1
# 2 MODEL1 STDERR   dist 15.37959   6.75844017 4.155128e-01  NA
# 3 MODEL1      T    dist 15.37959  -2.60105800 9.463990e+00  NA
# 4 MODEL1 PVALUE   dist 15.37959   0.01231882 1.489919e-12  NA
# 5 MODEL1  L95B    dist 15.37959 -31.16784960 3.096964e+00  NA
# 6 MODEL1  U95B    dist 15.37959  -3.99034018 4.767853e+00  NA

# Example 6: Multiple Models plus Statistics Keywords
res6 <- proc_reg(dat, model = list(mod1 = dist ~ speed,
                                   mod2 = speed ~ dist),
                 stats = v(press, seb))

# View Results
res6
#      MODEL  TYPE DEPVAR      RMSE  PRESS  Intercept      speed      dist
# 1 mod1  PARMS   dist 15.379587 12320.2708 -17.5790949  3.9324088 -1.00000000
# 2 mod1  SEB    dist 15.379587      NA    6.7584402   0.4155128 -1.00000000
# 3 mod2  PARMS  speed  3.155753   526.2665  8.2839056 -1.00000000  0.16556757
# 4 mod2  SEB    speed  3.155753      NA    0.8743845 -1.00000000  0.01749448
```

proc_sort

Sorts a dataset

Description

The `proc_sort` function sorts a dataset according to the variables passed on the `by` parameter. If no parameters are passed on the `by` parameter, it will sort by all variables. The direction of the sort is controlled with the `order` parameter. Use the `nodupkey` option to eliminate duplicate rows from the dataset, and the `keep` parameter to subset columns. The parameters will accept either quoted or unquoted values.

Usage

```
proc_sort(
  data,
  by = NULL,
  keep = NULL,
  order = "ascending",
  options = NULL,
  as.character = FALSE
)
```

Arguments

data	The input data to sort.
by	A vector of variables to sort by.
keep	A vector of variables on the output data to keep. All other variables will be dropped.
order	The sort order of the variables on the by parameter. Valid values are 'ascending' or 'descending'. These values may also be abbreviated to 'asc', 'desc', 'a', or 'd'. You may pass a vector of order values equal to the number of variables on the by parameter. Default is 'ascending' for all by variables.
options	Any options desired for the sort. Available options are 'dupkey' and 'nodupkey'. The 'nodupkey' option removes duplicate rows from the sorted dataset. The 'dupkey' option removes unique rows from the sorted dataset.
as.character	If TRUE, will cast any factors in the 'by' parameter to character. Default is FALSE. This parameter is included because it is common to use factors for sorting in R, but you may not want to keep the variable as a factor. This parameter therefore allows you to use the factor for the sort, but then convert back to a character once the sort is complete.

Value

The sorted dataset. If a data frame was input, a data frame will be output. If a tibble was input, a tibble will be output.

Options

Below are the available options for the `proc_sort` function:

- **dupkey**: This option keeps duplicate rows and discards unique rows. Duplicate rows will be identified by the key variables listed on the `by` parameter if passed. This option is the opposite of 'nodupkey'.
- **nodupkey**: Removes duplicate rows following the sort. Duplicate rows will be identified by the key variables listed on the `by` parameter if passed. Otherwise, the function will dedupe on all variables returned.

Examples

```
# Prepare data subset
dat <- data.frame(HairEyeColor, stringsAsFactors = FALSE)[1:32 %% 4 == 1, ]

# View data
dat
#      Hair   Eye   Sex Freq
# 1  Black Brown  Male   32
# 5  Black  Blue  Male   11
# 9  Black Hazel  Male   10
# 13 Black Green  Male    3
# 17 Black Brown Female  36
# 21 Black  Blue Female   9
# 25 Black Hazel Female   5
# 29 Black Green Female   2

# Sort by Frequency
res1 <- proc_sort(dat, by = Freq)

# View results
res1
#      Hair   Eye   Sex Freq
# 29 Black Green Female    2
# 13 Black Green  Male    3
# 25 Black Hazel Female    5
# 21 Black  Blue Female    9
# 9  Black Hazel  Male   10
# 5  Black  Blue  Male   11
# 1  Black Brown  Male   32
# 17 Black Brown Female  36

# Sort by Frequency descending
res2 <- proc_sort(dat, by = Freq, order = d)

# View results
res2
#      Hair   Eye   Sex Freq
# 17 Black Brown Female  36
# 1  Black Brown  Male   32
# 5  Black  Blue  Male   11
# 9  Black Hazel  Male   10
# 21 Black  Blue Female    9
# 25 Black Hazel Female    5
# 13 Black Green  Male    3
# 29 Black Green Female    2

# Get unique combinations of Eye and Sex
res3 <- proc_sort(dat, keep = v(Eye, Sex), options = nodupkey)

# View results
res3
#      Eye   Sex
```

```
# 1 Brown Male
# 17 Brown Female
# 5 Blue Male
# 21 Blue Female
# 9 Hazel Male
# 25 Hazel Female
# 13 Green Male
# 29 Green Female
```

proc_transpose

Transposes a Dataset

Description

A function to pivot or transpose a data frame. In the default usage, the variables identified by the parameter `var` are transposed to become rows. The variable values in the parameter `id` become the new columns. The function has several more parameters to control how variables are named in the transposed data set. Parameters will accept quoted or unquoted values.

Usage

```
proc_transpose(
  data,
  by = NULL,
  var = NULL,
  id = NULL,
  idlabel = NULL,
  copy = NULL,
  name = "NAME",
  namelabel = NULL,
  prefix = NULL,
  delimiter = ".",
  suffix = NULL,
  where = NULL,
  options = NULL,
  log = TRUE
)
```

Arguments

<code>data</code>	The input data to transpose.
<code>by</code>	An optional by group. Parameter accepts a vector of one or more quoted variable names. If the by group is requested, the data will be subset by that variable and the transpose function will transpose each group and stack them together in a single table.
<code>var</code>	The variable or variables to transpose. Parameter accepts a vector of variable names. By default, all numeric variables will be transposed.

id	The variable or variables to use for the transposed column names.
idlabel	The variable to use for the transposed column labels.
copy	A vector of variables to retain in the output data without transposition. Values will be truncated or recycled to fit the number of output rows.
name	Specifies the name of the variable to be used for the var values.
namelabel	The label to use for the name variable.
prefix	Contains a prefix to be used in the construction of column names.
delimiter	Specifies a delimiter to be used in the construction of column names.
suffix	Contains a suffix to be used in the construction of column names.
where	An expression to filter the rows after the transform is complete. Use the expression function to define the where clause.
options	Optional keywords that affect the transpose. Default is NULL. Available option is "noname" which drops the name column from the output dataset.
log	Whether or not to log the procedure. Default is TRUE. This parameter is used internally.

Details

The `proc_transpose` function takes an input data frame or tibble and transposes the columns and rows. If no parameters are specified, the function will assign all numeric variables to the `var` parameter. These variables will become rows, and generic column names ("COL1", "COL2", etc.) will be generated. Other variables will be dropped.

There are several parameters to control how new column names are constructed. If the desired column names already exist in your data, identify them on the `id` parameter. The function will then use those data values unaltered. The label for these new columns can also be constructed from data values using the `idlabel` parameter.

The `name` and `namelabel` parameter are used to control the name of the column created for the `var` values. If this parameter is not passed, the column will be called "NAME", and no label will be assigned.

You may group the transposed values using the `by` parameter. This parameter accepts one or more variable names to use for grouping. If this parameter is used, the function will first subset the data by the unique combination of `by` variables, transpose each subset, and then combine the result into a single output dataset. The `by` group variables will be named on the output dataset with a generic name ("BY1", "BY2", etc.).

The `copy` parameter is used to simply copy columns from the input dataset to the transposed dataset. If necessary, these values will be recycled or truncated to fit the number of output rows. Any input variables not included in the `var`, `id`, or `copy` parameter will be dropped.

Once the transpose is complete, you may wish to filter the output data. Filtering can be accomplished using the `where` parameter. This parameter takes an expression using the `expression` function. The expression is constructed using standard R logical operators. Variable names do not need to be quoted.

The `prefix`, `delimiter`, and `suffix` parameter are used to control how generic column names are constructed. These parameters are especially useful when there are multiple `var` variables.

Value

The transposed dataset. If a data frame is input, a data frame will be output. If a tibble is input, a tibble will be output.

Examples

```
# Prepare data
dat <- data.frame(CAT = rownames(USPersonalExpenditure),
                  USPersonalExpenditure, stringsAsFactors = FALSE,
                  row.names = NULL)[1:4, ]

# View data
dat
#           CAT X1940 X1945 X1950 X1955 X1960
# 1 Food and Tobacco 22.20 44.50 59.60  73.2  86.8
# 2 Household Operation 10.50 15.50 29.00  36.5  46.2
# 3 Medical and Health  3.53  5.76  9.71  14.0  21.1
# 4 Personal Care  1.04  1.98  2.45   3.4   5.4

# Default transpose
tdat1 <- proc_transpose(dat)

# View results
tdat1
#   NAME COL1 COL2 COL3 COL4
# 1 X1940 22.2 10.5  3.53 1.04
# 2 X1945 44.5 15.5  5.76 1.98
# 3 X1950 59.6 29.0  9.71 2.45
# 4 X1955 73.2 36.5 14.00 3.40
# 5 X1960 86.8 46.2 21.10 5.40

# Transpose with ID and Name
tdat2 <- proc_transpose(dat, id = CAT, name = Year)

# View results
tdat2
#   Year Food and Tobacco Household Operation Medical and Health Personal Care
# 1 X1940                22.2                10.5                3.53                1.04
# 2 X1945                44.5                15.5                5.76                1.98
# 3 X1950                59.6                29.0                9.71                2.45
# 4 X1955                73.2                36.5               14.00                3.40
# 5 X1960                86.8                46.2               21.10                5.40

# Transpose only some of the variables
tdat3 <- proc_transpose(dat, var = v(X1940, X1950, X1960), id = CAT, name = Year)

# View results
tdat3
#   Year Food and Tobacco Household Operation Medical and Health Personal Care
# 1 X1940                22.2                10.5                3.53                1.04
# 2 X1950                59.6                29.0                9.71                2.45
# 3 X1960                86.8                46.2               21.10                5.40
```

```
# By with a where clause
tdata4 <- proc_transpose(dat, by = CAT, name = Year,
                        where = expression(Year %in% c("X1940", "X1950", "X1960")))

# View Results
tdata4
#           CAT Year COL1
# 1 Food and Tobacco X1940 22.20
# 2 Food and Tobacco X1950 59.60
# 3 Food and Tobacco X1960 86.80
# 4 Household Operation X1940 10.50
# 5 Household Operation X1950 29.00
# 6 Household Operation X1960 46.20
# 7 Medical and Health X1940 3.53
# 8 Medical and Health X1950 9.71
# 9 Medical and Health X1960 21.10
# 10 Personal Care X1940 1.04
# 11 Personal Care X1950 2.45
# 12 Personal Care X1960 5.40
```

proc_ttest

Calculates T-Test Statistics

Description

The `proc_ttest` function generates T-Test statistics for selected variables on the input dataset. The variables are identified on the `var` parameter or the `paired` parameter. The function will calculate a standard set of T-Test statistics. Results are displayed in the viewer interactively and returned from the function.

Usage

```
proc_ttest(
  data,
  var = NULL,
  paired = NULL,
  output = NULL,
  by = NULL,
  class = NULL,
  options = NULL,
  titles = NULL
)
```

Arguments

`data` The input data frame for which to calculate summary statistics. This parameter is required.

var	The variable or variables to be used for hypothesis testing. Pass the variable names in a quoted vector, or an unquoted vector using the <code>v()</code> function. If there is only one variable, it may be passed unquoted. If the <code>class</code> variable is specified, the function will compare the two groups identified in the <code>class</code> variable. If the <code>class</code> variable is not specified, enter the baseline hypothesis value on the <code>"h0"</code> option. Default <code>"h0"</code> value is zero (0).
paired	A vector of paired variables to perform a paired T-Test on. Variables should be separated by a star (*). The entire string should be quoted, for example, <code>paired = "var1 * var2"</code> . To test multiple pairs, place the pairs in a quoted vector : <code>paired = c("var1 * var2", "var3 * var4")</code> . The parameter does not accept parenthesis, hyphens, or any other shortcut syntax.
output	Whether or not to return datasets from the function. Valid values are <code>"out"</code> , <code>"none"</code> , and <code>"report"</code> . Default is <code>"out"</code> , and will produce dataset output specifically designed for programmatic use. The <code>"none"</code> option will return a NULL instead of a dataset or list of datasets. The <code>"report"</code> keyword returns the datasets from the interactive report, which may be different from the standard output. The output parameter also accepts data shaping keywords <code>"long"</code> , <code>"stacked"</code> , and <code>"wide"</code> . These shaping keywords control the structure of the output data. See the Data Shaping section for additional details. Note that multiple output keywords may be passed on a character vector. For example, to produce both a report dataset and a <code>"long"</code> output dataset, use the parameter <code>output = c("report", "out", "long")</code> .
by	An optional by group. If you specify a by group, the input data will be subset on the by variable(s) prior to performing any statistics.
class	The <code>class</code> parameter is used to perform a unpaired T-Test between two different groups of the same variable. For example, if you want to test for a significant difference between a control group and a test group, where the control and test groups are in rows identified by a variable <code>"Group"</code> . Note that there can only be two different values on the <code>class</code> variable. Also, the analysis is restricted to only one <code>class</code> variable.
options	A vector of optional keywords. Valid values are: <code>"alpha ="</code> , <code>"h0 ="</code> , and <code>"no-print"</code> . The <code>"alpha ="</code> option will set the alpha value for confidence limit statistics. The default is 95% (<code>alpha = 0.05</code>). The <code>"h0 ="</code> option sets the baseline hypothesis value for single-variable hypothesis testing. The <code>"no-print"</code> option turns off the interactive report.
titles	A vector of one or more titles to use for the report output.

Details

The `proc_ttest` function is for performing hypothesis testing. Data is passed in on the `data` parameter. The function can segregate data into groups using the `by` parameter. There are also options to determine whether and what results are returned.

The `proc_ttest` function allows for three types of analysis:

- **One Sample:** The one sample test allows you to perform significance testing of a single variable against a known baseline value or null hypothesis. To perform this test, pass the variable name on the `var` parameter and the baseline on the `h0=` option. The one sample T-Test performs a classic Student's T-Test and assumes your data has a normal distribution.

- **Paired Comparison:** The paired comparison is for tests of two variables with a natural pairing and the same number of observations for both measures. For instance, if you are checking for a change in blood pressure for the same group of patients at different time points. To perform a paired comparison, use the `paired` parameter with the two variables separated by a star (*). The paired T-Test performs a classic Student's T-Test and assumes your data has a normal distribution.
- **Two Independent Samples:** The analysis of two independent samples is used when there is no natural pairing, and there may be a different number of observations in each group. This method is used, for example, if you are comparing the effectiveness of a treatment between two different groups of patients. The function assumes that there is a single variable that contains the analysis values for both groups, and another variable to identify the groups. To perform this analysis, pass the target variable name on the `var` parameter, and the grouping variable on the `class` parameter. The Two Sample T-Test provides both a Student's T-Test and a Welch-Satterthwaite T-Test. Select the appropriate T-Test results for your data based on the known normality.

Value

Normally, the requested T-Test statistics are shown interactively in the viewer, and output results are returned as a list of data frames. You may then access individual datasets from the list using dollar sign (\$) syntax. The interactive report can be turned off using the "noprint" option, and the output datasets can be turned off using the "none" keyword on the output parameter.

Interactive Output

By default, `proc_ttest` results will be sent to the viewer as an HTML report. This functionality makes it easy to get a quick analysis of your data. To turn off the interactive report, pass the "noprint" keyword to the options parameter.

The `titles` parameter allows you to set one or more titles for your report. Pass these titles as a vector of strings.

The exact datasets used for the interactive report can be returned as a list. To return these datasets, pass the "report" keyword on the output parameter. This list may in turn be passed to `proc_print` to write the report to a file.

Dataset Output

Dataset results are also returned from the function by default. `proc_ttest` typically returns multiple datasets in a list. Each dataset will be named according to the category of statistical results. There are three standard categories: "Statistics", "ConfLimits", and "TTests". For the class style analysis, the function also returns a dataset called "Equality" that shows the Folded F analysis.

The output datasets generated are optimized for data manipulation. The column names have been standardized, and additional variables may be present to help with data manipulation. For example, the `by` variable will always be named "BY". In addition, data values in the output datasets are intentionally not rounded or formatted to give you the most accurate numeric results.

Options

The `proc_ttest` function recognizes the following options. Options may be passed as a quoted vector of strings, or an unquoted vector using the `v()` function.

- **alpha = :** The "alpha =" option will set the alpha value for confidence limit statistics. Set the alpha as a decimal value between 0 and 1. For example, you can set a 90% confidence limit as `alpha = 0.1`.
- **h0:** The "h0 =" option is used to set the baseline mean value for testing a single variable. Pass the option as a name/value pair, such as `h0 = 95`.
- **noprint:** Whether to print the interactive report to the viewer. By default, the report is printed to the viewer. The "noprint" option will inhibit printing. You may inhibit printing globally by setting the package print option to false: `options("procs.print" = FALSE)`.

Data Shaping

The output datasets produced by the function can be shaped in different ways. These shaping options allow you to decide whether the data should be returned long and skinny, or short and wide. The shaping options can reduce the amount of data manipulation necessary to get the data into the desired form. The shaping options are as follows:

- **long:** Transposes the output datasets so that statistics are in rows and variables are in columns.
- **stacked:** Requests that output datasets be returned in "stacked" form, such that both statistics and variables are in rows.
- **wide:** Requests that output datasets be returned in "wide" form, such that statistics are across the top in columns, and variables are in rows. This shaping option is the default.

These shaping options are passed on the output parameter. For example, to return the data in "long" form, use `output = "long"`.

Examples

```
# Turn off printing for CRAN checks
options("procs.print" = FALSE)

# Prepare sample data
dat1 <- subset(sleep, group == 1, c("ID", "extra"))
dat2 <- subset(sleep, group == 2, c("ID", "extra"))
dat <- data.frame(ID = dat1$ID, group1 = dat1$extra, group2 = dat2$extra)

# View sample data
dat
#   ID group1 group2
# 1  1    0.7    1.9
# 2  2   -1.6    0.8
# 3  3   -0.2    1.1
# 4  4   -1.2    0.1
# 5  5   -0.1   -0.1
# 6  6    3.4    4.4
# 7  7    3.7    5.5
# 8  8    0.8    1.6
# 9  9    0.0    4.6
# 10 10    2.0    3.4

# Example 1: T-Test using h0 option
```

```

res1 <- proc_ttest(dat, var = "group1", options = c("h0" = 0))

# View results
res1
# $Statistics
#      VAR  N MEAN      STD      STDERR  MIN MAX
# 1 group1 10 0.75 1.78901 0.5657345 -1.6 3.7
#
# $ConFLimits
#      VAR MEAN      LCLM      UCLM      STD
# 1 group1 0.75 -0.5297804 2.02978 1.78901
#
# $TTests
#      VAR DF      T      PROBT
# 1 group1  9 1.32571 0.2175978

# Example 2: T-Test using paired parameter
res2 <- proc_ttest(dat, paired = "group2 * group1")

# View results
res2
# $Statistics
#      VAR1  VAR2      DIFF  N MEAN      STD      STDERR  MIN MAX
# 1 group2 group1 group2-group1 10 1.58 1.229995 0.3889587  0 4.6
#
# $ConFLimits
#      VAR1  VAR2      DIFF MEAN      LCLM      UCLM      STD  LCLMSTD  UCLMSTD
# 1 group2 group1 group2-group1 1.58 0.7001142 2.459886 1.229995 0.8460342 2.245492
#
# $TTests
#      VAR1  VAR2      DIFF DF      T      PROBT
# 1 group2 group1 group2-group1  9 4.062128 0.00283289

# Example 3: T-Test using class parameter
res3 <- proc_ttest(sleep, var = "extra", class = "group")

# View results
res3
# $Statistics
#      VAR      CLASS      METHOD  N MEAN      STD      STDERR  MIN MAX
# 1 extra          1      <NA> 10 0.75 1.789010 0.5657345 -1.6 3.7
# 2 extra          2      <NA> 10 2.33 2.002249 0.6331666 -0.1 5.5
# 3 extra Diff (1-2)      Pooled NA -1.58      NA 0.8490910  NA  NA
# 4 extra Diff (1-2) Satterthwaite NA -1.58      NA 0.8490910  NA  NA
#
# $ConFLimits
#      VAR      CLASS      METHOD MEAN      LCLM      UCLM      STD  LCLMSTD  UCLMSTD
# 1 extra          1      <NA> 0.75 -0.5297804 2.0297804 1.789010 1.230544 3.266034
# 2 extra          2      <NA> 2.33 0.8976775 3.7623225 2.002249 1.377217 3.655326
# 3 extra Diff (1-2)      Pooled -1.58 -3.3638740 0.2038740      NA      NA      NA
# 4 extra Diff (1-2) Satterthwaite -1.58 -3.3654832 0.2054832      NA      NA      NA
#
# $TTests

```

```

#      VAR      METHOD  VARIANCES      DF      T      PROBT
# 1 extra      Pooled      Equal 18.00000 -1.860813 0.07918671
# 2 extra Satterthwaite  Unequal 17.77647 -1.860813 0.07939414
#
# $Equality
#      VAR      METHOD  NDF DDF      FVAL      PROBF
# 1 extra Folded F    9    9 1.252595 0.7427199

# Example 4: T-Test using alpha option and by variable
res4 <- proc_ttest(sleep, var = "extra", by = "group", options = c(alpha = 0.1))

# View results
res4
# $Statistics
#   BY   VAR  N MEAN      STD      STDERR  MIN MAX
# 1   1 extra 10 0.75 1.789010 0.5657345 -1.6 3.7
# 2   2 extra 10 2.33 2.002249 0.6331666 -0.1 5.5
#
# $ConFLimits
# BY   VAR MEAN      LCLM      UCLM      STD  LCLMSTD  UCLMSTD
# 1   1 extra 0.75 -0.2870553 1.787055 1.789010 1.304809 2.943274
# 2   2 extra 2.33  1.1693340 3.490666 2.002249 1.460334 3.294095
#
# $TTests
#   BY   VAR DF      T      PROBT
# 1   1 extra  9 1.325710 0.217597780
# 2   2 extra  9 3.679916 0.005076133

# Example 5: Single variable T-Test using "long" shaping option
res5 <- proc_ttest(sleep, var = "extra", output = "long")

# View results
res5
# $Statistics
#      STAT      extra
# 1      N 20.0000000
# 2  MEAN  1.5400000
# 3   STD  2.0179197
# 4 STDERR  0.4512206
# 5   MIN -1.6000000
# 6   MAX  5.5000000
#
# $ConFLimits
#      STAT      extra
# 1  MEAN  1.5400000
# 2  LCLM  0.5955845
# 3  UCLM  2.4844155
# 4   STD  2.0179197
# 5 LCLMSTD 1.5346086
# 6 UCLMSTD 2.9473163
#
# $TTests
#      STAT      extra

```



```
# 1    DF 19.00000000
# 2     T  3.41296500
# 3 PROBT 0.00291762
```

Index

create_style, [15](#)

expression, [25](#)

proc_freq, [2](#)

proc_means, [6](#), [9](#)

proc_print, [3](#), [10](#), [14](#), [17](#), [29](#)

proc_reg, [15](#)

proc_sort, [21](#)

proc_transpose, [6](#), [24](#)

proc_ttest, [27](#)

v, [16](#)