

Package ‘formatdown’

July 22, 2025

Title Formatting Numbers in 'rmarkdown' Documents

Version 0.1.4

Language en-US

Description Provides a small set of tools for formatting numbers in R-markdown documents. Convert a numerical vector to character strings in power-of-ten form, decimal form, or measurement-units form; all are math-delimited for rendering as inline equations. Can also convert text into math-delimited text to match the font face and size of math-delimited numbers. Useful for rendering single numbers in inline R code chunks and for rendering columns in tables.

Depends R (>= 3.5.0)

License MIT + file LICENSE

Encoding UTF-8

LazyData TRUE

LazyDataCompression bzip2

RoxygenNote 7.2.3

Imports checkmate, data.table, settings, units, wrapr

Suggests covr, knitr, rmarkdown, tinytest

VignetteBuilder knitr

URL <https://github.com/graphdr/formatdown/>,
<https://graphdr.github.io/formatdown/>,
<https://CRAN.R-project.org/package=formatdown>

BugReports <https://github.com/graphdr/formatdown/issues>

Collate 'data.R' 'format_decimal.R' 'format_numbers.R'
'format_power.R' 'format_text.R' 'format_units.R'
'formatdown_options.R' 'formatdown-deprecated.R'
'formatdown-package.R' 'roxygen.R' 'utils.R'

NeedsCompilation no

Author Richard Layton [aut, cre]

Maintainer Richard Layton <graphdoctor@gmail.com>
Repository CRAN
Date/Publication 2024-05-07 23:20:02 UTC

Contents

air_meas	2
atmos	3
formatdown_options	3
format_dcml	6
format_engr	9
format_numbers	12
format_sci	16
format_text	19
metals	20
water	21
Index	22

air_meas	<i>Air density measurements</i>
----------	---------------------------------

Description

Table of air properties at room temperature and pressure, simulating multiple measurements at approximately steady state,

Usage

```
data(air_meas, package = "formatdown")
```

Format

- Classes data.table and data.frame: 5 observations of 7 variables:
- date** "Date" class format "YYYY-MM-DD".
 - trial** Character, label "a" through "e".
 - humid** Factor, humidity, "low", "med", or "high."
 - temp** Numeric, measured temperature (K).
 - pres** Numeric, measured atmospheric pressure (Pa).
 - sp_gas** Numeric, specific gas constant in mass form R_{sp} , ideal gas reference value, (J kg⁻¹K⁻¹).
 - dens** Numeric, calculated air density $\rho = pR_{sp}^{-1}T^{-1}$ (kg m⁻³).

atmos	<i>Properties of standard atmosphere</i>
-------	--

Description

Table of atmospheric properties as a function of altitude, sea level to 1000 km.

Usage

```
data(atmos, package = "formatdown")
```

Format

Classes data.table and data.frame: 9 observations of 5 variables:

alt Numeric, altitude (km)

temp Numeric, air temperature (K)

pres Numeric, atmospheric pressure (Pa)

dens Numeric, air density (kg m^{-3})

sound Numeric, speed of sound (m/s)

Source

Marks' Standard Handbook for Mechanical Engineers 9/e (1987) E.A. Avallone and T. Baumeister (ed.), "Table 4.2.2 International Standard Atmosphere", pp. 4-38, McGraw-Hill, NY.

formatdown_options	<i>Get and set function arguments via options</i>
--------------------	---

Description

Changes the default values of function arguments which affect the markup and appearance of formatdown results.

Usage

```
formatdown_options(..., reset = FALSE)
```

Arguments

...	One or more name = value pairs to set values; or one or more quoted option names to get values.
reset	Logical vector of length 1; if TRUE, reset all options to their default values.

Details

Global options are provided for arguments that users would likely prefer to set once in a document instead of repeating in every function call. For example, some users prefer a comma decimal marker (",") throughout a document.

Globally-set arguments can be overridden locally by assigning them in a function call.

The arguments that can be set with this function are as follows:

- `delim`: Character, length 1 or 2, to define the left and right math markup delimiters. The default setting, `delim = "$"`, produces left and right delimiters $\$. \dots \$$. The alternate built-in setting, `delim = "\("`, produces left and right delimiters $\backslash(\dots \backslash)$. Custom delimiters can be assigned in a vector of length 2 with left and right delimiter symbols, e.g., `c("\[" , "\]")`. Special characters typically must be escaped.
- `size`: Character, length 1, to assign a font size. If not empty, adds a font size macro to the markup inside the math delimiters. Possible values are "scriptsize", "small", "normalsize", "large", and "huge". One may also assign the equivalent LaTeX-style markup itself, e.g., `"\scriptsize"`, `"\small"`, etc. Default is NULL.
- `decimal_mark`: Character, length 1, to assign the decimal marker. Possible values are a period "." (default) or a comma ",". Passed to `formatC(decimal.mark)`.
- `big_mark`: Character, length 1, used as the mark between every `big_interval` number of digits to the left of the decimal marker to improve readability. Possible values are empty "" (default) or "thin" to produce a LaTeX-style thin, horizontal space. One may also assign the thin-space markup itself `"\\, "`. Passed to `formatC(big.mark)`.
- `big_interval`: Integer, length 1, that defines the number of digits (default 3) in groups separated by `big_mark`. Passed to `formatC(big.interval)`.
- `small_mark`: Character, length 1, used as the mark between every `small_interval` number of digits to the right of the decimal marker to improve readability. Possible values are empty "" (default) or "thin" to produce a LaTeX-style thin, horizontal space. One may also assign the thin-space markup itself `"\\, "`. Passed to `formatC(small.mark)`.
- `small_interval`: Integer, length 1, that defines the number of digits (default 5) in groups separated by `small_mark`. Passed to `formatC(small.interval)`.
- `whitespace`: Character, length 1, to define the LaTeX-style math-mode macro to preserve a horizontal space between words of text or between physical-unit abbreviations when formatting numbers of class "units". Default is `"\\> "`. Alternatives include `"\\: "` or `"\\ "`.

Value

Nothing; used for its side-effect.

Examples

```
# Show all options
formatdown_options()

# Store existing settings, including any changes made by the user
old_settings <- formatdown_options()
```

```
# View one option
formatdown_options()$delim

# View multiple options
formatdown_options("size", "delim")

# Change options
formatdown_options(size = "small", delim = "\\(")
formatdown_options("size", "delim")

# Reset to default values
formatdown_options(reset = TRUE)
formatdown_options("size", "delim")

# Reset options to those before this example was run
do.call(formatdown_options, old_settings)

# Option effects

# delim
x <- 101300
format_dcml(x)
format_dcml(x, delim = "\\(")

# size
format_dcml(x, size = "small")
format_dcml(x, size = "\\small")

# decimal_mark
y <- 6.02214076E+10
format_sci(y, 5, decimal_mark = ".")
format_sci(y, 5, decimal_mark = ",")

# big_mark
format_dcml(y, 9)
format_dcml(y, 9, big_mark = "thin")
format_dcml(y, 9, big_mark = "\\\\\",")

# big_interval
format_dcml(y, 9, big_mark = "thin", big_interval = 3)
format_dcml(y, 9, big_mark = "thin", big_interval = 5)

# small_mark
z <- 1.602176634e-8
format_sci(z, 10)
format_sci(z, 10, small_mark = "thin")
format_sci(z, 10, small_mark = "\\\\\",")
format_engr(z, 10, small_mark = "thin")

# small_interval
format_sci(z, 10, small_mark = "thin", small_interval = 3)
format_sci(z, 10, small_mark = "thin", small_interval = 5)
format_engr(z, 10, small_mark = "thin", small_interval = 5)
```

```
# whitespace in text
p <- "Hello world!"
format_text(p, whitespace = "\\:\\:")

# whitespace in physical units expression
x <- pi
units(x) <- "m/s"
format_dcml(x, whitespace = "\\:\\:")
```

format_dcml

Format decimal notation

Description

Convert a numeric vector to a character vector in which the numbers are formatted in decimal form and delimited for rendering as inline equations in an R markdown document.

Usage

```
format_dcml(
  x,
  digits = 4,
  ...,
  delim = formatdown_options("delim"),
  size = formatdown_options("size"),
  decimal_mark = formatdown_options("decimal_mark"),
  big_mark = formatdown_options("big_mark"),
  big_interval = formatdown_options("big_interval"),
  small_mark = formatdown_options("small_mark"),
  small_interval = formatdown_options("small_interval"),
  whitespace = formatdown_options("whitespace")
)
```

Arguments

<code>x</code>	Number or numbers to be formatted. Can be a single number, a vector, or a column of a data frame.
<code>digits</code>	Integer from 1 through 20 that controls the number of significant digits in printed numeric values. Passed to <code>signif()</code> . Default is 4.
<code>...</code>	Not used for values; forces subsequent arguments to be referable only by name.
<code>delim</code>	Character, length 1 or 2, to define the left and right math markup delimiters. The default setting, <code>delim = "\$"</code> , produces left and right delimiters $\$ \dots \$$. The alternate built-in setting, <code>delim = "\("</code> , produces left and right delimiters $\backslash (\dots \backslash)$. Custom delimiters can be assigned in a vector of length 2 with left and right delimiter symbols, e.g., <code>c("\["</code> , <code>"]\)"</code>). Special characters typically must be escaped.

size	Character, length 1, to assign a font size. If not empty, adds a font size macro to the markup inside the math delimiters. Possible values are "scriptsize", "small", "normalsize", "large", and "huge". One may also assign the equivalent LaTeX-style markup itself, e.g., "\scriptsize", "\small", etc. Default is NULL.
decimal_mark	Character, length 1, to assign the decimal marker. Possible values are a period "." (default) or a comma ",". Passed to formatC(decimal.mark).
big_mark	Character, length 1, used as the mark between every big_interval number of digits to the left of the decimal marker to improve readability. Possible values are empty "" (default) or "thin" to produce a LaTeX-style thin, horizontal space. One may also assign the thin-space markup itself "\\\", ". Passed to formatC(big.mark).
big_interval	Integer, length 1, that defines the number of digits (default 3) in groups separated by big_mark. Passed to formatC(big.interval).
small_mark	Character, length 1, used as the mark between every small_interval number of digits to the right of the decimal marker to improve readability. Possible values are empty "" (default) or "thin" to produce a LaTeX-style thin, horizontal space. One may also assign the thin-space markup itself "\\\", ". Passed to formatC(small.mark).
small_interval	Integer, length 1, that defines the number of digits (default 5) in groups separated by small_mark. Passed to formatC(small.interval).
whitespace	Character, length 1, to define the LaTeX-style math-mode macro to preserve a horizontal space between words of text or between physical-unit abbreviations when formatting numbers of class "units". Default is "\\\>". Alternatives include "\\\: " or "\\\ \".

Details

format_dcml() is a wrapper for the more general function format_numbers(). Where defaults are defined by formatdown_options(), users may reassign the arguments locally in the function call or globally using formatdown_options().

Arguments after the dots (...) must be referred to by name.

Value

A character vector in which numbers are formatted in decimal form and delimited for rendering as inline equations in an R markdown document.

See Also

Other format_*: [format_engr\(\)](#), [format_numbers\(\)](#), [format_sci\(\)](#), [format_text\(\)](#)

Examples

```
# input: single number
x <- 6.0221E+23
format_numbers(x)
```

```

# input: units class
x <- 103400
units(x) <- "N m2 C-2"
format_numbers(x)

# input: vector
data("metals", package = "formatdown")
x <- metals$dens
format_numbers(x)

# significant digits
x <- 9.75358e+5
format_numbers(x, 2)
format_numbers(x, 3)
format_numbers(x, 4)

# format & wrappers: format_engr(), format_sci(), format_dcml()
x <- 6.0221E+23
format_numbers(x, format = "engr")
format_engr(x)

format_numbers(x, format = "sci")
format_sci(x)

x <- 103400
format_numbers(x, format = "dcml")
format_dcml(x)

# input: data frame
x <- metals[, c("thrm_exp", "thrm_cond")]
as.data.frame(apply(x, 2, format_sci, digits = 3))

# omit_power
x <- 103400
format_sci(x, omit_power = c(-1, 2)) # default
format_sci(x, omit_power = c(-1, 5))
format_sci(x, omit_power = 5) # equivalent to omit_power = c(5, 5)
x <- 1.2
format_sci(x, omit_power = NULL)

# set_power
format_sci(x, set_power = NULL) # default
format_sci(x, set_power = 3)

# set_power overrides format
x <- 6.0221E+23
format_engr(x)
format_engr(x, set_power = 24L)
format_sci(x)
format_sci(x, set_power = 24L)

# set_power overrides omit_power
x <- 101300

```

```

format_sci(x, omit_power = 5)
format_sci(x, omit_power = 5, set_power = 2)
format_sci(x, omit_power = 2)
format_sci(x, omit_power = 2, set_power = 2)

# decimal format ignores set_power
x <- 103400
format_numbers(x, format = "dcml")
format_numbers(x, format = "dcml", set_power = 3)

```

format_engr

Format engineering notation

Description

Convert a numeric vector to a character vector in which the numbers are formatted in power-of-ten notation in engineering form and delimited for rendering as inline equations in an R markdown document.

Usage

```

format_engr(
  x,
  digits = 4,
  ...,
  omit_power = c(-1, 2),
  set_power = NULL,
  delim = formatdown_options("delim"),
  size = formatdown_options("size"),
  decimal_mark = formatdown_options("decimal_mark"),
  small_mark = formatdown_options("small_mark"),
  small_interval = formatdown_options("small_interval"),
  whitespace = formatdown_options("whitespace")
)

```

Arguments

x	Number or numbers to be formatted. Can be a single number, a vector, or a column of a data frame.
digits	Integer from 1 through 20 that controls the number of significant digits in printed numeric values. Passed to signif(). Default is 4.
...	Not used for values; forces subsequent arguments to be referable only by name.
omit_power	Numeric vector c(p, q) with p ≤ q, specifying the range of exponents over which power-of-ten notation is omitted in either scientific or engineering format. Default is c(-1, 2). If a single value is assigned, i.e., omit_power = p, the argument is interpreted as c(p, p). If NULL or NA, all elements are formatted

	in power-of-ten notation. Argument is overridden by specifying <code>set_power</code> or decimal notation.
<code>set_power</code>	Integer, length 1. Formats all values in <code>x</code> with the same power-of-ten exponent. Default NULL. Overrides <code>format</code> and <code>omit_power</code> arguments.
<code>delim</code>	Character, length 1 or 2, to define the left and right math markup delimiters. The default setting, <code>delim = "\$"</code> , produces left and right delimiters $\$ \dots \$$. The alternate built-in setting, <code>delim = "\("</code> , produces left and right delimiters $\backslash (\dots \backslash)$. Custom delimiters can be assigned in a vector of length 2 with left and right delimiter symbols, e.g., <code>c("\[" , "\]")</code> . Special characters typically must be escaped.
<code>size</code>	Character, length 1, to assign a font size. If not empty, adds a font size macro to the markup inside the math delimiters. Possible values are <code>"scriptsize"</code> , <code>"small"</code> , <code>"normalsize"</code> , <code>"large"</code> , and <code>"huge"</code> . One may also assign the equivalent LaTeX-style markup itself, e.g., <code>"\scriptsize"</code> , <code>"\small"</code> , etc. Default is NULL.
<code>decimal_mark</code>	Character, length 1, to assign the decimal marker. Possible values are a period <code>"."</code> (default) or a comma <code>","</code> . Passed to <code>formatC(decimal.mark)</code> .
<code>small_mark</code>	Character, length 1, used as the mark between every <code>small_interval</code> number of digits to the right of the decimal marker to improve readability. Possible values are empty <code>""</code> (default) or <code>"thin"</code> to produce a LaTeX-style thin, horizontal space. One may also assign the thin-space markup itself <code>"\\,"</code> . Passed to <code>formatC(small.mark)</code> .
<code>small_interval</code>	Integer, length 1, that defines the number of digits (default 5) in groups separated by <code>small_mark</code> . Passed to <code>formatC(small.interval)</code> .
<code>whitespace</code>	Character, length 1, to define the LaTeX-style math-mode macro to preserve a horizontal space between words of text or between physical-unit abbreviations when formatting numbers of class <code>"units"</code> . Default is <code>"\\>"</code> . Alternatives include <code>"\\: "</code> or <code>"\\ " "</code> .

Details

In engineering notation, all exponents are multiples of three. `format_engr()` is a wrapper for the more general function `format_numbers()`. Where defaults are defined by `formatdown_options()`, users may reassign the arguments locally in the function call or globally using `formatdown_options()`.

Arguments after the dots (`...`) must be referred to by name.

Value

A character vector in which numbers are formatted in power-of-ten notation in engineering form and delimited for rendering as inline equations in an R markdown document.

See Also

Other `format_*`: `format_dcml()`, `format_numbers()`, `format_sci()`, `format_text()`

Examples

```
# input: single number
x <- 6.0221E+23
format_numbers(x)

# input: units class
x <- 103400
units(x) <- "N m2 C-2"
format_numbers(x)

# input: vector
data("metals", package = "formatdown")
x <- metals$dens
format_numbers(x)

# significant digits
x <- 9.75358e+5
format_numbers(x, 2)
format_numbers(x, 3)
format_numbers(x, 4)

# format & wrappers: format_engr(), format_sci(), format_dcml()
x <- 6.0221E+23
format_numbers(x, format = "engr")
format_engr(x)

format_numbers(x, format = "sci")
format_sci(x)

x <- 103400
format_numbers(x, format = "dcml")
format_dcml(x)

# input: data frame
x <- metals[, c("thrm_exp", "thrm_cond")]
as.data.frame(apply(x, 2, format_sci, digits = 3))

# omit_power
x <- 103400
format_sci(x, omit_power = c(-1, 2)) # default
format_sci(x, omit_power = c(-1, 5))
format_sci(x, omit_power = 5) # equivalent to omit_power = c(5, 5)
x <- 1.2
format_sci(x, omit_power = NULL)

# set_power
format_sci(x, set_power = NULL) # default
format_sci(x, set_power = 3)

# set_power overrides format
x <- 6.0221E+23
format_engr(x)
```

```

format_engr(x, set_power = 24L)
format_sci(x)
format_sci(x, set_power = 24L)

# set_power overrides omit_power
x <- 101300
format_sci(x, omit_power = 5)
format_sci(x, omit_power = 5, set_power = 2)
format_sci(x, omit_power = 2)
format_sci(x, omit_power = 2, set_power = 2)

# decimal format ignores set_power
x <- 103400
format_numbers(x, format = "dcml")
format_numbers(x, format = "dcml", set_power = 3)

```

format_numbers

Format numbers

Description

Convert a numeric vector to a character vector in which the numbers are formatted in power-of-ten notation in scientific or engineering form and delimited for rendering as inline equations in an R markdown document. Decimal numbers can be similarly formatted, without the power-of-ten notation.

Usage

```

format_numbers(
  x,
  digits = 4,
  format = "engr",
  ...,
  omit_power = c(-1, 2),
  set_power = NULL,
  delim = formatdown_options("delim"),
  size = formatdown_options("size"),
  decimal_mark = formatdown_options("decimal_mark"),
  big_mark = formatdown_options("big_mark"),
  big_interval = formatdown_options("big_interval"),
  small_mark = formatdown_options("small_mark"),
  small_interval = formatdown_options("small_interval"),
  whitespace = formatdown_options("whitespace")
)

```

Arguments

<code>x</code>	Number or numbers to be formatted. Can be a single number, a vector, or a column of a data frame.
<code>digits</code>	Integer from 1 through 20 that controls the number of significant digits in printed numeric values. Passed to <code>signif()</code> . Default is 4.
<code>format</code>	Character, length 1, defines the type of notation. Possible values are "engr" (default) for engineering power-of-ten notation, "sci" for scientific power-of-ten notation, and "dcm1" for decimal notation.
<code>...</code>	Not used for values; forces subsequent arguments to be referable only by name.
<code>omit_power</code>	Numeric vector <code>c(p, q)</code> with $p \leq q$, specifying the range of exponents over which power-of-ten notation is omitted in either scientific or engineering format. Default is <code>c(-1, 2)</code> . If a single value is assigned, i.e., <code>omit_power = p</code> , the argument is interpreted as <code>c(p, p)</code> . If NULL or NA, all elements are formatted in power-of-ten notation. Argument is overridden by specifying <code>set_power</code> or decimal notation.
<code>set_power</code>	Integer, length 1. Formats all values in <code>x</code> with the same power-of-ten exponent. Default NULL. Overrides <code>format</code> and <code>omit_power</code> arguments.
<code>delim</code>	Character, length 1 or 2, to define the left and right math markup delimiters. The default setting, <code>delim = "\$"</code> , produces left and right delimiters <code>\$. . \$.</code> . The alternate built-in setting, <code>delim = "\("</code> , produces left and right delimiters <code>\(. . \)</code> . Custom delimiters can be assigned in a vector of length 2 with left and right delimiter symbols, e.g., <code>c("\["</code> , <code>"\]"</code>). Special characters typically must be escaped.
<code>size</code>	Character, length 1, to assign a font size. If not empty, adds a font size macro to the markup inside the math delimiters. Possible values are "scriptsize", "small", "normalsize", "large", and "huge". One may also assign the equivalent LaTeX-style markup itself, e.g., <code>"\scriptsize"</code> , <code>"\small"</code> , etc. Default is NULL.
<code>decimal_mark</code>	Character, length 1, to assign the decimal marker. Possible values are a period <code>"."</code> (default) or a comma <code>","</code> . Passed to <code>formatC(decimal.mark)</code> .
<code>big_mark</code>	Character, length 1, used as the mark between every <code>big_interval</code> number of digits to the left of the decimal marker to improve readability. Possible values are empty <code>""</code> (default) or <code>"thin"</code> to produce a LaTeX-style thin, horizontal space. One may also assign the thin-space markup itself <code>"\\, "</code> . Passed to <code>formatC(big.mark)</code> .
<code>big_interval</code>	Integer, length 1, that defines the number of digits (default 3) in groups separated by <code>big_mark</code> . Passed to <code>formatC(big.interval)</code> .
<code>small_mark</code>	Character, length 1, used as the mark between every <code>small_interval</code> number of digits to the right of the decimal marker to improve readability. Possible values are empty <code>""</code> (default) or <code>"thin"</code> to produce a LaTeX-style thin, horizontal space. One may also assign the thin-space markup itself <code>"\\, "</code> . Passed to <code>formatC(small.mark)</code> .
<code>small_interval</code>	Integer, length 1, that defines the number of digits (default 5) in groups separated by <code>small_mark</code> . Passed to <code>formatC(small.interval)</code> .

whitespace Character, length 1, to define the LaTeX-style math-mode macro to preserve a horizontal space between words of text or between physical-unit abbreviations when formatting numbers of class "units". Default is "`\\\\\\>`". Alternatives include "`\\\\\\:`" or "`\\\\\\`".

Details

Given a number, a numerical vector, or a numerical column from a data frame, `format_numbers()` converts the numbers to character strings of the form, "`$a \\times 10^{n}$`", where `a` is the coefficient to a specified number of significant digits and `n` is the exponent. When used for decimal notation, `format_numbers()` converts numbers to character strings of the form "`$a$`".

Powers-of-ten notation is omitted over a range of exponents via `omit_power` such that numbers so specified are converted to decimal notation. For example, the default `omit_power = c(-1, 2)` formats numbers such as 0.123, 1.23, 12.3, and 123 in decimal form. To cancel these exceptions and convert all numbers to powers-of-ten notation, set the `omit_power` argument to `NULL` or `NA`.

Delimiters for inline math markup can be edited if necessary. If the default argument fails, try using "`\\(`" as an alternative. If using a custom delimiter to suit the markup environment, be sure to escape all special symbols.

When inputs are of class "units" (created with the units package), a math-text macro of the form `\\mathrm{<units_string>}` is appended to the formatted numerical value inside the math delimiters.

Arguments after the dots (`...`) must be referred to by name.

Value

A character vector in which numbers are formatted in power-of-ten or decimal notation and delimited for rendering as inline equations in an R markdown document.

See Also

Other `format_*`: [format_dcml\(\)](#), [format_engr\(\)](#), [format_sci\(\)](#), [format_text\(\)](#)

Examples

```
# input: single number
x <- 6.0221E+23
format_numbers(x)

# input: units class
x <- 103400
units(x) <- "N m2 C-2"
format_numbers(x)

# input: vector
data("metals", package = "formatdown")
x <- metals$dens
format_numbers(x)

# significant digits
```

```
x <- 9.75358e+5
format_numbers(x, 2)
format_numbers(x, 3)
format_numbers(x, 4)

# format & wrappers: format_engr(), format_sci(), format_dcml()
x <- 6.0221E+23
format_numbers(x, format = "engr")
format_engr(x)

format_numbers(x, format = "sci")
format_sci(x)

x <- 103400
format_numbers(x, format = "dcml")
format_dcml(x)

# input: data frame
x <- metals[, c("thrm_exp", "thrm_cond")]
as.data.frame(apply(x, 2, format_sci, digits = 3))

# omit_power
x <- 103400
format_sci(x, omit_power = c(-1, 2)) # default
format_sci(x, omit_power = c(-1, 5))
format_sci(x, omit_power = 5) # equivalent to omit_power = c(5, 5)
x <- 1.2
format_sci(x, omit_power = NULL)

# set_power
format_sci(x, set_power = NULL) # default
format_sci(x, set_power = 3)

# set_power overrides format
x <- 6.0221E+23
format_engr(x)
format_engr(x, set_power = 24L)
format_sci(x)
format_sci(x, set_power = 24L)

# set_power overrides omit_power
x <- 101300
format_sci(x, omit_power = 5)
format_sci(x, omit_power = 5, set_power = 2)
format_sci(x, omit_power = 2)
format_sci(x, omit_power = 2, set_power = 2)

# decimal format ignores set_power
x <- 103400
format_numbers(x, format = "dcml")
format_numbers(x, format = "dcml", set_power = 3)
```

format_sci	<i>Format scientific notation</i>
------------	-----------------------------------

Description

Convert a numeric vector to a character vector in which the numbers are formatted in power-of-ten notation in scientific form and delimited for rendering as inline equations in an R markdown document.

Usage

```
format_sci(
  x,
  digits = 4,
  ...,
  omit_power = c(-1, 2),
  set_power = NULL,
  delim = formatdown_options("delim"),
  size = formatdown_options("size"),
  decimal_mark = formatdown_options("decimal_mark"),
  small_mark = formatdown_options("small_mark"),
  small_interval = formatdown_options("small_interval"),
  whitespace = formatdown_options("whitespace")
)
```

Arguments

<code>x</code>	Number or numbers to be formatted. Can be a single number, a vector, or a column of a data frame.
<code>digits</code>	Integer from 1 through 20 that controls the number of significant digits in printed numeric values. Passed to <code>signif()</code> . Default is 4.
<code>...</code>	Not used for values; forces subsequent arguments to be referable only by name.
<code>omit_power</code>	Numeric vector <code>c(p, q)</code> with <code>p <= q</code> , specifying the range of exponents over which power-of-ten notation is omitted in either scientific or engineering format. Default is <code>c(-1, 2)</code> . If a single value is assigned, i.e., <code>omit_power = p</code> , the argument is interpreted as <code>c(p, p)</code> . If <code>NULL</code> or <code>NA</code> , all elements are formatted in power-of-ten notation. Argument is overridden by specifying <code>set_power</code> or decimal notation.
<code>set_power</code>	Integer, length 1. Formats all values in <code>x</code> with the same power-of-ten exponent. Default <code>NULL</code> . Overrides <code>format</code> and <code>omit_power</code> arguments.
<code>delim</code>	Character, length 1 or 2, to define the left and right math markup delimiters. The default setting, <code>delim = "\$"</code> , produces left and right delimiters <code>\$. . \$.</code> . The alternate built-in setting, <code>delim = "\(""</code> , produces left and right delimiters <code>\(. . \)</code> . Custom delimiters can be assigned in a vector of length 2 with left and right delimiter symbols, e.g., <code>c("\[""</code> , <code>"]\)"</code>). Special characters typically must be escaped.

size	Character, length 1, to assign a font size. If not empty, adds a font size macro to the markup inside the math delimiters. Possible values are "scriptsize", "small", "normalsize", "large", and "huge". One may also assign the equivalent LaTeX-style markup itself, e.g., "\scriptsize", "\small", etc. Default is NULL.
decimal_mark	Character, length 1, to assign the decimal marker. Possible values are a period "." (default) or a comma ",". Passed to formatC(decimal.mark).
small_mark	Character, length 1, used as the mark between every small_interval number of digits to the right of the decimal marker to improve readability. Possible values are empty "" (default) or "thin" to produce a LaTeX-style thin, horizontal space. One may also assign the thin-space markup itself "\\\", ". Passed to formatC(small.mark).
small_interval	Integer, length 1, that defines the number of digits (default 5) in groups separated by small_mark. Passed to formatC(small.interval).
whitespace	Character, length 1, to define the LaTeX-style math-mode macro to preserve a horizontal space between words of text or between physical-unit abbreviations when formatting numbers of class "units". Default is "\\\>". Alternatives include "\\\: " or "\\\ ".

Details

format_sci() is a wrapper for the more general function format_numbers(). Where defaults are defined by formatdown_options(), users may reassign the arguments locally in the function call or globally using formatdown_options().

Arguments after the dots (...) must be referred to by name.

Value

A character vector in which numbers are formatted in power-of-ten notation in scientific form and delimited for rendering as inline equations in an R markdown document.

See Also

Other format_*: [format_dcm1\(\)](#), [format_engr\(\)](#), [format_numbers\(\)](#), [format_text\(\)](#)

Examples

```
# input: single number
x <- 6.0221E+23
format_numbers(x)

# input: units class
x <- 103400
units(x) <- "N m2 C-2"
format_numbers(x)

# input: vector
data("metals", package = "formatdown")
x <- metals$dens
```

```
format_numbers(x)

# significant digits
x <- 9.75358e+5
format_numbers(x, 2)
format_numbers(x, 3)
format_numbers(x, 4)

# format & wrappers: format_engr(), format_sci(), format_dcml()
x <- 6.0221E+23
format_numbers(x, format = "engr")
format_engr(x)

format_numbers(x, format = "sci")
format_sci(x)

x <- 103400
format_numbers(x, format = "dcml")
format_dcml(x)

# input: data frame
x <- metals[, c("thrm_exp", "thrm_cond")]
as.data.frame(apply(x, 2, format_sci, digits = 3))

# omit_power
x <- 103400
format_sci(x, omit_power = c(-1, 2)) # default
format_sci(x, omit_power = c(-1, 5))
format_sci(x, omit_power = 5) # equivalent to omit_power = c(5, 5)
x <- 1.2
format_sci(x, omit_power = NULL)

# set_power
format_sci(x, set_power = NULL) # default
format_sci(x, set_power = 3)

# set_power overrides format
x <- 6.0221E+23
format_engr(x)
format_engr(x, set_power = 24L)
format_sci(x)
format_sci(x, set_power = 24L)

# set_power overrides omit_power
x <- 101300
format_sci(x, omit_power = 5)
format_sci(x, omit_power = 5, set_power = 2)
format_sci(x, omit_power = 2)
format_sci(x, omit_power = 2, set_power = 2)

# decimal format ignores set_power
x <- 103400
format_numbers(x, format = "dcml")
```

```
format_numbers(x, format = "dcml", set_power = 3)
```

format_text

Format text

Description

Convert a character vector to "math text" delimited for rendering as inline equations in an R markdown document. Particularly useful for matching the font face of character columns to that of numerical columns in a table.

Usage

```
format_text(
  x,
  face = "plain",
  ...,
  size = formatdown_options("size"),
  delim = formatdown_options("delim"),
  whitespace = formatdown_options("whitespace")
)
```

Arguments

x	Vector to be formatted.
face	Font face. Determines the font face macro inside the math delimiters. Possible values are "plain" (default), "italic", "bold", "sans", or "mono". One may assign instead the corresponding LaTeX-style markup itself, e.g., <code>\mathrm</code> , <code>\mathit</code> , <code>\mathbf</code> , <code>\mathsf</code> , or <code>\mathtt</code> .
...	Not used, force later arguments to be used by name.
size, delim, whitespace	Used to format the math-delimited character strings. For details, see the help page for <code>formatdown_options()</code> .

Details

Given a scalar, vector, or data frame column, `format_text()` converts its argument to a character string of the form `"$\mathxx{a}$"` where `a` is the element to be formatted and `\mathxx` determines the font face: plain type is set by `\mathrm`; italic by `\mathit`; bold by `\mathbf`; sans serif by `\mathsf`; and monospace (typewriter text) by `\mathtt`. All strings include markup delimiters `$. . . $` for rendering (in an R markdown or Quarto markdown document) as an inline equation.

Value

A character vector with elements delimited as inline math markup in plain, italic, sans serif, bold, or monospace font face.

See Also

Other format_*: [format_dcm1\(\)](#), [format_engr\(\)](#), [format_numbers\(\)](#), [format_sci\(\)](#)

Examples

```
# Text vector

# default face = "plain"
x <- air_meas$humid
format_text(x)

# equivalently
format_text(x, face = "plain")

# input vector
x <- c("Hello world!", "Goodbye blues!")
format_text(x)

# argument coerced to character string if possible
format_text(c(1.2, 2.3, 3.4))
format_text(x = NA)
format_text(x = c(TRUE, FALSE, TRUE))

# numbers as strings are rendered as-is
format_text(x = c("1.2E-3", "3.4E+0", "5.6E+3"))

# other font faces
format_text(x, face = "italic")
format_text(x, face = "bold")
format_text(x, face = "sans")
format_text(x, face = "mono")
```

metals	<i>Properties of metals</i>
--------	-----------------------------

Description

Table of mechanical and thermal properties of selected metals.

Usage

```
data(metals, package = "formatdown")
```

Format

Classes data.table and data.frame: 6 observations of 5 variables:

- metal** Character, name of material
- dens** Numeric, density (kg m⁻³)

thrm_exp Numeric, coefficient of thermal expansion ($\text{m m}^{-1}\text{K}^{-1}$)

thrm_cond Numeric, thermal conductivity ($\text{W m}^{-1}\text{K}^{-1}$)

elast_mod Numeric, modulus of elasticity (Pa)

Source

Marks' Standard Handbook for Mechanical Engineers 9/e (1987) E.A. Avallone and T. Baumeister (ed.), "Basic Properties of Several Metals", pp. 6-11, McGraw-Hill, NY.

water

Properties of water

Description

Table of water properties at atmospheric pressure as a function of temperature.

Usage

```
data(water, package = "formatdown")
```

Format

Classes data.table and data.frame: 11 observations of 5 variables:

temp Numeric, temperature (K)

dens Numeric, density (kg m^{-3})

sp_wt Numeric, specific weight (N m^{-3})

visc Numeric, dynamic viscosity (Pa s)

bulk_mod Numeric, bulk modulus (Pa)

Source

E. Maurer E and I. Embry (2022) *hydraulics: Basic Pipe and Open Channel Hydraulics*, R package ver. 0.6.0, <https://edm44.github.io/hydraulics/>.

Index

* datasets

air_meas, [2](#)

atmos, [3](#)

metals, [20](#)

water, [21](#)

* format_*

format_dcml, [6](#)

format_engr, [9](#)

format_numbers, [12](#)

format_sci, [16](#)

format_text, [19](#)

air_meas, [2](#)

atmos, [3](#)

format_dcml, [6](#), [10](#), [14](#), [17](#), [20](#)

format_engr, [7](#), [9](#), [14](#), [17](#), [20](#)

format_numbers, [7](#), [10](#), [12](#), [17](#), [20](#)

format_sci, [7](#), [10](#), [14](#), [16](#), [20](#)

format_text, [7](#), [10](#), [14](#), [17](#), [19](#)

formatdown_options, [3](#)

metals, [20](#)

water, [21](#)