

# Wake Model Description for Optimization Only Case Study

IEA Task 37 on System Engineering in Wind Energy

This is an explanatory enclosure to accompany `iea37-wflocs-announcement.pdf`. For the Optimization Only Case Study, we will use the enclosed Python file `iea37-aepcalc.py` to evaluate your reported optimal turbine locations in `.yaml` format. If you desire to implement the AEP calculations in a language other than Python, the algorithm's description and wake model equations are provided below. Please insure your implementation computes the same AEP value given in each of the example layouts (`iea37-ex##.yaml`) also enclosed.

## Wake Model Equations

The wake model for the Optimization Only Case Study is a simplified version of Bastankhah's Gaussian wake model [?]. The governing equations for the velocity deficit in a waked region are:

$$\frac{\Delta V}{V_\infty} = \begin{cases} \left(1 - \sqrt{1 - \frac{C_T}{8\sigma_y^2/D^2}}\right) \exp\left(-0.5\left(\frac{y_i - y_g}{\sigma_y}\right)^2\right), & \text{if } (x_i - x_g) > 0 \\ 0, & \text{otherwise} \end{cases} \quad (1)$$

$$\sigma_y = k_y \cdot (x_i - x_g) + \frac{D}{\sqrt{8}} \quad (2)$$

Variable	Value	Definition
$\Delta V/V_\infty$	Eq. (1)	Normalized wake velocity deficit
$C_T$	8/9	Thrust coefficient
$x_i - x_g$	-	Dist. from hub generating wake ( $x_g$ ) to hub of interest ( $x_i$ ), along freestream
$y_i - y_g$	-	Dist. from hub generating wake ( $y_g$ ) to hub of interest ( $y_i$ ), $\perp$ to freestream
$\sigma_y$	Eq. (2)	Standard deviation of the wake deficit
$k_y$	0.0324555	Variable based on a turbulence intensity of 0.075 [?, ?]
$D$	130 m	Turbine diameter [?]

The two cases in the wake velocity equation are needed because wakes are assumed to only affect points downstream. Hub coordinates are used for all location calculations. For turbines placed in multiple wakes, the total velocity deficit is calculated using the square root of the sum of the squares:

$$\left(\frac{\Delta V}{V_\infty}\right)_{total} = \sqrt{\left(\frac{\Delta V}{V_\infty}\right)_1^2 + \left(\frac{\Delta V}{V_\infty}\right)_2^2 + \left(\frac{\Delta V}{V_\infty}\right)_3^2 + \dots} \quad (3)$$

## AEP Algorithm

1. Read the following input from `.yaml` files:

- Turbine ( $x, y$ ) locations.
- Turbine attributes (cut-in\cut-out\rated wind speed\rated power).
- Number of wind directional bins,  $\theta_i$  ( $i = 16$  for these Case Studies).
- Wind frequency at each binned direction,  $f(\theta)$ .
- Wind speed at each binned direction,  $V_\infty(\theta)$  (invariant for these Case Studies).

2. Calculate the power produced in the farm for one wind direction:

- (a) For each binned direction  $\theta$ , rotate the turbine locations  $(x, y)$  into the into the wind frame of reference  $(x_w, y_w)$ :

$$\begin{aligned}\Psi &= -\left(\frac{\pi}{2} + \theta\right) \\ x_w &= x \cos(\Psi) + y \sin(\Psi) \\ y_w &= -x \sin(\Psi) + y \cos(\Psi)\end{aligned}$$

- (b) Iterating through each turbine in the field to compute its power:

- Compute the wake deficit between each turbine pair Eq. (1) (there is no wake effect of a turbine on itself).
- Use Eq. (3) to calculate the total wake loss.
- Compute effective wind speed ( $V_e$ ) at each turbine:

$$V_e = V_\infty \left[ 1 - \left( \frac{\Delta V}{V_\infty} \right)_{total} \right]$$

- Use  $V_e$  and the IEA37 3.35MW power curve to calculate each turbine's power:

$$P_{turb}(V_e) = \begin{cases} 0 & V_e < V_{cut-in} \\ P_{rated} \cdot \left( \frac{V_e - V_{cut-in}}{V_{rated} - V_{cut-in}} \right)^3 & V_{cut-in} \leq V_e < V_{rated} \\ P_{rated} & V_{rated} \leq V_e < V_{cut-out} \\ 0 & V_e \geq V_{cut-out} \end{cases} \quad (4)$$

- (c) Sum powers from all  $n$  turbines

$$P_{farm} = \sum_{j=1}^n P_{turb,j} \quad (5)$$

3. Compute AEP using farm power for all  $m$  directions where  $P$  is the wind farm power for direction  $i$  and  $f$  is the corresponding frequency for direction  $i$ . The factor of 8760 is just to multiply by hours in a year:

$$AEP = \left( \sum_{i=1}^m f_i P_i \right) 8760 \frac{\text{hrs}}{\text{yr}} \quad (6)$$

## References

- [1] Thomas, J. J. and Ning, A., "A method for reducing multi-modality in the wind farm layout optimization problem," *Journal of Physics: Conference Series*, The Science of Making Torque from Wind, Milano, Italy, June 2018.
- [2] Niayifar, A. and Porté-Agel, F., "Analytical Modeling of Wind Farms: A New Approach for Power Prediction," *Energies*, September 2016.
- [3] Bortolotti, P., Dykes, K., Merz, K., Sethuraman, L., and Zahle, F., "IEA Wind Task 37 on System Engineering in Wind Energy, WP2 - Reference Wind Turbines," Tech. rep., National Renewable Energy Laboratory (NREL), Golden, CO., May 2018.