

Package ‘cpp11armadillo’

May 6, 2025

Type Package

Title An 'Armadillo' Interface

Description Provides function declarations and inline function definitions that facilitate communication between R and the 'Armadillo' 'C++' library for linear algebra and scientific computing. This implementation is detailed in Vargas Sepulveda and Schneider Malamud (2024) [<doi:10.1016/j.softx.2025.102087>](https://doi.org/10.1016/j.softx.2025.102087).

Version 0.5.0

Imports cpp11

Suggests desc, knitr, mockery, rmarkdown, testthat (>= 3.0.0), withr

Depends R(>= 3.5.0)

License Apache License (>= 2)

BugReports <https://github.com/pachadotdev/cpp11armadillo/issues>

URL <https://pacha.dev/cpp11armadillo/>,
<https://github.com/pachadotdev/cpp11armadillo>

RoxygenNote 7.3.2

Encoding UTF-8

VignetteBuilder knitr

Config/testthat/edition 3

NeedsCompilation no

Author Mauricio Vargas Sepulveda [aut, cre] (ORCID:
 [<https://orcid.org/0000-0003-1017-7574>](https://orcid.org/0000-0003-1017-7574)),
Jonathan Schneider Malamud [ctb],
Conrad Sanderson [aut] (Armadillo library (C++))

Maintainer Mauricio Vargas Sepulveda [<m.sepulveda@mail.utoronto.ca>](mailto:m.sepulveda@mail.utoronto.ca)

Repository CRAN

Date/Publication 2025-05-06 04:20:02 UTC

Contents

armadillo_version	2
cpp_vendor	2
pkg_template	3
Index	4

armadillo_version	<i>Get Armadillo version</i>
-------------------	------------------------------

Description

Provides the Armadillo C++ library version name and number included in the package.

Usage

```
armadillo_version()
```

Value

A string with the Armadillo version name and number

Examples

```
armadillo_version()
```

cpp_vendor	<i>Vendor the cpp11 and cpp11armadillo dependency</i>
------------	---

Description

Vendoring is the act of making your own copy of the 3rd party packages your project is using. It is often used in the go language community.

Usage

```
cpp_vendor(dir = NULL, subdir = "/inst/include")
```

Arguments

- | | |
|--------|---|
| dir | The directory to vendor the code into. |
| subdir | The subdirectory to vendor the code into. |

Details

This function vendors cpp11 and cpp11armadillo into your package by copying the cpp11 and cpp11armadillo headers into the ‘inst/include’ folder and adding ‘cpp11 version: XYZ’ and ‘cpp11armadillo version: XYZ’ to the top of the files, where XYZ is the version of cpp11 and cpp11armadillo currently installed on your machine.

Vendoring places the responsibility of updating the code on you. Bugfixes and new features in cpp11 and cpp11armadillo will not be available for your code until you run ‘cpp_vendor()’ again.

Value

The file path to the vendored code (invisibly).

Examples

```
# create a new directory
dir <- tempdir()
dir.create(dir)

# vendor the cpp11 headers into the directory
cpp_vendor(dir)
```

pkg_template

Start a new project with the cpp11armadillo package template

Description

Start a new project with the cpp11armadillo package template

Usage

```
pkg_template(path = NULL, pkgname = NULL)
```

Arguments

path	Path to the new project
pkgname	Name of the new package

Value

The file path to the copied template (invisibly).

Examples

```
# create a new directory
dir <- tempdir()
dir.create(dir)

# copy the package template into the directory
pkg_template(dir, "mynewpkg")
```

Index

`armadillo_version`, [2](#)

`cpp_vendor`, [2](#)

`pkg_template`, [3](#)