

Package ‘pccc’

January 23, 2026

Title Pediatric Complex Chronic Conditions

Version 1.0.7

Description An implementation of the pediatric complex chronic conditions (CCC) classification system using R and C++.

Depends R (>= 3.5.0)

License GPL-2

Encoding UTF-8

Language en-us

LazyData true

Imports dplyr (>= 1.0.0), Rcpp (>= 1.0.11)

Suggests covr, knitr, rmarkdown, readr

RoxygenNote 7.3.3

LinkingTo Rcpp (>= 1.0.11)

VignetteBuilder knitr

URL <https://github.com/CUD2V/pccc>

BugReports <https://github.com/CUD2V/pccc/issues>

NeedsCompilation yes

Author Peter DeWitt [aut] (ORCID: <<https://orcid.org/0000-0002-6391-0795>>),
Tell Bennett [ctb] (ORCID: <<https://orcid.org/0000-0003-1483-4236>>),
James Feinstein [aut] (ORCID: <<https://orcid.org/0000-0003-3074-8805>>),
Seth Russell [aut, cre] (ORCID:
<<https://orcid.org/0000-0002-2436-1367>>)

Maintainer Seth Russell <seth.russell@cuanschutz.edu>

Repository CRAN

Date/Publication 2026-01-23 03:50:02 UTC

Contents

ccc	2
comparability	3
get_codes	4
pccc_icd10_dataset	5
pccc_icd9_dataset	6
test_helper	8
Index	9

ccc	<i>Complex Chronic Conditions (CCC)</i>
-----	---

Description

Generate CCC and CCC subcategory flags and the number of categories.

Usage

```
ccc(data, id, dx_cols = NULL, pc_cols = NULL, icdv)
```

Arguments

data	a data.frame containing a patient id and all the ICD-9-CM or ICD-10-CM codes. The data.frame passed to the function should be in wide format.
id	bare name of the column containing the patient id
dx_cols, pc_cols	column names with the diagnostic codes and procedure codes respectively. These argument are passed to select .
icdv	ICD version 9 or 10

Details

It is recommended that you view the codes defining the CCC via [get_codes](#) and make sure that the ICD codes in your data set are formatted in the same way. The ICD codes used for CCC are character strings must be formatted as follows:

- **Do not** use decimal points or other separators
- ICD 9 codes: Codes less than 10 should be left padded with 2 zeros. Codes less than 100 should be left padded with 1 zero.

See ‘`vignette("pccc-overview")`’ for more details.

Value

A data.frame with a column for the subject id and integer (0 or 1) columns for each each of the categories.

References

See [pccc-package](#) for published paper on the topic of identifying Complex Chronic Conditions

See Also

[get_codes](#) to view the ICD codes used to define the CCC. [select](#) for more examples and details on how to identify and select the diagnostic and procedure code columns.

Examples

```
eg_data <- data.frame(id = letters,
                      dx1 = c(NA, NA, sample(get_codes(10)[["hemato_immu", "dx"]], 24)),
                      dx2 = c("A", sample(get_codes(10)[["gi", "dx"]], 25)),
                      dx3 = LETTERS,
                      pc1 = c("B", sample(get_codes(10)[["cvd", "pc"]], 25)),
                      pc2 = LETTERS,
                      other_col = LETTERS)

ccc(eg_data,
     id,
     dx_cols = dplyr::starts_with("dx"),
     pc_cols = dplyr::starts_with("pc"),
     icdv = 10)
```

comparability

Multiple Cause of Death (MCOD) file extract

Description

The Center for Disease Control has made publicly available death certificate data. This data set is a subset of the 2006 MCODE file for decedents aged <= 21 showing just the underlying cause of death diagnosis code in ICD-9-CM and ICD-10.

Usage

```
comparability
```

Format

A data frame with 65037 rows and 3 variables.

id Sequentially assigned patient identifier

icd9 Underlying Cause of Death ICD 9 CM diagnosis code

icd10 Underlying Cause of Death ICD 10 diagnosis code

See Also

`vignette("pccc-example")` for more details about the MCODE source file.

get_codes

Get (view) Diagnostic and Procedure Codes

Description

View the ICD, version 9 or 10, for the Complex Chronic Conditions (CCC) categories.

Usage

```
get_codes(icdv)
```

Arguments

icdv and integer value specifying ICD version. Accepted values are 9 or 10.

Details

The CCC categories for diagnostic and procedure codes are:

category	dx	dx_fixed	pc	pc_fixed
neuromuscul	X	X	X	
cvd	X	X	X	
respiratory	X	X	X	
renal	X		X	
gi	X		X	
hemato_immu	X		X	
metabolic	X		X	X
congeni_genetic	X			
malignancy	X		X	
neonatal	X			
tech_dep	X		X	
transplant	X		X	

The ICD codes were taken from the SAS macro provided by the reference paper.

Value

A matrix of character vectors. Rows are the categories and columns for diagnostic and procedure codes.

References

Feudtner C, et al. Pediatric complex chronic conditions classification system version 2: updated for ICD-10 and complex medical technology dependence and transplantation, BMC Pediatrics, 2014, 14:199, DOI: 10.1186/1471-2431-14-199

Examples

```
# All ICD 9 codes for CCC
get_codes(9)

# All ICD 10 codes for CCC
get_codes(10)

# Get all the codes for ICD 9 related to malignancy
get_codes(9)["malignancy", ]
```

pccc_icd10_dataset *Randomly Generated ICD 10 Sample Data Set*

Description

This dataset was produced from a tool available at https://github.com/magic-lantern/icd_file_generator. ICD codes were taken from CMS. The code source, for both the diagnosis and produced codes can be found at <https://www.cms.gov/medicare/coding-billing/icd-10-codes/icd-10-cm-icd-10-pcs-gem-archive> with a copy of the downloaded data on the package github page, <https://github.com/CUD2V/pccc>

Usage

```
pccc_icd10_dataset
```

Format

A data frame with 1000 rows and 31 variables. There is a patient identifier, ten diagnosis codes, ten procedure codes, and ten "other data" values, specifically:

id Sequentially assigned patient identifier

dx1 a ICD 10 diagnosis code

dx2 a ICD 10 diagnosis code

dx3 a ICD 10 diagnosis code

dx4 a ICD 10 diagnosis code

dx5 a ICD 10 diagnosis code

dx6 a ICD 10 diagnosis code

dx7 a ICD 10 diagnosis code

dx8 a ICD 10 diagnosis code

dx9 a ICD 10 diagnosis code

dx10 a ICD 10 diagnosis code

pc1 a ICD 10 procedure codes

pc2 a ICD 10 procedure codes

pc3 a ICD 10 procedure codes

- pc4** a ICD 10 procedure codes
- pc5** a ICD 10 procedure codes
- pc6** a ICD 10 procedure codes
- pc7** a ICD 10 procedure codes
- pc8** a ICD 10 procedure codes
- pc9** a ICD 10 procedure codes
- pc10** a ICD 10 procedure codes
- g1** Random data to simulate other data often present in export of patient data with 20% of values missing.
- g2** Random data to simulate other data often present in export of patient data with 20% of values missing.
- g3** Random data to simulate other data often present in export of patient data with 20% of values missing.
- g4** Random data to simulate other data often present in export of patient data with 20% of values missing.
- g5** Random data to simulate other data often present in export of patient data with 20% of values missing.
- g6** Random data to simulate other data often present in export of patient data with 20% of values missing.
- g7** Random data to simulate other data often present in export of patient data with 20% of values missing.
- g8** Random data to simulate other data often present in export of patient data with 20% of values missing.
- g9** Random data to simulate other data often present in export of patient data with 20% of values missing.
- g10** Random data to simulate other data often present in export of patient data with 20% of values missing.

pccc_icd9_dataset

Randomly Generated ICD 9 Sample Data Set

Description

This dataset was produced from a tool available at https://github.com/magic-lantern/icd_file_generator. ICD codes were taken from CMS. The ICD 9 diagnosis and procedure codes were generated with 20 missing values. Code source: <https://www.cms.gov/medicare/coding-billing/icd-10-codes/icd-9-cm-diagnosis-procedure-codes-abbreviated-and-full-code-titles>

Usage

pccc_icd9_dataset

Format

A data frame with 1000 rows and 31 variables. There is a patient identifier, ten diagnosis codes, ten procedure codes, and ten "other data" values, specifically:

id Sequentially assigned patient identifier

dx1 a ICD 9 diagnosis code

dx2 a ICD 9 diagnosis code

dx3 a ICD 9 diagnosis code

dx4 a ICD 9 diagnosis code

dx5 a ICD 9 diagnosis code

dx6 a ICD 9 diagnosis code

dx7 a ICD 9 diagnosis code

dx8 a ICD 9 diagnosis code

dx9 a ICD 9 diagnosis code

dx10 a ICD 9 diagnosis code

pc1 a ICD 9 procedure codes

pc2 a ICD 9 procedure codes

pc3 a ICD 9 procedure codes

pc4 a ICD 9 procedure codes

pc5 a ICD 9 procedure codes

pc6 a ICD 9 procedure codes

pc7 a ICD 9 procedure codes

pc8 a ICD 9 procedure codes

pc9 a ICD 9 procedure codes

pc10 a ICD 9 procedure codes

g1 Random data to simulate other data often present in export of patient data with 20% of values missing.

g2 Random data to simulate other data often present in export of patient data with 20% of values missing.

g3 Random data to simulate other data often present in export of patient data with 20% of values missing.

g4 Random data to simulate other data often present in export of patient data with 20% of values missing.

g5 Random data to simulate other data often present in export of patient data with 20% of values missing.

g6 Random data to simulate other data often present in export of patient data with 20% of values missing.

g7 Random data to simulate other data often present in export of patient data with 20% of values missing.

- g8** Random data to simulate other data often present in export of patient data with 20% of values missing.
- g9** Random data to simulate other data often present in export of patient data with 20% of values missing.
- g10** Random data to simulate other data often present in export of patient data with 20% of values missing.

test_helper

Test Helper

Description

Tool to help access internal variables to use in testthat scripts, or anytime access via `:::` would be needed.

Usage

```
test_helper(var)
```

Arguments

var bare name of the internal variable to be accessed.

Value

Object from internal PCCC name space (if it exists)

Index

* **datasets**

- comparability, [3](#)
- pccc_icd10_dataset, [5](#)
- pccc_icd9_dataset, [6](#)

ccc, [2](#)

comparability, [3](#)

get_codes, [2](#), [3](#), [4](#)

pccc_icd10_dataset, [5](#)

pccc_icd9_dataset, [6](#)

select, [2](#), [3](#)

test_helper, [8](#)