



API Reference

AWS App Mesh



API Version 2019-01-25

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

AWS App Mesh: API Reference

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
CreateGatewayRoute	4
Request Syntax	4
URI Request Parameters	7
Request Body	8
Response Syntax	9
Response Elements	12
Errors	14
Examples	15
See Also	17
CreateMesh	18
Request Syntax	18
URI Request Parameters	18
Request Body	18
Response Syntax	19
Response Elements	20
Errors	21
Examples	22
See Also	23
CreateRoute	25
Request Syntax	25
URI Request Parameters	29
Request Body	30
Response Syntax	31
Response Elements	35
Errors	36
Examples	38
See Also	40
CreateVirtualGateway	41
Request Syntax	41
URI Request Parameters	42
Request Body	43
Response Syntax	44

Response Elements	46
Errors	46
Examples	48
See Also	50
CreateVirtualNode	51
Request Syntax	51
URI Request Parameters	53
Request Body	54
Response Syntax	55
Response Elements	57
Errors	58
Examples	59
See Also	61
CreateVirtualRouter	63
Request Syntax	63
URI Request Parameters	63
Request Body	64
Response Syntax	65
Response Elements	66
Errors	67
Examples	68
See Also	70
CreateVirtualService	71
Request Syntax	71
URI Request Parameters	71
Request Body	72
Response Syntax	73
Response Elements	73
Errors	74
Examples	75
See Also	77
DeleteGatewayRoute	78
Request Syntax	78
URI Request Parameters	78
Request Body	79
Response Syntax	79

Response Elements	82
Errors	83
Examples	84
See Also	86
DeleteMesh	87
Request Syntax	87
URI Request Parameters	87
Request Body	87
Response Syntax	87
Response Elements	88
Errors	89
Examples	90
See Also	91
DeleteRoute	92
Request Syntax	92
URI Request Parameters	92
Request Body	93
Response Syntax	93
Response Elements	97
Errors	98
Examples	99
See Also	101
DeleteVirtualGateway	102
Request Syntax	102
URI Request Parameters	102
Request Body	102
Response Syntax	103
Response Elements	104
Errors	105
Examples	106
See Also	108
DeleteVirtualNode	109
Request Syntax	109
URI Request Parameters	109
Request Body	109
Response Syntax	110

Response Elements	112
Errors	113
Examples	114
See Also	115
DeleteVirtualRouter	117
Request Syntax	117
URI Request Parameters	117
Request Body	117
Response Syntax	118
Response Elements	118
Errors	119
Examples	120
See Also	122
DeleteVirtualService	123
Request Syntax	123
URI Request Parameters	123
Request Body	123
Response Syntax	123
Response Elements	124
Errors	125
Examples	126
See Also	127
DescribeGatewayRoute	129
Request Syntax	129
URI Request Parameters	129
Request Body	130
Response Syntax	130
Response Elements	133
Errors	134
Examples	135
See Also	137
DescribeMesh	138
Request Syntax	138
URI Request Parameters	138
Request Body	138
Response Syntax	138

Response Elements	139
Errors	140
Examples	141
See Also	142
DescribeRoute	143
Request Syntax	143
URI Request Parameters	143
Request Body	144
Response Syntax	144
Response Elements	148
Errors	149
Examples	150
See Also	152
DescribeVirtualGateway	153
Request Syntax	153
URI Request Parameters	153
Request Body	153
Response Syntax	154
Response Elements	155
Errors	156
Examples	157
See Also	159
DescribeVirtualNode	160
Request Syntax	160
URI Request Parameters	160
Request Body	160
Response Syntax	161
Response Elements	163
Errors	164
Examples	164
See Also	166
DescribeVirtualRouter	168
Request Syntax	168
URI Request Parameters	168
Request Body	168
Response Syntax	169

Response Elements	169
Errors	170
Examples	171
See Also	172
DescribeVirtualService	174
Request Syntax	174
URI Request Parameters	174
Request Body	174
Response Syntax	174
Response Elements	175
Errors	176
Examples	177
See Also	178
ListGatewayRoutes	180
Request Syntax	180
URI Request Parameters	180
Request Body	181
Response Syntax	181
Response Elements	182
Errors	182
Examples	183
See Also	184
ListMeshes	186
Request Syntax	186
URI Request Parameters	186
Request Body	186
Response Syntax	187
Response Elements	187
Errors	188
Examples	188
See Also	190
ListRoutes	191
Request Syntax	191
URI Request Parameters	191
Request Body	192
Response Syntax	192

Response Elements	193
Errors	193
Examples	194
See Also	195
ListTagsForResource	196
Request Syntax	196
URI Request Parameters	196
Request Body	196
Response Syntax	197
Response Elements	197
Errors	197
See Also	198
ListVirtualGateways	200
Request Syntax	200
URI Request Parameters	200
Request Body	201
Response Syntax	201
Response Elements	201
Errors	202
Examples	203
See Also	204
ListVirtualNodes	205
Request Syntax	205
URI Request Parameters	205
Request Body	206
Response Syntax	206
Response Elements	206
Errors	207
Examples	208
See Also	210
ListVirtualRouters	211
Request Syntax	211
URI Request Parameters	211
Request Body	212
Response Syntax	212
Response Elements	212

Errors	213
Examples	214
See Also	215
ListVirtualServices	216
Request Syntax	216
URI Request Parameters	216
Request Body	217
Response Syntax	217
Response Elements	217
Errors	218
Examples	219
See Also	220
TagResource	222
Request Syntax	222
URI Request Parameters	222
Request Body	222
Response Syntax	223
Response Elements	223
Errors	223
See Also	224
UntagResource	225
Request Syntax	225
URI Request Parameters	225
Request Body	225
Response Syntax	226
Response Elements	226
Errors	226
See Also	227
UpdateGatewayRoute	228
Request Syntax	228
URI Request Parameters	231
Request Body	232
Response Syntax	232
Response Elements	236
Errors	237
Examples	238

See Also	240
UpdateMesh	241
Request Syntax	241
URI Request Parameters	241
Request Body	241
Response Syntax	242
Response Elements	243
Errors	243
See Also	244
UpdateRoute	246
Request Syntax	246
URI Request Parameters	250
Request Body	251
Response Syntax	251
Response Elements	256
Errors	257
Examples	258
See Also	260
UpdateVirtualGateway	262
Request Syntax	262
URI Request Parameters	263
Request Body	264
Response Syntax	264
Response Elements	266
Errors	267
Examples	268
See Also	270
UpdateVirtualNode	271
Request Syntax	271
URI Request Parameters	272
Request Body	273
Response Syntax	274
Response Elements	276
Errors	277
Examples	278
See Also	280

UpdateVirtualRouter	282
Request Syntax	282
URI Request Parameters	282
Request Body	283
Response Syntax	283
Response Elements	284
Errors	285
Examples	286
See Also	288
UpdateVirtualService	289
Request Syntax	289
URI Request Parameters	289
Request Body	290
Response Syntax	290
Response Elements	291
Errors	291
Examples	293
See Also	294
Data Types	296
AccessLog	302
Contents	302
See Also	302
AwsCloudMapInstanceAttribute	303
Contents	303
See Also	303
AwsCloudMapServiceDiscovery	305
Contents	305
See Also	306
Backend	307
Contents	307
See Also	307
BackendDefaults	308
Contents	308
See Also	308
ClientPolicy	309
Contents	309

See Also	309
ClientPolicyTls	310
Contents	310
See Also	310
ClientTlsCertificate	312
Contents	312
See Also	312
DnsServiceDiscovery	313
Contents	313
See Also	313
Duration	315
Contents	315
See Also	315
EgressFilter	316
Contents	316
See Also	316
FileAccessLog	317
Contents	317
See Also	317
GatewayRouteData	319
Contents	319
See Also	320
GatewayRouteHostnameMatch	321
Contents	321
See Also	321
GatewayRouteHostnameRewrite	322
Contents	322
See Also	322
GatewayRouteRef	323
Contents	323
See Also	325
GatewayRouteSpec	326
Contents	326
See Also	326
GatewayRouteStatus	328
Contents	328

See Also	328
GatewayRouteTarget	329
Contents	329
See Also	329
GatewayRouteVirtualService	330
Contents	330
See Also	330
GrpcGatewayRoute	331
Contents	331
See Also	331
GrpcGatewayRouteAction	332
Contents	332
See Also	332
GrpcGatewayRouteMatch	333
Contents	333
See Also	333
GrpcGatewayRouteMetadata	335
Contents	335
See Also	335
GrpcGatewayRouteRewrite	337
Contents	337
See Also	337
GrpcMetadataMatchMethod	338
Contents	338
See Also	339
GrpcRetryPolicy	340
Contents	340
See Also	341
GrpcRoute	342
Contents	342
See Also	342
GrpcRouteAction	344
Contents	344
See Also	344
GrpcRouteMatch	345
Contents	345

See Also	346
GrpcRouteMetadata	347
Contents	347
See Also	347
GrpcRouteMetadataMatchMethod	349
Contents	349
See Also	350
GrpcTimeout	351
Contents	351
See Also	351
HeaderMatchMethod	352
Contents	352
See Also	353
HealthCheckPolicy	354
Contents	354
See Also	355
HttpGatewayRoute	356
Contents	356
See Also	356
HttpGatewayRouteAction	357
Contents	357
See Also	357
HttpGatewayRouteHeader	358
Contents	358
See Also	358
HttpGatewayRouteMatch	360
Contents	360
See Also	361
HttpGatewayRoutePathRewrite	362
Contents	362
See Also	362
HttpGatewayRoutePrefixRewrite	363
Contents	363
See Also	363
HttpGatewayRouteRewrite	364
Contents	364

See Also	364
HttpPathMatch	365
Contents	365
See Also	365
HttpQueryParameter	366
Contents	366
See Also	366
HttpRetryPolicy	367
Contents	367
See Also	368
HttpRoute	369
Contents	369
See Also	369
HttpRouteAction	371
Contents	371
See Also	371
HttpRouteHeader	372
Contents	372
See Also	372
HttpRouteMatch	374
Contents	374
See Also	375
HttpTimeout	376
Contents	376
See Also	376
JsonFormatRef	377
Contents	377
See Also	377
Listener	378
Contents	378
See Also	379
ListenerTimeout	380
Contents	380
See Also	381
ListenerTls	382
Contents	382

See Also	382
ListenerTlsAcmeCertificate	384
Contents	384
See Also	384
ListenerTlsCertificate	385
Contents	385
See Also	385
ListenerTlsFileCertificate	387
Contents	387
See Also	387
ListenerTlsSdsCertificate	388
Contents	388
See Also	388
ListenerTlsValidationContext	389
Contents	389
See Also	389
ListenerTlsValidationContextTrust	390
Contents	390
See Also	390
Logging	391
Contents	391
See Also	391
LoggingFormat	392
Contents	392
See Also	392
MatchRange	393
Contents	393
See Also	393
MeshData	394
Contents	394
See Also	394
MeshRef	396
Contents	396
See Also	397
MeshServiceDiscovery	398
Contents	398

See Also	398
MeshSpec	399
Contents	399
See Also	399
MeshStatus	400
Contents	400
See Also	400
OutlierDetection	401
Contents	401
See Also	402
PortMapping	403
Contents	403
See Also	403
QueryParamMatch	404
Contents	404
See Also	404
ResourceMetadata	405
Contents	405
See Also	406
RouteData	407
Contents	407
See Also	408
RouteRef	409
Contents	409
See Also	411
RouteSpec	412
Contents	412
See Also	413
RouteStatus	414
Contents	414
See Also	414
ServiceDiscovery	415
Contents	415
See Also	415
SubjectAlternativeNameMatchers	416
Contents	416

See Also	416
SubjectAlternativeNames	417
Contents	417
See Also	417
TagRef	418
Contents	418
See Also	418
TcpRoute	419
Contents	419
See Also	419
TcpRouteAction	420
Contents	420
See Also	420
TcpRouteMatch	421
Contents	421
See Also	421
TcpTimeout	422
Contents	422
See Also	422
TlsValidationContext	423
Contents	423
See Also	423
TlsValidationContextAcmTrust	425
Contents	425
See Also	425
TlsValidationContextFileTrust	426
Contents	426
See Also	426
TlsValidationContextSdsTrust	427
Contents	427
See Also	427
TlsValidationContextTrust	428
Contents	428
See Also	428
VirtualGatewayAccessLog	430
Contents	430

See Also	430
VirtualGatewayBackendDefaults	431
Contents	431
See Also	431
VirtualGatewayClientPolicy	432
Contents	432
See Also	432
VirtualGatewayClientPolicyTls	433
Contents	433
See Also	434
VirtualGatewayClientTlsCertificate	435
Contents	435
See Also	435
VirtualGatewayConnectionPool	437
Contents	437
See Also	438
VirtualGatewayData	439
Contents	439
See Also	440
VirtualGatewayFileAccessLog	441
Contents	441
See Also	441
VirtualGatewayGrpcConnectionPool	442
Contents	442
See Also	442
VirtualGatewayHealthCheckPolicy	443
Contents	443
See Also	444
VirtualGatewayHttp2ConnectionPool	445
Contents	445
See Also	445
VirtualGatewayHttpConnectionPool	446
Contents	446
See Also	446
VirtualGatewayListener	447
Contents	447

See Also	447
VirtualGatewayListenerTls	449
Contents	449
See Also	449
VirtualGatewayListenerTlsAcmCertificate	451
Contents	451
See Also	451
VirtualGatewayListenerTlsCertificate	452
Contents	452
See Also	452
VirtualGatewayListenerTlsFileCertificate	454
Contents	454
See Also	454
VirtualGatewayListenerTlsSdsCertificate	455
Contents	455
See Also	455
VirtualGatewayListenerTlsValidationContext	456
Contents	456
See Also	456
VirtualGatewayListenerTlsValidationContextTrust	457
Contents	457
See Also	457
VirtualGatewayLogging	459
Contents	459
See Also	459
VirtualGatewayPortMapping	460
Contents	460
See Also	460
VirtualGatewayRef	461
Contents	461
See Also	462
VirtualGatewaySpec	464
Contents	464
See Also	464
VirtualGatewayStatus	465
Contents	465

See Also	465
VirtualGatewayTlsValidationContext	466
Contents	466
See Also	466
VirtualGatewayTlsValidationContextAcmTrust	467
Contents	467
See Also	467
VirtualGatewayTlsValidationContextFileTrust	468
Contents	468
See Also	468
VirtualGatewayTlsValidationContextSdsTrust	469
Contents	469
See Also	469
VirtualGatewayTlsValidationContextTrust	470
Contents	470
See Also	470
VirtualNodeConnectionPool	472
Contents	472
See Also	473
VirtualNodeData	474
Contents	474
See Also	475
VirtualNodeGrpcConnectionPool	476
Contents	476
See Also	476
VirtualNodeHttp2ConnectionPool	477
Contents	477
See Also	477
VirtualNodeHttpConnectionPool	478
Contents	478
See Also	478
VirtualNodeRef	479
Contents	479
See Also	480
VirtualNodeServiceProvider	482
Contents	482

See Also	482
VirtualNodeSpec	483
Contents	483
See Also	484
VirtualNodeStatus	485
Contents	485
See Also	485
VirtualNodeTcpConnectionPool	486
Contents	486
See Also	486
VirtualRouterData	487
Contents	487
See Also	488
VirtualRouterListener	489
Contents	489
See Also	489
VirtualRouterRef	490
Contents	490
See Also	491
VirtualRouterServiceProvider	493
Contents	493
See Also	493
VirtualRouterSpec	494
Contents	494
See Also	494
VirtualRouterStatus	495
Contents	495
See Also	495
VirtualServiceBackend	496
Contents	496
See Also	496
VirtualServiceData	497
Contents	497
See Also	498
VirtualServiceProvider	499
Contents	499

See Also 499

VirtualServiceRef 500

 Contents 500

 See Also 501

VirtualServiceSpec 503

 Contents 503

 See Also 503

VirtualServiceStatus 504

 Contents 504

 See Also 504

WeightedTarget 505

 Contents 505

 See Also 505

Welcome

AWS App Mesh is a service mesh based on the Envoy proxy that makes it easy to monitor and control microservices. App Mesh standardizes how your microservices communicate, giving you end-to-end visibility and helping to ensure high availability for your applications.

App Mesh gives you consistent visibility and network traffic controls for every microservice in an application. You can use App Mesh with AWS Fargate, Amazon ECS, Amazon EKS, Kubernetes on AWS, and Amazon EC2.

Note

App Mesh supports microservice applications that use service discovery naming for their components. For more information about service discovery on Amazon ECS, see [Service Discovery](#) in the *Amazon Elastic Container Service Developer Guide*. Kubernetes kube-dns and coredns are supported. For more information, see [DNS for Services and Pods](#) in the Kubernetes documentation.

This document was last published on November 15, 2025.

Actions

The following actions are supported:

- [CreateGatewayRoute](#)
- [CreateMesh](#)
- [CreateRoute](#)
- [CreateVirtualGateway](#)
- [CreateVirtualNode](#)
- [CreateVirtualRouter](#)
- [CreateVirtualService](#)
- [DeleteGatewayRoute](#)
- [DeleteMesh](#)
- [DeleteRoute](#)
- [DeleteVirtualGateway](#)
- [DeleteVirtualNode](#)
- [DeleteVirtualRouter](#)
- [DeleteVirtualService](#)
- [DescribeGatewayRoute](#)
- [DescribeMesh](#)
- [DescribeRoute](#)
- [DescribeVirtualGateway](#)
- [DescribeVirtualNode](#)
- [DescribeVirtualRouter](#)
- [DescribeVirtualService](#)
- [ListGatewayRoutes](#)
- [ListMeshes](#)
- [ListRoutes](#)
- [ListTagsForResource](#)
- [ListVirtualGateways](#)
- [ListVirtualNodes](#)

- [ListVirtualRouters](#)
- [ListVirtualServices](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateGatewayRoute](#)
- [UpdateMesh](#)
- [UpdateRoute](#)
- [UpdateVirtualGateway](#)
- [UpdateVirtualNode](#)
- [UpdateVirtualRouter](#)
- [UpdateVirtualService](#)

CreateGatewayRoute

Creates a gateway route.

A gateway route is attached to a virtual gateway and routes traffic to an existing virtual service. If a route matches a request, it can distribute traffic to a target virtual service.

For more information about gateway routes, see [Gateway routes](#).

Request Syntax

```
PUT /v20190125/meshes/meshName/virtualGateway/virtualGatewayName/gatewayRoutes?
meshOwner=meshOwner HTTP/1.1
Content-type: application/json
```

```
{
  "clientToken": "string",
  "gatewayRouteName": "string",
  "spec": {
    "grpcRoute": {
      "action": {
        "rewrite": {
          "hostname": {
            "defaultTargetHostname": "string"
          }
        },
        "target": {
          "port": number,
          "virtualService": {
            "virtualServiceName": "string"
          }
        }
      },
      "match": {
        "hostname": {
          "exact": "string",
          "suffix": "string"
        },
        "metadata": [
          {
            "invert": boolean,
            "match": { ... },
            "name": "string"
          }
        ]
      }
    }
  }
}
```



```

    }
  ],
  "port": number,
  "serviceName": "string"
}
},
"http2Route": {
  "action": {
    "rewrite": {
      "hostname": {
        "defaultTargetHostname": "string"
      },
      "path": {
        "exact": "string"
      },
      "prefix": {
        "defaultPrefix": "string",
        "value": "string"
      }
    },
    "target": {
      "port": number,
      "virtualService": {
        "virtualServiceName": "string"
      }
    }
  },
  "match": {
    "headers": [
      {
        "invert": boolean,
        "match": { ... },
        "name": "string"
      }
    ],
    "hostname": {
      "exact": "string",
      "suffix": "string"
    },
    "method": "string",
    "path": {
      "exact": "string",
      "regex": "string"
    }
  },

```

```

    "port": number,
    "prefix": "string",
    "queryParameters": [
      {
        "match": {
          "exact": "string"
        },
        "name": "string"
      }
    ]
  },
  "httpRoute": {
    "action": {
      "rewrite": {
        "hostname": {
          "defaultTargetHostname": "string"
        },
        "path": {
          "exact": "string"
        },
        "prefix": {
          "defaultPrefix": "string",
          "value": "string"
        }
      },
      "target": {
        "port": number,
        "virtualService": {
          "virtualServiceName": "string"
        }
      }
    },
    "match": {
      "headers": [
        {
          "invert": boolean,
          "match": { ... },
          "name": "string"
        }
      ],
      "hostname": {
        "exact": "string",
        "suffix": "string"
      }
    }
  }
}

```

```
    },
    "method": "string",
    "path": {
      "exact": "string",
      "regex": "string"
    },
    "port": number,
    "prefix": "string",
    "queryParameters": [
      {
        "match": {
          "exact": "string"
        },
        "name": "string"
      }
    ]
  },
  "priority": number
},
"tags": [
  {
    "key": "string",
    "value": "string"
  }
]
}
```

URI Request Parameters

The request uses the following URI parameters.

meshName

The name of the service mesh to create the gateway route in.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then the account that you specify must share the mesh with your account before you can create

the resource in the service mesh. For more information about mesh sharing, see [Working with shared meshes](#).

Length Constraints: Fixed length of 12.

[**virtualGatewayName**](#)

The name of the virtual gateway to associate the gateway route with. If the virtual gateway is in a shared mesh, then you must be the owner of the virtual gateway resource.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

Request Body

The request accepts the following data in JSON format.

[**clientToken**](#)

Unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Up to 36 letters, numbers, hyphens, and underscores are allowed.

Type: String

Required: No

[**gatewayRouteName**](#)

The name to use for the gateway route.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

[**spec**](#)

The gateway route specification to apply.

Type: [**GatewayRouteSpec**](#) object

Required: Yes

tags

Optional metadata that you can apply to the gateway route to assist with categorization and organization. Each tag consists of a key and an optional value, both of which you define. Tag keys can have a maximum character length of 128 characters, and tag values can have a maximum length of 256 characters.

Type: Array of [TagRef](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "gatewayRouteName": "string",
  "meshName": "string",
  "metadata": {
    "arn": "string",
    "createdAt": number,
    "lastUpdatedAt": number,
    "meshOwner": "string",
    "resourceOwner": "string",
    "uid": "string",
    "version": number
  },
  "spec": {
    "grpcRoute": {
      "action": {
        "rewrite": {
          "hostname": {
            "defaultTargetHostname": "string"
          }
        }
      },
      "target": {
        "port": number,
        "virtualService": {
          "virtualServiceName": "string"
        }
      }
    }
  }
}
```

```

    }
  }
},
"match": {
  "hostname": {
    "exact": "string",
    "suffix": "string"
  },
  "metadata": [
    {
      "invert": boolean,
      "match": { ... },
      "name": "string"
    }
  ],
  "port": number,
  "serviceName": "string"
}
},
"http2Route": {
  "action": {
    "rewrite": {
      "hostname": {
        "defaultTargetHostname": "string"
      },
      "path": {
        "exact": "string"
      },
      "prefix": {
        "defaultPrefix": "string",
        "value": "string"
      }
    },
    "target": {
      "port": number,
      "virtualService": {
        "virtualServiceName": "string"
      }
    }
  },
  "match": {
    "headers": [
      {
        "invert": boolean,

```

```

        "match": { ... },
        "name": "string"
    }
],
"hostname": {
    "exact": "string",
    "suffix": "string"
},
"method": "string",
"path": {
    "exact": "string",
    "regex": "string"
},
"port": number,
"prefix": "string",
"queryParameters": [
    {
        "match": {
            "exact": "string"
        },
        "name": "string"
    }
]
},
"httpRoute": {
    "action": {
        "rewrite": {
            "hostname": {
                "defaultTargetHostname": "string"
            },
            "path": {
                "exact": "string"
            },
            "prefix": {
                "defaultPrefix": "string",
                "value": "string"
            }
        },
        "target": {
            "port": number,
            "virtualService": {
                "virtualServiceName": "string"
            }
        }
    }
}

```

```

    }
  },
  "match": {
    "headers": [
      {
        "invert": boolean,
        "match": { ... },
        "name": "string"
      }
    ],
    "hostname": {
      "exact": "string",
      "suffix": "string"
    },
    "method": "string",
    "path": {
      "exact": "string",
      "regex": "string"
    },
    "port": number,
    "prefix": "string",
    "queryParameters": [
      {
        "match": {
          "exact": "string"
        },
        "name": "string"
      }
    ]
  },
  "priority": number
},
"status": {
  "status": "string"
},
"virtualGatewayName": "string"
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

gatewayRouteName

The name of the gateway route.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

meshName

The name of the service mesh that the resource resides in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

metadata

An object that represents metadata for a resource.

Type: [ResourceMetadata](#) object

spec

The specifications of the gateway route.

Type: [GatewayRouteSpec](#) object

status

The status of the gateway route.

Type: [GatewayRouteStatus](#) object

virtualGatewayName

The virtual gateway that the gateway route is associated with.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ConflictException

The request contains a client token that was used for a previous update resource call with different specifications. Try the request again with a new client token.

HTTP Status Code: 409

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

LimitExceededException

You have exceeded a service limit for your account. For more information, see [Service Limits](#) in the *AWS App Mesh User Guide*.

HTTP Status Code: 400

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You need to learn how to sign HTTP requests only if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

The following example creates an HTTP/2 gateway route named `myGatewayRoute` that is associated to a virtual gateway named `myVirtualGateway` in the `apps` service mesh. The route routes all traffic to the virtual service named `myservicea.svc.cluster.local`.

Sample Request

```
PUT /v20190125/meshes/apps/virtualGateways HTTP/1.1
Host: appmesh.us-west-2.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.16.298 Python/3.6.0 Windows/10 botocore/1.13.34
X-Amz-Date: 20200608T194401Z
Authorization: AUTHPARAMS
```

```
{
  "gatewayRouteName": "myGatewayRoute",
  "spec": {
    "http2Route": {
      "action": {
        "target": {
          "virtualService": {
```

```
    "virtualServiceName": "myservicea.svc.cluster.local"
  }
}
},
"match": {
  "prefix": "/"
}
}
},
"clientToken": "1aa1111a-1111-1111-111a-a1a1a1aa111a"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-requestid: 696b569b-3593-446d-832c-0a38ce1c53ac
content-type: application/json
content-length: 517
date: Mon, 08 Jun 2020 19:44:02 GMT
x-envoy-upstream-service-time: 48
server: envoy
Connection: keep-alive

{
  "gatewayRouteName": "myGatewayRoute",
  "meshName": "myApps",
  "metadata": {
    "arn": "arn:aws:appmesh:us-west-2:123456789012:mesh/apps/virtualGateway/myVirtualGateway/gatewayRoute/myGatewayRoute",
    "createdAt": 1.591642091122E9,
    "lastUpdatedAt": 1.591642091122E9,
    "meshOwner": "123456789012",
    "resourceOwner": "123456789012",
    "uid": "ff111ff2-33ff-4ff4-ffff-111f111f111f",
    "version": 1
  },
  "spec": {
    "grpcRoute": null,
    "http2Route": {
      "action": {
        "target": {
          "virtualService": {
            "virtualServiceName": "myservicea.svc.cluster.local"
          }
        }
      }
    }
  }
}
```

```
    }
  }
},
"match": {
  "prefix": "/"
}
},
"httpRoute": null
},
"status": {
  "status": "ACTIVE"
},
"virtualGatewayName": "myVirtualGateway"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateMesh

Creates a service mesh.

A service mesh is a logical boundary for network traffic between services that are represented by resources within the mesh. After you create your service mesh, you can create virtual services, virtual nodes, virtual routers, and routes to distribute traffic between the applications in your mesh.

For more information about service meshes, see [Service meshes](#).

Request Syntax

```
PUT /v20190125/meshes HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "meshName": "string",
  "spec": {
    "egressFilter": {
      "type": "string"
    },
    "serviceDiscovery": {
      "ipPreference": "string"
    }
  },
  "tags": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

Unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Up to 36 letters, numbers, hyphens, and underscores are allowed.

Type: String

Required: No

meshName

The name to use for the service mesh.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

spec

The service mesh specification to apply.

Type: [MeshSpec](#) object

Required: No

tags

Optional metadata that you can apply to the service mesh to assist with categorization and organization. Each tag consists of a key and an optional value, both of which you define. Tag keys can have a maximum character length of 128 characters, and tag values can have a maximum length of 256 characters.

Type: Array of [TagRef](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "meshName": "string",
  "metadata": {
    "arn": "string",
    "createdAt": number,
    "lastUpdatedAt": number,
    "meshOwner": "string",
    "resourceOwner": "string",
    "uid": "string",
    "version": number
  },
  "spec": {
    "egressFilter": {
      "type": "string"
    },
    "serviceDiscovery": {
      "ipPreference": "string"
    }
  },
  "status": {
    "status": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

meshName

The name of the service mesh.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

metadata

The associated metadata for the service mesh.

Type: [ResourceMetadata](#) object

spec

The associated specification for the service mesh.

Type: [MeshSpec](#) object

status

The status of the service mesh.

Type: [MeshStatus](#) object

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ConflictException

The request contains a client token that was used for a previous update resource call with different specifications. Try the request again with a new client token.

HTTP Status Code: 409

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

LimitExceededException

You have exceeded a service limit for your account. For more information, see [Service Limits](#) in the *AWS App Mesh User Guide*.

HTTP Status Code: 400

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You need to learn how to sign HTTP requests only if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

The following example creates a service mesh named `ecs-mesh`.

Sample Request

```
PUT /v20190125/meshes HTTP/1.1
Host: appmesh.us-east-1.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.16.56 Python/3.7.0 Darwin/17.7.0 botocore/1.12.46
X-Amz-Date: 20190227T192324Z
```

Authorization: AUTHPARAMS

```
{
  "meshName": "ecs-mesh",
  "clientToken": "34a20934-da3a-43a0-9d1b-390308a7393b"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-requestid: 5c2f774d-da0b-40f3-80c5-d8711eb15dce
content-type: application/json
content-length: 245
date: Wed, 27 Feb 2019 19:23:24 GMT
x-envoy-upstream-service-time: 76
server: envoy
Connection: keep-alive

{
  "meshName": "ecs-mesh",
  "metadata": {
    "arn": "arn:aws:appmesh:us-east-1:123456789012:mesh/ecs-mesh",
    "createdAt": 1.551295405298E9,
    "lastUpdatedAt": 1.551295405298E9,
    "uid": "2d29a11c-f2dd-44a6-b620-33661cfdfe97",
    "version": 1
  },
  "status": {
    "status": "ACTIVE"
  }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateRoute

Creates a route that is associated with a virtual router.

You can route several different protocols and define a retry policy for a route. Traffic can be routed to one or more virtual nodes.

For more information about routes, see [Routes](#).

Request Syntax

```
PUT /v20190125/meshes/meshName/virtualRouter/virtualRouterName/routes?
meshOwner=meshOwner HTTP/1.1
Content-type: application/json
```

```
{
  "clientToken": "string",
  "routeName": "string",
  "spec": {
    "grpcRoute": {
      "action": {
        "weightedTargets": [
          {
            "port": number,
            "virtualNode": "string",
            "weight": number
          }
        ]
      },
      "match": {
        "metadata": [
          {
            "invert": boolean,
            "match": { ... },
            "name": "string"
          }
        ],
        "methodName": "string",
        "port": number,
        "serviceName": "string"
      },
      "retryPolicy": {
        "grpcRetryEvents": [ "string" ],

```

```

    "httpRetryEvents": [ "string" ],
    "maxRetries": number,
    "perRetryTimeout": {
        "unit": "string",
        "value": number
    },
    "tcpRetryEvents": [ "string" ]
},
"timeout": {
    "idle": {
        "unit": "string",
        "value": number
    },
    "perRequest": {
        "unit": "string",
        "value": number
    }
}
},
"http2Route": {
    "action": {
        "weightedTargets": [
            {
                "port": number,
                "virtualNode": "string",
                "weight": number
            }
        ]
    },
    "match": {
        "headers": [
            {
                "invert": boolean,
                "match": { ... },
                "name": "string"
            }
        ],
        "method": "string",
        "path": {
            "exact": "string",
            "regex": "string"
        },
        "port": number,
        "prefix": "string",

```

```

    "queryParameters": [
      {
        "match": {
          "exact": "string"
        },
        "name": "string"
      }
    ],
    "scheme": "string"
  },
  "retryPolicy": {
    "httpRetryEvents": [ "string" ],
    "maxRetries": number,
    "perRetryTimeout": {
      "unit": "string",
      "value": number
    },
    "tcpRetryEvents": [ "string" ]
  },
  "timeout": {
    "idle": {
      "unit": "string",
      "value": number
    },
    "perRequest": {
      "unit": "string",
      "value": number
    }
  }
},
"httpRoute": {
  "action": {
    "weightedTargets": [
      {
        "port": number,
        "virtualNode": "string",
        "weight": number
      }
    ]
  },
  "match": {
    "headers": [
      {
        "invert": boolean,

```

```

        "match": { ... },
        "name": "string"
    }
],
"method": "string",
"path": {
    "exact": "string",
    "regex": "string"
},
"port": number,
"prefix": "string",
"queryParameters": [
    {
        "match": {
            "exact": "string"
        },
        "name": "string"
    }
],
"scheme": "string"
},
"retryPolicy": {
    "httpRetryEvents": [ "string" ],
    "maxRetries": number,
    "perRetryTimeout": {
        "unit": "string",
        "value": number
    },
    "tcpRetryEvents": [ "string" ]
},
"timeout": {
    "idle": {
        "unit": "string",
        "value": number
    },
    "perRequest": {
        "unit": "string",
        "value": number
    }
}
},
"priority": number,
"tcpRoute": {
    "action": {

```



```
    "weightedTargets": [
      {
        "port": number,
        "virtualNode": "string",
        "weight": number
      }
    ],
    "match": {
      "port": number
    },
    "timeout": {
      "idle": {
        "unit": "string",
        "value": number
      }
    }
  },
  "tags": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}
```

URI Request Parameters

The request uses the following URI parameters.

meshName

The name of the service mesh to create the route in.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then the account that you specify must share the mesh with your account before you can create

the resource in the service mesh. For more information about mesh sharing, see [Working with shared meshes](#).

Length Constraints: Fixed length of 12.

[**virtualRouterName**](#)

The name of the virtual router in which to create the route. If the virtual router is in a shared mesh, then you must be the owner of the virtual router resource.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

Request Body

The request accepts the following data in JSON format.

[**clientToken**](#)

Unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Up to 36 letters, numbers, hyphens, and underscores are allowed.

Type: String

Required: No

[**routeName**](#)

The name to use for the route.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

[**spec**](#)

The route specification to apply.

Type: [RouteSpec](#) object

Required: Yes

tags

Optional metadata that you can apply to the route to assist with categorization and organization. Each tag consists of a key and an optional value, both of which you define. Tag keys can have a maximum character length of 128 characters, and tag values can have a maximum length of 256 characters.

Type: Array of [TagRef](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "meshName": "string",
  "metadata": {
    "arn": "string",
    "createdAt": number,
    "lastUpdatedAt": number,
    "meshOwner": "string",
    "resourceOwner": "string",
    "uid": "string",
    "version": number
  },
  "routeName": "string",
  "spec": {
    "grpcRoute": {
      "action": {
        "weightedTargets": [
          {
            "port": number,
            "virtualNode": "string",
            "weight": number
          }
        ]
      }
    },
    "match": {
```

```

    "metadata": [
      {
        "invert": boolean,
        "match": { ... },
        "name": "string"
      }
    ],
    "methodName": "string",
    "port": number,
    "serviceName": "string"
  },
  "retryPolicy": {
    "grpcRetryEvents": [ "string" ],
    "httpRetryEvents": [ "string" ],
    "maxRetries": number,
    "perRetryTimeout": {
      "unit": "string",
      "value": number
    },
    "tcpRetryEvents": [ "string" ]
  },
  "timeout": {
    "idle": {
      "unit": "string",
      "value": number
    },
    "perRequest": {
      "unit": "string",
      "value": number
    }
  }
},
"http2Route": {
  "action": {
    "weightedTargets": [
      {
        "port": number,
        "virtualNode": "string",
        "weight": number
      }
    ]
  },
  "match": {
    "headers": [

```

```

        {
            "invert": boolean,
            "match": { ... },
            "name": "string"
        }
    ],
    "method": "string",
    "path": {
        "exact": "string",
        "regex": "string"
    },
    "port": number,
    "prefix": "string",
    "queryParameters": [
        {
            "match": {
                "exact": "string"
            },
            "name": "string"
        }
    ],
    "scheme": "string"
},
"retryPolicy": {
    "httpRetryEvents": [ "string" ],
    "maxRetries": number,
    "perRetryTimeout": {
        "unit": "string",
        "value": number
    },
    "tcpRetryEvents": [ "string" ]
},
"timeout": {
    "idle": {
        "unit": "string",
        "value": number
    },
    "perRequest": {
        "unit": "string",
        "value": number
    }
}
},
"httpRoute": {

```

```

    "action": {
      "weightedTargets": [
        {
          "port": number,
          "virtualNode": "string",
          "weight": number
        }
      ]
    },
    "match": {
      "headers": [
        {
          "invert": boolean,
          "match": { ... },
          "name": "string"
        }
      ],
      "method": "string",
      "path": {
        "exact": "string",
        "regex": "string"
      },
      "port": number,
      "prefix": "string",
      "queryParameters": [
        {
          "match": {
            "exact": "string"
          },
          "name": "string"
        }
      ],
      "scheme": "string"
    },
    "retryPolicy": {
      "httpRetryEvents": [ "string" ],
      "maxRetries": number,
      "perRetryTimeout": {
        "unit": "string",
        "value": number
      },
      "tcpRetryEvents": [ "string" ]
    },
    "timeout": {

```

```

    "idle": {
      "unit": "string",
      "value": number
    },
    "perRequest": {
      "unit": "string",
      "value": number
    }
  },
  "priority": number,
  "tcpRoute": {
    "action": {
      "weightedTargets": [
        {
          "port": number,
          "virtualNode": "string",
          "weight": number
        }
      ]
    },
    "match": {
      "port": number
    },
    "timeout": {
      "idle": {
        "unit": "string",
        "value": number
      }
    }
  }
},
"status": {
  "status": "string"
},
"virtualRouterName": "string"
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

meshName

The name of the service mesh that the route resides in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

metadata

The associated metadata for the route.

Type: [ResourceMetadata](#) object

routeName

The name of the route.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

spec

The specifications of the route.

Type: [RouteSpec](#) object

status

The status of the route.

Type: [RouteStatus](#) object

virtualRouterName

The virtual router that the route is associated with.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ConflictException

The request contains a client token that was used for a previous update resource call with different specifications. Try the request again with a new client token.

HTTP Status Code: 409

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

LimitExceededException

You have exceeded a service limit for your account. For more information, see [Service Limits](#) in the *AWS App Mesh User Guide*.

HTTP Status Code: 400

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You need to learn how to sign HTTP requests only if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

The following example creates a route named colorgateway-route for the colorgateway-vr virtual router in the ecs-mesh service mesh. The route directs all traffic to the colorgateway-vn virtual node.

Sample Request

```
PUT /v20190125/meshes/ecs-mesh/virtualRouter/colorgateway-vr/routes HTTP/1.1
Host: appmesh.us-east-1.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.16.56 Python/3.7.0 Darwin/17.7.0 botocore/1.12.46
X-Amz-Date: 20190227T192454Z
Authorization: AUTHPARAMS

{
  "routeName": "colorgateway-route",
  "spec": {
    "httpRoute": {
      "action": {
        "weightedTargets": [
          {
            "virtualNode": "colorgateway-vn",
            "weight": 100
          }
        ]
      },
      "match": {
        "prefix": "/"
      }
    }
  }
}
```

```
}
},
"clientToken": "a785b959-201d-49d7-b81d-32e7f393968f"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-requestid: 159941a8-18be-423c-89fe-3beb9542ca3f
content-type: application/json
content-length: 511
date: Wed, 27 Feb 2019 19:24:54 GMT
x-envoy-upstream-service-time: 59
server: envoy
Connection: keep-alive

{
  "meshName": "ecs-mesh",
  "metadata": {
    "arn": "arn:aws:appmesh:us-east-1:123456789012:mesh/ecs-mesh/virtualRouter/
colorgateway-vr/route/colorgateway-route",
    "createdAt": 1.551295495004E9,
    "lastUpdatedAt": 1.551295495004E9,
    "uid": "3251bf37-2d01-4b79-be96-d0c36c61511f",
    "version": 1
  },
  "routeName": "colorgateway-route",
  "spec": {
    "httpRoute": {
      "action": {
        "weightedTargets": [{
          "virtualNode": "colorgateway-vn",
          "weight": 100
        }]
      },
      "match": {
        "prefix": "/"
      }
    },
    "tcpRoute": null
  },
  "status": {
    "status": "ACTIVE"
  }
}
```

```
},  
  "virtualRouterName": "colorgateway-vr"  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateVirtualGateway

Creates a virtual gateway.

A virtual gateway allows resources outside your mesh to communicate to resources that are inside your mesh. The virtual gateway represents an Envoy proxy running in an Amazon ECS task, in a Kubernetes service, or on an Amazon EC2 instance. Unlike a virtual node, which represents an Envoy running with an application, a virtual gateway represents Envoy deployed by itself.

For more information about virtual gateways, see [Virtual gateways](#).

Request Syntax

```
PUT /v20190125/meshes/meshName/virtualGateways?meshOwner=meshOwner HTTP/1.1
Content-type: application/json
```

```
{
  "clientToken": "string",
  "spec": {
    "backendDefaults": {
      "clientPolicy": {
        "tls": {
          "certificate": { ... },
          "enforce": boolean,
          "ports": [ number ],
          "validation": {
            "subjectAlternativeNames": {
              "match": {
                "exact": [ "string" ]
              }
            },
            "trust": { ... }
          }
        }
      }
    },
    "listeners": [
      {
        "connectionPool": { ... },
        "healthCheck": {
          "healthyThreshold": number,
          "intervalMillis": number,
          "path": "string",
```

```

        "port": number,
        "protocol": "string",
        "timeoutMillis": number,
        "unhealthyThreshold": number
    },
    "portMapping": {
        "port": number,
        "protocol": "string"
    },
    "tls": {
        "certificate": { ... },
        "mode": "string",
        "validation": {
            "subjectAlternativeNames": {
                "match": {
                    "exact": [ "string" ]
                }
            },
            "trust": { ... }
        }
    }
},
"logging": {
    "accessLog": { ... }
},
"tags": [
    {
        "key": "string",
        "value": "string"
    }
],
"virtualGatewayName": "string"
}

```

URI Request Parameters

The request uses the following URI parameters.

meshName

The name of the service mesh to create the virtual gateway in.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then the account that you specify must share the mesh with your account before you can create the resource in the service mesh. For more information about mesh sharing, see [Working with shared meshes](#).

Length Constraints: Fixed length of 12.

Request Body

The request accepts the following data in JSON format.

clientToken

Unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Up to 36 letters, numbers, hyphens, and underscores are allowed.

Type: String

Required: No

spec

The virtual gateway specification to apply.

Type: [VirtualGatewaySpec](#) object

Required: Yes

tags

Optional metadata that you can apply to the virtual gateway to assist with categorization and organization. Each tag consists of a key and an optional value, both of which you define. Tag keys can have a maximum character length of 128 characters, and tag values can have a maximum length of 256 characters.

Type: Array of [TagRef](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

virtualGatewayName

The name to use for the virtual gateway.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "meshName": "string",
  "metadata": {
    "arn": "string",
    "createdAt": number,
    "lastUpdatedAt": number,
    "meshOwner": "string",
    "resourceOwner": "string",
    "uid": "string",
    "version": number
  },
  "spec": {
    "backendDefaults": {
      "clientPolicy": {
        "tls": {
          "certificate": { ... },
          "enforce": boolean,
          "ports": [ number ],
          "validation": {
            "subjectAlternativeNames": {
              "match": {
                "exact": [ "string" ]
              }
            },
            "trust": { ... }
          }
        }
      }
    }
  }
}
```



```

    }
  },
  "listeners": [
    {
      "connectionPool": { ... },
      "healthCheck": {
        "healthyThreshold": number,
        "intervalMillis": number,
        "path": "string",
        "port": number,
        "protocol": "string",
        "timeoutMillis": number,
        "unhealthyThreshold": number
      },
      "portMapping": {
        "port": number,
        "protocol": "string"
      },
      "tls": {
        "certificate": { ... },
        "mode": "string",
        "validation": {
          "subjectAlternativeNames": {
            "match": {
              "exact": [ "string" ]
            }
          },
          "trust": { ... }
        }
      }
    }
  ],
  "logging": {
    "accessLog": { ... }
  }
},
"status": {
  "status": "string"
},
"virtualGatewayName": "string"
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

meshName

The name of the service mesh that the virtual gateway resides in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

metadata

An object that represents metadata for a resource.

Type: [ResourceMetadata](#) object

spec

The specifications of the virtual gateway.

Type: [VirtualGatewaySpec](#) object

status

The current status of the virtual gateway.

Type: [VirtualGatewayStatus](#) object

virtualGatewayName

The name of the virtual gateway.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ConflictException

The request contains a client token that was used for a previous update resource call with different specifications. Try the request again with a new client token.

HTTP Status Code: 409

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

LimitExceededException

You have exceeded a service limit for your account. For more information, see [Service Limits](#) in the *AWS App Mesh User Guide*.

HTTP Status Code: 400

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You need to learn how to sign HTTP requests only if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

The following example creates a virtual gateway named myVirtualGateway in the apps service mesh. The virtual gateway listens for http2 traffic on port 80.

Sample Request

```
PUT /v20190125/meshes/apps/virtualGateways HTTP/1.1
Host: appmesh.us-west-2.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.16.298 Python/3.6.0 Windows/10 botocore/1.13.34
X-Amz-Date: 20200706T144617Z
Authorization: AUTHPARAMS
Content-Length: 174

{
  "spec": {
    "listeners": [{
      "portMapping": {
        "port": 80,
        "protocol": "http2"
      }
    }]
  },
  "virtualGatewayName": "myVirtualGateway",
  "clientToken": "1aa1111a-1111-1111-111a-a1a1a1aa111a"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-requestid: 696b569b-3593-446d-832c-0a38ce1c53ac
content-type: application/json
content-length: 513
date: Mon, 06 Jul 2020 14:46:17 GMT
x-envoy-upstream-service-time: 33
server: envoy
Connection: keep-alive

{
  "meshName": "apps",
  "metadata": {
    "arn": "arn:aws:appmesh:us-west-2:123456789012:mesh/apps/virtualGateway/myVirtualGateway",
    "createdAt": 1.594046778215E9,
    "lastUpdatedAt": 1.594046778215E9,
    "meshOwner": "123456789012",
    "resourceOwner": "123456789012",
    "uid": "ff111ff2-33ff-4ff4-ffff-111f111f111f",
    "version": 1
  },
  "spec": {
    "backendDefaults": null,
    "listeners": [{
      "healthCheck": null,
      "portMapping": {
        "port": 80,
        "protocol": "http2"
      },
      "tls": null
    }],
    "logging": null
  },
  "status": {
    "status": "ACTIVE"
  },
  "virtualGatewayName": "myVirtualGateway"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateVirtualNode

Creates a virtual node within a service mesh.

A virtual node acts as a logical pointer to a particular task group, such as an Amazon ECS service or a Kubernetes deployment. When you create a virtual node, you can specify the service discovery information for your task group, and whether the proxy running in a task group will communicate with other proxies using Transport Layer Security (TLS).

You define a `listener` for any inbound traffic that your virtual node expects. Any virtual service that your virtual node expects to communicate to is specified as a backend.

The response metadata for your new virtual node contains the `arn` that is associated with the virtual node. Set this value to the full ARN; for example, `arn:aws:appmesh:us-west-2:123456789012:myMesh/default/virtualNode/myApp`) as the `APPMESH_RESOURCE_ARN` environment variable for your task group's Envoy proxy container in your task definition or pod spec. This is then mapped to the `node.id` and `node.cluster` Envoy parameters.

Note

By default, App Mesh uses the name of the resource you specified in `APPMESH_RESOURCE_ARN` when Envoy is referring to itself in metrics and traces. You can override this behavior by setting the `APPMESH_RESOURCE_CLUSTER` environment variable with your own name.

For more information about virtual nodes, see [Virtual nodes](#). You must be using 1.15.0 or later of the Envoy image when setting these variables. For more information about App Mesh Envoy variables, see [Envoy image](#) in the AWS App Mesh User Guide.

Request Syntax

```
PUT /v20190125/meshes/meshName/virtualNodes?meshOwner=meshOwner HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "spec": {
    "backendDefaults": {
```

```

    "clientPolicy": {
      "tls": {
        "certificate": { ... },
        "enforce": boolean,
        "ports": [ number ],
        "validation": {
          "subjectAlternativeNames": {
            "match": {
              "exact": [ "string" ]
            }
          },
          "trust": { ... }
        }
      }
    },
    "backends": [
      { ... }
    ],
    "listeners": [
      {
        "connectionPool": { ... },
        "healthCheck": {
          "healthyThreshold": number,
          "intervalMillis": number,
          "path": "string",
          "port": number,
          "protocol": "string",
          "timeoutMillis": number,
          "unhealthyThreshold": number
        },
        "outlierDetection": {
          "baseEjectionDuration": {
            "unit": "string",
            "value": number
          },
          "interval": {
            "unit": "string",
            "value": number
          },
          "maxEjectionPercent": number,
          "maxServerErrors": number
        },
        "portMapping": {

```



```

        "port": number,
        "protocol": "string"
    },
    "timeout": { ... },
    "tls": {
        "certificate": { ... },
        "mode": "string",
        "validation": {
            "subjectAlternativeNames": {
                "match": {
                    "exact": [ "string" ]
                }
            },
            "trust": { ... }
        }
    }
},
"logging": {
    "accessLog": { ... }
},
"serviceDiscovery": { ... }
},
"tags": [
    {
        "key": "string",
        "value": "string"
    }
],
"virtualNodeName": "string"
}

```

URI Request Parameters

The request uses the following URI parameters.

meshName

The name of the service mesh to create the virtual node in.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then the account that you specify must share the mesh with your account before you can create the resource in the service mesh. For more information about mesh sharing, see [Working with shared meshes](#).

Length Constraints: Fixed length of 12.

Request Body

The request accepts the following data in JSON format.

clientToken

Unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Up to 36 letters, numbers, hyphens, and underscores are allowed.

Type: String

Required: No

spec

The virtual node specification to apply.

Type: [VirtualNodeSpec](#) object

Required: Yes

tags

Optional metadata that you can apply to the virtual node to assist with categorization and organization. Each tag consists of a key and an optional value, both of which you define. Tag keys can have a maximum character length of 128 characters, and tag values can have a maximum length of 256 characters.

Type: Array of [TagRef](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

virtualNodeName

The name to use for the virtual node.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "meshName": "string",
  "metadata": {
    "arn": "string",
    "createdAt": number,
    "lastUpdatedAt": number,
    "meshOwner": "string",
    "resourceOwner": "string",
    "uid": "string",
    "version": number
  },
  "spec": {
    "backendDefaults": {
      "clientPolicy": {
        "tls": {
          "certificate": { ... },
          "enforce": boolean,
          "ports": [ number ],
          "validation": {
            "subjectAlternativeNames": {
              "match": {
                "exact": [ "string" ]
              }
            },
            "trust": { ... }
          }
        }
      }
    }
  }
}
```

```

},
"backends": [
  { ... }
],
"listeners": [
  {
    "connectionPool": { ... },
    "healthCheck": {
      "healthyThreshold": number,
      "intervalMillis": number,
      "path": "string",
      "port": number,
      "protocol": "string",
      "timeoutMillis": number,
      "unhealthyThreshold": number
    },
    "outlierDetection": {
      "baseEjectionDuration": {
        "unit": "string",
        "value": number
      },
      "interval": {
        "unit": "string",
        "value": number
      },
      "maxEjectionPercent": number,
      "maxServerErrors": number
    },
    "portMapping": {
      "port": number,
      "protocol": "string"
    },
    "timeout": { ... },
    "tls": {
      "certificate": { ... },
      "mode": "string",
      "validation": {
        "subjectAlternativeNames": {
          "match": {
            "exact": [ "string" ]
          }
        },
        "trust": { ... }
      }
    }
  }
]

```

```
    }
  },
],
"logging": {
  "accessLog": { ... }
},
"serviceDiscovery": { ... }
},
"status": {
  "status": "string"
},
"virtualNodeName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

meshName

The name of the service mesh that the virtual node resides in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

metadata

The associated metadata for the virtual node.

Type: [ResourceMetadata](#) object

spec

The specifications of the virtual node.

Type: [VirtualNodeSpec](#) object

status

The current status for the virtual node.

Type: [VirtualNodeStatus](#) object

virtualNodeName

The name of the virtual node.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ConflictException

The request contains a client token that was used for a previous update resource call with different specifications. Try the request again with a new client token.

HTTP Status Code: 409

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

LimitExceededException

You have exceeded a service limit for your account. For more information, see [Service Limits](#) in the *AWS App Mesh User Guide*.

HTTP Status Code: 400

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You need to learn how to sign HTTP requests only if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

The following example creates a virtual node named colorgateway-vn in the ecs-mesh service mesh.

Sample Request

```
PUT /v20190125/meshes/ecs-mesh/virtualNodes HTTP/1.1
Host: appmesh.us-east-1.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.16.56 Python/3.7.0 Darwin/17.7.0 botocore/1.12.46
X-Amz-Date: 20190227T192431Z
Authorization: AUTHPARAMS

{
```

```
"spec": {
  "listeners": [
    {
      "portMapping": {
        "port": 9080,
        "protocol": "http"
      }
    }
  ],
  "serviceDiscovery": {
    "dns": {
      "hostname": "colorgateway.default.svc.cluster.local"
    }
  },
  "backends": [
    {
      "virtualService": {
        "virtualServiceName": "tcpecho.default.svc.cluster.local"
      }
    },
    {
      "virtualService": {
        "virtualServiceName": "colorteller.default.svc.cluster.local"
      }
    }
  ],
  "virtualNodeName": "colorgateway-vn",
  "clientToken": "c148ccbb-3619-49da-bb3e-4561eb5370c4"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-requestid: cc29e2dd-e4c4-4d6e-9424-e9211580f70e
content-type: application/json
content-length: 687
date: Wed, 27 Feb 2019 19:24:31 GMT
x-envoy-upstream-service-time: 132
server: envoy
Connection: keep-alive

{
```



```
"meshName": "ecs-mesh",
"metadata": {
  "arn": "arn:aws:appmesh:us-east-1:123456789012:mesh/ecs-mesh/virtualNode/
colorgateway-vn",
  "createdAt": 1.551295471546E9,
  "lastUpdatedAt": 1.551295471546E9,
  "uid": "887cfab8-a727-41b2-8cd7-2fdebfd6304e",
  "version": 1
},
"spec": {
  "backends": [{
    "virtualService": {
      "virtualServiceName": "tcpecho.default.svc.cluster.local"
    }
  }, {
    "virtualService": {
      "virtualServiceName": "colorteller.default.svc.cluster.local"
    }
  }],
  "listeners": [{
    "healthCheck": null,
    "portMapping": {
      "port": 9080,
      "protocol": "http"
    }
  }],
  "logging": null,
  "serviceDiscovery": {
    "dns": {
      "hostname": "colorgateway.default.svc.cluster.local"
    }
  }
},
"status": {
  "status": "ACTIVE"
},
"virtualNodeName": "colorgateway-vn"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateVirtualRouter

Creates a virtual router within a service mesh.

Specify a `listener` for any inbound traffic that your virtual router receives. Create a virtual router for each protocol and port that you need to route. Virtual routers handle traffic for one or more virtual services within your mesh. After you create your virtual router, create and associate routes for your virtual router that direct incoming requests to different virtual nodes.

For more information about virtual routers, see [Virtual routers](#).

Request Syntax

```
PUT /v20190125/meshes/meshName/virtualRouters?meshOwner=meshOwner HTTP/1.1
Content-type: application/json
```

```
{
  "clientToken": "string",
  "spec": {
    "listeners": [
      {
        "portMapping": {
          "port": number,
          "protocol": "string"
        }
      }
    ],
    "tags": [
      {
        "key": "string",
        "value": "string"
      }
    ],
    "virtualRouterName": "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

meshName

The name of the service mesh to create the virtual router in.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then the account that you specify must share the mesh with your account before you can create the resource in the service mesh. For more information about mesh sharing, see [Working with shared meshes](#).

Length Constraints: Fixed length of 12.

Request Body

The request accepts the following data in JSON format.

clientToken

Unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Up to 36 letters, numbers, hyphens, and underscores are allowed.

Type: String

Required: No

spec

The virtual router specification to apply.

Type: [VirtualRouterSpec](#) object

Required: Yes

tags

Optional metadata that you can apply to the virtual router to assist with categorization and organization. Each tag consists of a key and an optional value, both of which you define.

Tag keys can have a maximum character length of 128 characters, and tag values can have a maximum length of 256 characters.

Type: Array of [TagRef](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

[virtualRouterName](#)

The name to use for the virtual router.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "meshName": "string",
  "metadata": {
    "arn": "string",
    "createdAt": number,
    "lastUpdatedAt": number,
    "meshOwner": "string",
    "resourceOwner": "string",
    "uid": "string",
    "version": number
  },
  "spec": {
    "listeners": [
      {
        "portMapping": {
          "port": number,
          "protocol": "string"
        }
      }
    ]
  }
}
```

```
    }  
  ]  
},  
"status": {  
  "status": "string"  
},  
"virtualRouterName": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

meshName

The name of the service mesh that the virtual router resides in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

metadata

The associated metadata for the virtual router.

Type: [ResourceMetadata](#) object

spec

The specifications of the virtual router.

Type: [VirtualRouterSpec](#) object

status

The current status of the virtual router.

Type: [VirtualRouterStatus](#) object

virtualRouterName

The name of the virtual router.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ConflictException

The request contains a client token that was used for a previous update resource call with different specifications. Try the request again with a new client token.

HTTP Status Code: 409

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

LimitExceededException

You have exceeded a service limit for your account. For more information, see [Service Limits](#) in the *AWS App Mesh User Guide*.

HTTP Status Code: 400

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You need to learn how to sign HTTP requests only if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

The following example creates a virtual router named `colorteller-vr` in the `ecs-mesh` service mesh.

Sample Request

```
PUT /v20190125/meshes/ecs-mesh/virtualRouters HTTP/1.1
Host: appmesh.us-east-1.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.16.56 Python/3.7.0 Darwin/17.7.0 botocore/1.12.46
X-Amz-Date: 20190227T192446Z
Authorization: AUTHPARAMS

{
  "spec": {
```



```
    listeners: [
      {
        port: 80,
        protocol: http
      }
    ]},
    "virtualRouterName": "colorteller-vr",
    "clientToken": "e90d8ee2-c111-4431-bfa3-4725a06a84b1"
  }
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-requestid: 770a356d-60e5-45f7-9f47-823eb5f1b750
content-type: application/json
content-length: 337
date: Wed, 27 Feb 2019 19:24:46 GMT
x-envoy-upstream-service-time: 19
server: envoy
Connection: keep-alive

{
  "meshName": "ecs-mesh",
  "metadata": {
    "arn": "arn:aws:appmesh:us-east-1:123456789012:mesh/ecs-mesh/virtualRouter/colorteller-vr",
    "createdAt": 1551295486.588,
    "lastUpdatedAt": 1551295486.588,
    "uid": "a756d1e5-ce8f-40a5-afbc-380f61f0c1e0",
    "version": 1
  },
  "spec": {
    "listeners": [
      {
        "portMapping": {
          "port": 9080,
          "protocol": "http"
        }
      }
    ]
  },
  "status": {
    "status": "ACTIVE"
  }
}
```

```
  },  
  "virtualRouterName": "colorteller-vr"  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateVirtualService

Creates a virtual service within a service mesh.

A virtual service is an abstraction of a real service that is provided by a virtual node directly or indirectly by means of a virtual router. Dependent services call your virtual service by its `virtualServiceName`, and those requests are routed to the virtual node or virtual router that is specified as the provider for the virtual service.

For more information about virtual services, see [Virtual services](#).

Request Syntax

```
PUT /v20190125/meshes/meshName/virtualServices?meshOwner=meshOwner HTTP/1.1
Content-type: application/json
```

```
{
  "clientToken": "string",
  "spec": {
    "provider": { ... }
  },
  "tags": [
    {
      "key": "string",
      "value": "string"
    }
  ],
  "virtualServiceName": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

meshName

The name of the service mesh to create the virtual service in.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then the account that you specify must share the mesh with your account before you can create the resource in the service mesh. For more information about mesh sharing, see [Working with shared meshes](#).

Length Constraints: Fixed length of 12.

Request Body

The request accepts the following data in JSON format.

clientToken

Unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Up to 36 letters, numbers, hyphens, and underscores are allowed.

Type: String

Required: No

spec

The virtual service specification to apply.

Type: [VirtualServiceSpec](#) object

Required: Yes

tags

Optional metadata that you can apply to the virtual service to assist with categorization and organization. Each tag consists of a key and an optional value, both of which you define. Tag keys can have a maximum character length of 128 characters, and tag values can have a maximum length of 256 characters.

Type: Array of [TagRef](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

virtualServiceName

The name to use for the virtual service.

Type: String

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "meshName": "string",
  "metadata": {
    "arn": "string",
    "createdAt": number,
    "lastUpdatedAt": number,
    "meshOwner": "string",
    "resourceOwner": "string",
    "uid": "string",
    "version": number
  },
  "spec": {
    "provider": { ... }
  },
  "status": {
    "status": "string"
  },
  "virtualServiceName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

meshName

The name of the service mesh that the virtual service resides in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

metadata

An object that represents metadata for a resource.

Type: [ResourceMetadata](#) object

spec

The specifications of the virtual service.

Type: [VirtualServiceSpec](#) object

status

The current status of the virtual service.

Type: [VirtualServiceStatus](#) object

virtualServiceName

The name of the virtual service.

Type: String

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ConflictException

The request contains a client token that was used for a previous update resource call with different specifications. Try the request again with a new client token.

HTTP Status Code: 409

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

LimitExceededException

You have exceeded a service limit for your account. For more information, see [Service Limits](#) in the *AWS App Mesh User Guide*.

HTTP Status Code: 400

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You need to learn how to sign HTTP requests only if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example creates a virtual service named `colorgateway.default.svc.cluster.local` in the `ecs-mesh` service mesh.

Sample Request

```
PUT /v20190125/meshes/ecs-mesh/virtualServices HTTP/1.1
Host: appmesh.us-east-1.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.16.56 Python/3.7.0 Darwin/17.7.0 botocore/1.12.46
X-Amz-Date: 20190227T192448Z
Authorization: AUTHPARAMS

{
  "spec": {
    "provider": {
      "virtualNode": {
        "virtualNodeName": "colorgateway-vn"
      }
    }
  },
  "virtualServiceName": "colorgateway.default.svc.cluster.local",
  "clientToken": "0a263779-366d-400f-9c4c-0ab7ff0ef392"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-requestid: 6418af7b-e02b-4f0e-bb96-a3b4aab428c8
content-type: application/json
content-length: 456
date: Wed, 27 Feb 2019 19:24:48 GMT
x-envoy-upstream-service-time: 67
server: envoy
Connection: keep-alive

{
  "meshName": "ecs-mesh",
  "metadata": {
    "arn": "arn:aws:appmesh:us-east-1:123456789012:mesh/ecs-mesh/virtualService/colorgateway.default.svc.cluster.local",
    "createdAt": 1.551295488701E9,
```



```
{
  "lastUpdatedAt": 1.551295488701E9,
  "uid": "f1b0ed85-7648-4be2-a0fc-c97865029c48",
  "version": 1
},
"spec": {
  "provider": {
    "virtualNode": {
      "virtualNodeName": "colorgateway-vn"
    },
    "virtualRouter": null
  }
},
"status": {
  "status": "ACTIVE"
},
"virtualServiceName": "colorgateway.default.svc.cluster.local"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteGatewayRoute

Deletes an existing gateway route.

Request Syntax

```
DELETE /v20190125/meshes/meshName/virtualGateway/virtualGatewayName/
gatewayRoutes/gatewayRouteName?meshOwner=meshOwner HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

gatewayRouteName

The name of the gateway route to delete.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshName

The name of the service mesh to delete the gateway route from.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then it's the ID of the account that shared the mesh with your account. For more information about mesh sharing, see [Working with shared meshes](#).

Length Constraints: Fixed length of 12.

virtualGatewayName

The name of the virtual gateway to delete the route from.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "gatewayRouteName": "string",
  "meshName": "string",
  "metadata": {
    "arn": "string",
    "createdAt": number,
    "lastUpdatedAt": number,
    "meshOwner": "string",
    "resourceOwner": "string",
    "uid": "string",
    "version": number
  },
  "spec": {
    "grpcRoute": {
      "action": {
        "rewrite": {
          "hostname": {
            "defaultTargetHostname": "string"
          }
        },
        "target": {
          "port": number,
          "virtualService": {
            "virtualServiceName": "string"
          }
        }
      },
      "match": {
        "hostname": {
          "exact": "string",
          "suffix": "string"
        },
        "metadata": [
          {
```

```

        "invert": boolean,
        "match": { ... },
        "name": "string"
    }
],
    "port": number,
    "serviceName": "string"
}
},
"http2Route": {
    "action": {
        "rewrite": {
            "hostname": {
                "defaultTargetHostname": "string"
            },
            "path": {
                "exact": "string"
            },
            "prefix": {
                "defaultPrefix": "string",
                "value": "string"
            }
        },
        "target": {
            "port": number,
            "virtualService": {
                "virtualServiceName": "string"
            }
        }
    },
    "match": {
        "headers": [
            {
                "invert": boolean,
                "match": { ... },
                "name": "string"
            }
        ],
        "hostname": {
            "exact": "string",
            "suffix": "string"
        },
        "method": "string",
        "path": {

```

```

        "exact": "string",
        "regex": "string"
    },
    "port": number,
    "prefix": "string",
    "queryParameters": [
        {
            "match": {
                "exact": "string"
            },
            "name": "string"
        }
    ]
},
"httpRoute": {
    "action": {
        "rewrite": {
            "hostname": {
                "defaultTargetHostname": "string"
            },
            "path": {
                "exact": "string"
            },
            "prefix": {
                "defaultPrefix": "string",
                "value": "string"
            }
        },
        "target": {
            "port": number,
            "virtualService": {
                "virtualServiceName": "string"
            }
        }
    },
    "match": {
        "headers": [
            {
                "invert": boolean,
                "match": { ... },
                "name": "string"
            }
        ]
    }
},

```

```
    "hostname": {
      "exact": "string",
      "suffix": "string"
    },
    "method": "string",
    "path": {
      "exact": "string",
      "regex": "string"
    },
    "port": number,
    "prefix": "string",
    "queryParameters": [
      {
        "match": {
          "exact": "string"
        },
        "name": "string"
      }
    ]
  },
  "priority": number
},
"status": {
  "status": "string"
},
"virtualGatewayName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

gatewayRouteName

The name of the gateway route.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

meshName

The name of the service mesh that the resource resides in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

metadata

An object that represents metadata for a resource.

Type: [ResourceMetadata](#) object

spec

The specifications of the gateway route.

Type: [GatewayRouteSpec](#) object

status

The status of the gateway route.

Type: [GatewayRouteStatus](#) object

virtualGatewayName

The virtual gateway that the gateway route is associated with.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ResourceInUseException

You can't delete the specified resource because it's in use or required by another resource.

HTTP Status Code: 409

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You need to learn how to sign HTTP requests only if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

The following example deletes a gateway route named `myGatewayRoute` from the `myVirtualGateway` virtual gateway that is in the apps service mesh.

Sample Request

```
DELETE /v20190125/meshes/apps/virtualGateway/myVirtualGateway/gatewayRoutes/
myGatewayRoute HTTP/1.1
Host: appmesh.us-west-2.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.16.298 Python/3.6.0 Windows/10 botocore/1.13.34
X-Amz-Date: 20200608T193419Z
Authorization: AUTHPARAMS
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-requestid: a7e8bcc1-0dec-464d-9e69-5cd1f780c9eb
content-type: application/json
content-length: 618
date: Mon, 08 Jun 2020 19:34:19 GMT
x-envoy-upstream-service-time: 49
server: envoy
Connection: keep-alive

{
  "gatewayRouteName": "myGatewayRoute",
  "meshName": "myApps",
  "metadata": {
    "arn": "arn:aws:appmesh:us-west-2:123456789012:mesh/apps/virtualGateway/
myVirtualGateway/gatewayRoute/myGatewayRoute",
    "createdAt": 1.591642091122E9,
    "lastUpdatedAt": 1.591644859804E9,
    "meshOwner": "123456789012",
    "resourceOwner": "123456789012",
    "uid": "ff111ff2-33ff-4ff4-ffff-111f111f111f",
    "version": 3
  },
  "spec": {
    "grpcRoute": null,
    "http2Route": {
      "action": {
```

```
{
  "target": {
    "virtualService": {
      "virtualServiceName": "myserviceb.svc.cluster.local"
    }
  },
  "match": {
    "prefix": "/"
  },
  "httpRoute": null
},
"status": {
  "status": "DELETED"
},
"virtualGatewayName": "myVirtualGateway"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteMesh

Deletes an existing service mesh.

You must delete all resources (virtual services, routes, virtual routers, and virtual nodes) in the service mesh before you can delete the mesh itself.

Request Syntax

```
DELETE /v20190125/meshes/meshName HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

meshName

The name of the service mesh to delete.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "meshName": "string",
  "metadata": {
    "arn": "string",
    "createdAt": number,
    "lastUpdatedAt": number,
    "meshOwner": "string",
    "resourceOwner": "string",
```

```
  "uid": "string",
  "version": number
},
"spec": {
  "egressFilter": {
    "type": "string"
  },
  "serviceDiscovery": {
    "ipPreference": "string"
  }
},
"status": {
  "status": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

meshName

The name of the service mesh.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

metadata

The associated metadata for the service mesh.

Type: [ResourceMetadata](#) object

spec

The associated specification for the service mesh.

Type: [MeshSpec](#) object

status

The status of the service mesh.

Type: [MeshStatus](#) object

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ResourceInUseException

You can't delete the specified resource because it's in use or required by another resource.

HTTP Status Code: 409

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You need to learn how to sign HTTP requests only if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example command deletes a service mesh named `ecs-mesh` in your default region.

Sample Request

```
DELETE /v20190125/meshes/ecs-mesh HTTP/1.1
Host: appmesh.us-east-1.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.16.56 Python/3.7.0 Darwin/17.7.0 botocore/1.12.46
X-Amz-Date: 20190227T203825Z
Authorization: AUTHPARAMS
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-requestid: 5b4e49f2-dac7-4782-8be3-1e81c8599e14
content-type: application/json
content-length: 246
date: Wed, 27 Feb 2019 20:38:25 GMT
x-envoy-upstream-service-time: 35
server: envoy
Connection: keep-alive

{
  "meshName": "ecs-mesh",
  "metadata": {
    "arn": "arn:aws:appmesh:us-east-1:123456789012:mesh/ecs-mesh",
    "createdAt": 1.551295405298E9,
```

```
"lastUpdatedAt": 1.551299905963E9,  
"uid": "2d29a11c-f2dd-44a6-b620-33661cfdfe97",  
"version": 1  
},  
"status": {  
  "status": "DELETED"  
}  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteRoute

Deletes an existing route.

Request Syntax

```
DELETE /v20190125/meshes/meshName/virtualRouter/virtualRouterName/routes/routeName?  
meshOwner=meshOwner HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

meshName

The name of the service mesh to delete the route in.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then it's the ID of the account that shared the mesh with your account. For more information about mesh sharing, see [Working with shared meshes](#).

Length Constraints: Fixed length of 12.

routeName

The name of the route to delete.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

virtualRouterName

The name of the virtual router to delete the route in.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "meshName": "string",
  "metadata": {
    "arn": "string",
    "createdAt": number,
    "lastUpdatedAt": number,
    "meshOwner": "string",
    "resourceOwner": "string",
    "uid": "string",
    "version": number
  },
  "routeName": "string",
  "spec": {
    "grpcRoute": {
      "action": {
        "weightedTargets": [
          {
            "port": number,
            "virtualNode": "string",
            "weight": number
          }
        ]
      },
      "match": {
        "metadata": [
          {
            "invert": boolean,
            "match": { ... },
            "name": "string"
          }
        ],
        "methodName": "string",
        "port": number,
        "serviceName": "string"
      }
    }
  }
}
```

```

    },
    "retryPolicy": {
      "grpcRetryEvents": [ "string" ],
      "httpRetryEvents": [ "string" ],
      "maxRetries": number,
      "perRetryTimeout": {
        "unit": "string",
        "value": number
      },
    },
    "tcpRetryEvents": [ "string" ]
  },
  "timeout": {
    "idle": {
      "unit": "string",
      "value": number
    },
    "perRequest": {
      "unit": "string",
      "value": number
    }
  }
},
"http2Route": {
  "action": {
    "weightedTargets": [
      {
        "port": number,
        "virtualNode": "string",
        "weight": number
      }
    ]
  },
  "match": {
    "headers": [
      {
        "invert": boolean,
        "match": { ... },
        "name": "string"
      }
    ],
    "method": "string",
    "path": {
      "exact": "string",
      "regex": "string"
    }
  }
}

```

```

    },
    "port": number,
    "prefix": "string",
    "queryParameters": [
      {
        "match": {
          "exact": "string"
        },
        "name": "string"
      }
    ],
    "scheme": "string"
  },
  "retryPolicy": {
    "httpRetryEvents": [ "string" ],
    "maxRetries": number,
    "perRetryTimeout": {
      "unit": "string",
      "value": number
    },
    "tcpRetryEvents": [ "string" ]
  },
  "timeout": {
    "idle": {
      "unit": "string",
      "value": number
    },
    "perRequest": {
      "unit": "string",
      "value": number
    }
  }
},
"httpRoute": {
  "action": {
    "weightedTargets": [
      {
        "port": number,
        "virtualNode": "string",
        "weight": number
      }
    ]
  },
  "match": {

```

```

    "headers": [
      {
        "invert": boolean,
        "match": { ... },
        "name": "string"
      }
    ],
    "method": "string",
    "path": {
      "exact": "string",
      "regex": "string"
    },
    "port": number,
    "prefix": "string",
    "queryParameters": [
      {
        "match": {
          "exact": "string"
        },
        "name": "string"
      }
    ],
    "scheme": "string"
  },
  "retryPolicy": {
    "httpRetryEvents": [ "string" ],
    "maxRetries": number,
    "perRetryTimeout": {
      "unit": "string",
      "value": number
    },
    "tcpRetryEvents": [ "string" ]
  },
  "timeout": {
    "idle": {
      "unit": "string",
      "value": number
    },
    "perRequest": {
      "unit": "string",
      "value": number
    }
  }
},

```

```
"priority": number,
"tcpRoute": {
  "action": {
    "weightedTargets": [
      {
        "port": number,
        "virtualNode": "string",
        "weight": number
      }
    ]
  },
  "match": {
    "port": number
  },
  "timeout": {
    "idle": {
      "unit": "string",
      "value": number
    }
  }
},
"status": {
  "status": "string"
},
"virtualRouterName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

meshName

The name of the service mesh that the route resides in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

metadata

The associated metadata for the route.

Type: [ResourceMetadata](#) object

[routeName](#)

The name of the route.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

[spec](#)

The specifications of the route.

Type: [RouteSpec](#) object

[status](#)

The status of the route.

Type: [RouteStatus](#) object

[virtualRouterName](#)

The virtual router that the route is associated with.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ResourceInUseException

You can't delete the specified resource because it's in use or required by another resource.

HTTP Status Code: 409

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You need to learn how to sign HTTP requests only if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

The following example deletes a route named colorgateway-route for the colorgateway-vr virtual router in the ecs-mesh service mesh.

Sample Request

```
DELETE /v20190125/meshes/ecs-mesh/virtualRouter/colorgateway-vr/routes/colorgateway-
route HTTP/1.1
Host: appmesh.us-east-1.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.16.56 Python/3.7.0 Darwin/17.7.0 botocore/1.12.46
X-Amz-Date: 20190227T203328Z
Authorization: AUTHPARAMS
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-requestid: 59fda333-ead1-4fbd-ba64-b7150e52d29a
content-type: application/json
content-length: 512
date: Wed, 27 Feb 2019 20:33:28 GMT
x-envoy-upstream-service-time: 95
server: envoy
Connection: keep-alive

{
  "meshName": "ecs-mesh",
  "metadata": {
    "arn": "arn:aws:appmesh:us-east-1:123456789012:mesh/ecs-mesh/virtualRouter/
colorgateway-vr/route/colorgateway-route",
    "createdAt": 1.551295495004E9,
    "lastUpdatedAt": 1.551299608556E9,
    "uid": "3251bf37-2d01-4b79-be96-d0c36c61511f",
    "version": 2
  },
  "routeName": "colorgateway-route",
  "spec": {
    "httpRoute": {
      "action": {
        "weightedTargets": [{
          "virtualNode": "colorgateway-vn",
          "weight": 100
        }]
      },
      "match": {
        "prefix": "/"
      }
    }
  }
}
```



```
    },  
    "tcpRoute": null  
  },  
  "status": {  
    "status": "DELETED"  
  },  
  "virtualRouterName": "colorgateway-vr"  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteVirtualGateway

Deletes an existing virtual gateway. You cannot delete a virtual gateway if any gateway routes are associated to it.

Request Syntax

```
DELETE /v20190125/meshes/meshName/virtualGateways/virtualGatewayName?  
meshOwner=meshOwner HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

meshName

The name of the service mesh to delete the virtual gateway from.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then it's the ID of the account that shared the mesh with your account. For more information about mesh sharing, see [Working with shared meshes](#).

Length Constraints: Fixed length of 12.

virtualGatewayName

The name of the virtual gateway to delete.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "meshName": "string",
  "metadata": {
    "arn": "string",
    "createdAt": number,
    "lastUpdatedAt": number,
    "meshOwner": "string",
    "resourceOwner": "string",
    "uid": "string",
    "version": number
  },
  "spec": {
    "backendDefaults": {
      "clientPolicy": {
        "tls": {
          "certificate": { ... },
          "enforce": boolean,
          "ports": [ number ],
          "validation": {
            "subjectAlternativeNames": {
              "match": {
                "exact": [ "string" ]
              }
            },
            "trust": { ... }
          }
        }
      }
    },
    "listeners": [
      {
        "connectionPool": { ... },
        "healthCheck": {
          "healthyThreshold": number,
          "intervalMillis": number,
          "path": "string",
          "port": number,
          "protocol": "string",
```

```

        "timeoutMillis": number,
        "unhealthyThreshold": number
    },
    "portMapping": {
        "port": number,
        "protocol": "string"
    },
    "tls": {
        "certificate": { ... },
        "mode": "string",
        "validation": {
            "subjectAlternativeNames": {
                "match": {
                    "exact": [ "string" ]
                }
            },
            "trust": { ... }
        }
    }
},
"logging": {
    "accessLog": { ... }
},
"status": {
    "status": "string"
},
"virtualGatewayName": "string"
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

meshName

The name of the service mesh that the virtual gateway resides in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

metadata

An object that represents metadata for a resource.

Type: [ResourceMetadata](#) object

spec

The specifications of the virtual gateway.

Type: [VirtualGatewaySpec](#) object

status

The current status of the virtual gateway.

Type: [VirtualGatewayStatus](#) object

virtualGatewayName

The name of the virtual gateway.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ResourceInUseException

You can't delete the specified resource because it's in use or required by another resource.

HTTP Status Code: 409

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You need to learn how to sign HTTP requests only if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

The following example deletes a virtual gateway named myVirtualGateway from the apps service mesh.

Sample Request

```
DELETE /v20190125/meshes/apps/virtualGateways/myVirtualGateway HTTP/1.1
Host: appmesh.us-west-2.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.16.298 Python/3.6.0 Windows/10 botocore/1.13.34
X-Amz-Date: 20200706T150515Z
Authorization: AUTHPARAMS
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-requestid: 884f2830-6964-4d0e-9788-144631c36bb9
content-type: application/json
content-length: 514
date: Mon, 06 Jul 2020 15:05:15 GMT
x-envoy-upstream-service-time: 26
server: envoy
Connection: keep-alive

{
  "meshName": "apps",
  "metadata": {
    "arn": "arn:aws:appmesh:us-west-2:123456789012:mesh/apps/virtualGateway/myVirtualGateway",
    "createdAt": 1.594046778215E9,
    "lastUpdatedAt": 1.594047916142E9,
    "meshOwner": "123456789012",
    "resourceOwner": "123456789012",
    "uid": "ff111ff2-33ff-4ff4-ffff-111f111f111f",
    "version": 2
  },
  "spec": {
    "backendDefaults": null,
    "listeners": [{
      "healthCheck": null,
      "portMapping": {
        "port": 80,
        "protocol": "http2"
      },
      "tls": null
    }],
    "logging": null
  }
}
```

```
  },
  "status": {
    "status": "DELETED"
  },
  "virtualGatewayName": "myVirtualGateway"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteVirtualNode

Deletes an existing virtual node.

You must delete any virtual services that list a virtual node as a service provider before you can delete the virtual node itself.

Request Syntax

```
DELETE /v20190125/meshes/meshName/virtualNodes/virtualNodeName?meshOwner=meshOwner  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

meshName

The name of the service mesh to delete the virtual node in.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then it's the ID of the account that shared the mesh with your account. For more information about mesh sharing, see [Working with shared meshes](#).

Length Constraints: Fixed length of 12.

virtualNodeName

The name of the virtual node to delete.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "meshName": "string",
  "metadata": {
    "arn": "string",
    "createdAt": number,
    "lastUpdatedAt": number,
    "meshOwner": "string",
    "resourceOwner": "string",
    "uid": "string",
    "version": number
  },
  "spec": {
    "backendDefaults": {
      "clientPolicy": {
        "tls": {
          "certificate": { ... },
          "enforce": boolean,
          "ports": [ number ],
          "validation": {
            "subjectAlternativeNames": {
              "match": {
                "exact": [ "string" ]
              }
            }
          },
          "trust": { ... }
        }
      }
    },
    "backends": [
      { ... }
    ],
    "listeners": [
      {
        "connectionPool": { ... },
        "healthCheck": {
          "healthyThreshold": number,
          "intervalMillis": number,
```

```

        "path": "string",
        "port": number,
        "protocol": "string",
        "timeoutMillis": number,
        "unhealthyThreshold": number
    },
    "outlierDetection": {
        "baseEjectionDuration": {
            "unit": "string",
            "value": number
        },
        "interval": {
            "unit": "string",
            "value": number
        },
        "maxEjectionPercent": number,
        "maxServerErrors": number
    },
    "portMapping": {
        "port": number,
        "protocol": "string"
    },
    "timeout": { ... },
    "tls": {
        "certificate": { ... },
        "mode": "string",
        "validation": {
            "subjectAlternativeNames": {
                "match": {
                    "exact": [ "string" ]
                }
            },
            "trust": { ... }
        }
    }
},
],
"logging": {
    "accessLog": { ... }
},
"serviceDiscovery": { ... }
},
"status": {
    "status": "string"

```

```
  },  
  "virtualNodeName": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[meshName](#)

The name of the service mesh that the virtual node resides in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

[metadata](#)

The associated metadata for the virtual node.

Type: [ResourceMetadata](#) object

[spec](#)

The specifications of the virtual node.

Type: [VirtualNodeSpec](#) object

[status](#)

The current status for the virtual node.

Type: [VirtualNodeStatus](#) object

[virtualNodeName](#)

The name of the virtual node.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ResourceInUseException

You can't delete the specified resource because it's in use or required by another resource.

HTTP Status Code: 409

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You need to learn how to sign HTTP requests only if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example deletes a virtual node named `colorgateway-vn` in the `ecs-mesh` service mesh.

Sample Request

```
DELETE /v20190125/meshes/ecs-mesh/virtualNodes/colorgateway-vn HTTP/1.1
Host: appmesh.us-east-1.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.16.56 Python/3.7.0 Darwin/17.7.0 botocore/1.12.46
X-Amz-Date: 20190227T231337Z
Authorization: AUTHPARAMS
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-requestid: 84875cd2-d36c-445a-b1a7-6a26ec798e62
content-type: application/json
content-length: 688
date: Wed, 27 Feb 2019 23:13:37 GMT
x-envoy-upstream-service-time: 25
server: envoy
Connection: keep-alive

{
  "meshName": "ecs-mesh",
  "metadata": {
    "arn": "arn:aws:appmesh:us-east-1:123456789012:mesh/ecs-mesh/virtualNode/colorgateway-vn",
    "createdAt": 1.551307227168E9,
```

```
"lastUpdatedAt": 1.551309217745E9,
"uid": "4cd6303b-491e-4c2b-9108-1a4690ec9f36",
"version": 2
},
"spec": {
  "backends": [{
    "virtualService": {
      "virtualServiceName": "tcpecho.default.svc.cluster.local"
    }
  }, {
    "virtualService": {
      "virtualServiceName": "colorteller.default.svc.cluster.local"
    }
  }],
  "listeners": [{
    "healthCheck": null,
    "portMapping": {
      "port": 9080,
      "protocol": "http"
    }
  }],
  "logging": null,
  "serviceDiscovery": {
    "dns": {
      "hostname": "colorgateway.default.svc.cluster.local"
    }
  }
},
"status": {
  "status": "DELETED"
},
"virtualNodeName": "colorgateway-vn"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteVirtualRouter

Deletes an existing virtual router.

You must delete any routes associated with the virtual router before you can delete the router itself.

Request Syntax

```
DELETE /v20190125/meshes/meshName/virtualRouters/virtualRouterName?meshOwner=meshOwner  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

meshName

The name of the service mesh to delete the virtual router in.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then it's the ID of the account that shared the mesh with your account. For more information about mesh sharing, see [Working with shared meshes](#).

Length Constraints: Fixed length of 12.

virtualRouterName

The name of the virtual router to delete.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "meshName": "string",
  "metadata": {
    "arn": "string",
    "createdAt": number,
    "lastUpdatedAt": number,
    "meshOwner": "string",
    "resourceOwner": "string",
    "uid": "string",
    "version": number
  },
  "spec": {
    "listeners": [
      {
        "portMapping": {
          "port": number,
          "protocol": "string"
        }
      }
    ]
  },
  "status": {
    "status": "string"
  },
  "virtualRouterName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

meshName

The name of the service mesh that the virtual router resides in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

metadata

The associated metadata for the virtual router.

Type: [ResourceMetadata](#) object

spec

The specifications of the virtual router.

Type: [VirtualRouterSpec](#) object

status

The current status of the virtual router.

Type: [VirtualRouterStatus](#) object

virtualRouterName

The name of the virtual router.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ResourceInUseException

You can't delete the specified resource because it's in use or required by another resource.

HTTP Status Code: 409

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You need to learn how to sign HTTP requests only if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example deletes a virtual router named `colorgateway-vr` in the `ecs-mesh` service mesh.

Sample Request

```
DELETE /v20190125/meshes/ecs-mesh/virtualRouters/colorgateway-vr HTTP/1.1
Host: appmesh.us-east-1.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.16.56 Python/3.7.0 Darwin/17.7.0 botocore/1.12.46
X-Amz-Date: 20190227T231334Z
Authorization: AUTHPARAMS
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-requestid: 77a5e726-69b4-4bd4-9016-99f76f4d1daa
content-type: application/json
content-length: 340
date: Wed, 27 Feb 2019 23:13:34 GMT
x-envoy-upstream-service-time: 23
server: envoy
Connection: keep-alive

{
  "meshName": "ecs-mesh",
  "metadata": {
    "arn": "arn:aws:appmesh:us-east-1:123456789012:mesh/ecs-mesh/virtualRouter/colorgateway-vr",
    "createdAt": 1551307245.617,
    "lastUpdatedAt": 1551309214.686,
    "uid": "601f33c5-8938-4c07-a28a-3d3c91871ee4",
    "version": 2
  },
  "spec": {
    "listeners": [
      {
        "portMapping": {
          "port": 9080,
          "protocol": "http"
        }
      }
    ]
  },
  "status": {
    "status": "DELETED"
  },
}
```

```
"virtualRouterName": "colorgateway-vr"  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteVirtualService

Deletes an existing virtual service.

Request Syntax

```
DELETE /v20190125/meshes/meshName/virtualServices/virtualServiceName?  
meshOwner=meshOwner HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

meshName

The name of the service mesh to delete the virtual service in.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then it's the ID of the account that shared the mesh with your account. For more information about mesh sharing, see [Working with shared meshes](#).

Length Constraints: Fixed length of 12.

virtualServiceName

The name of the virtual service to delete.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Content-type: application/json

```
{
  "meshName": "string",
  "metadata": {
    "arn": "string",
    "createdAt": number,
    "lastUpdatedAt": number,
    "meshOwner": "string",
    "resourceOwner": "string",
    "uid": "string",
    "version": number
  },
  "spec": {
    "provider": { ... }
  },
  "status": {
    "status": "string"
  },
  "virtualServiceName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

meshName

The name of the service mesh that the virtual service resides in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

metadata

An object that represents metadata for a resource.

Type: [ResourceMetadata](#) object

spec

The specifications of the virtual service.

Type: [VirtualServiceSpec](#) object

[status](#)

The current status of the virtual service.

Type: [VirtualServiceStatus](#) object

[virtualServiceName](#)

The name of the virtual service.

Type: String

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ResourceInUseException

You can't delete the specified resource because it's in use or required by another resource.

HTTP Status Code: 409

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You need to learn how to sign HTTP requests only if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example deletes a virtual service named `colorgateway.default.svc.cluster.local` in the `ecs-mesh` service mesh.

Sample Request

```
DELETE /v20190125/meshes/ecs-mesh/virtualServices/
colorgateway.default.svc.cluster.local HTTP/1.1
Host: appmesh.us-east-1.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.16.56 Python/3.7.0 Darwin/17.7.0 botocore/1.12.46
X-Amz-Date: 20190227T231318Z
Authorization: AUTHPARAMS
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-requestid: 8a5c10db-aebc-4341-8b15-4003e87150e8
content-type: application/json
```

```
content-length: 456
date: Wed, 27 Feb 2019 23:13:18 GMT
x-envoy-upstream-service-time: 78
server: envoy
Connection: keep-alive

{
  "meshName": "ecs-mesh",
  "metadata": {
    "arn": "arn:aws:appmesh:us-east-1:123456789012:mesh/ecs-mesh/virtualService/
colorgateway.default.svc.cluster.local",
    "createdAt": 1.551307250696E9,
    "lastUpdatedAt": 1.55130919872E9,
    "uid": "90849766-3af0-40bc-9a83-a7b932d64fb6",
    "version": 2
  },
  "spec": {
    "provider": {
      "virtualNode": {
        "virtualNodeName": "colorgateway-vn"
      },
      "virtualRouter": null
    }
  },
  "status": {
    "status": "DELETED"
  },
  "virtualServiceName": "colorgateway.default.svc.cluster.local"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeGatewayRoute

Describes an existing gateway route.

Request Syntax

```
GET /v20190125/meshes/meshName/virtualGateway/virtualGatewayName/
gatewayRoutes/gatewayRouteName?meshOwner=meshOwner HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

gatewayRouteName

The name of the gateway route to describe.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshName

The name of the service mesh that the gateway route resides in.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then it's the ID of the account that shared the mesh with your account. For more information about mesh sharing, see [Working with shared meshes](#).

Length Constraints: Fixed length of 12.

virtualGatewayName

The name of the virtual gateway that the gateway route is associated with.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "gatewayRouteName": "string",
  "meshName": "string",
  "metadata": {
    "arn": "string",
    "createdAt": number,
    "lastUpdatedAt": number,
    "meshOwner": "string",
    "resourceOwner": "string",
    "uid": "string",
    "version": number
  },
  "spec": {
    "grpcRoute": {
      "action": {
        "rewrite": {
          "hostname": {
            "defaultTargetHostname": "string"
          }
        },
      },
      "target": {
        "port": number,
        "virtualService": {
          "virtualServiceName": "string"
        }
      }
    },
    "match": {
      "hostname": {
        "exact": "string",
        "suffix": "string"
      },
      "metadata": [
        {
```

```

        "invert": boolean,
        "match": { ... },
        "name": "string"
    }
],
    "port": number,
    "serviceName": "string"
}
},
"http2Route": {
    "action": {
        "rewrite": {
            "hostname": {
                "defaultTargetHostname": "string"
            },
            "path": {
                "exact": "string"
            },
            "prefix": {
                "defaultPrefix": "string",
                "value": "string"
            }
        },
        "target": {
            "port": number,
            "virtualService": {
                "virtualServiceName": "string"
            }
        }
    },
    "match": {
        "headers": [
            {
                "invert": boolean,
                "match": { ... },
                "name": "string"
            }
        ],
        "hostname": {
            "exact": "string",
            "suffix": "string"
        },
        "method": "string",
        "path": {

```

```

        "exact": "string",
        "regex": "string"
    },
    "port": number,
    "prefix": "string",
    "queryParameters": [
        {
            "match": {
                "exact": "string"
            },
            "name": "string"
        }
    ]
},
"httpRoute": {
    "action": {
        "rewrite": {
            "hostname": {
                "defaultTargetHostname": "string"
            },
            "path": {
                "exact": "string"
            },
            "prefix": {
                "defaultPrefix": "string",
                "value": "string"
            }
        },
        "target": {
            "port": number,
            "virtualService": {
                "virtualServiceName": "string"
            }
        }
    },
    "match": {
        "headers": [
            {
                "invert": boolean,
                "match": { ... },
                "name": "string"
            }
        ]
    }
}

```



```
    "hostname": {
      "exact": "string",
      "suffix": "string"
    },
    "method": "string",
    "path": {
      "exact": "string",
      "regex": "string"
    },
    "port": number,
    "prefix": "string",
    "queryParameters": [
      {
        "match": {
          "exact": "string"
        },
        "name": "string"
      }
    ]
  },
  "priority": number
},
"status": {
  "status": "string"
},
"virtualGatewayName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

gatewayRouteName

The name of the gateway route.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

meshName

The name of the service mesh that the resource resides in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

metadata

An object that represents metadata for a resource.

Type: [ResourceMetadata](#) object

spec

The specifications of the gateway route.

Type: [GatewayRouteSpec](#) object

status

The status of the gateway route.

Type: [GatewayRouteStatus](#) object

virtualGatewayName

The virtual gateway that the gateway route is associated with.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You need to learn how to sign HTTP requests only if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

The following example describes a gateway route named `myGatewayRoute` that is associated with a virtual gateway named `myVirtualGateway` in the apps service mesh.

Sample Request

```
GET /v20190125/meshes/apps/virtualGateway/myVirtualGateway/gatewayRoutes/myGatewayRoute
HTTP/1.1
Host: appmesh.us-west-2.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.16.298 Python/3.6.0 Windows/10 botocore/1.13.34
X-Amz-Date: 20200608T194902Z
Authorization: AUTHPARAMS
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-requestid: 6d60d9e4-294d-40ca-a829-37f9ebc058e8
content-type: application/json
content-length: 617
date: Mon, 08 Jun 2020 20:26:03 GMT
x-envoy-upstream-service-time: 31
server: envoy
Connection: keep-alive

{
  "gatewayRouteName": "myGatewayRoute",
  "meshName": "myApps",
  "metadata": {
    "arn": "arn:aws:appmesh:us-west-2:123456789012:mesh/apps/virtualGateway/
myVirtualGateway/gatewayRoute/myGatewayRoute",
    "createdAt": 1.591645848403E9,
    "lastUpdatedAt": 1.591645848403E9,
    "meshOwner": "123456789012",
    "resourceOwner": "123456789012",
    "uid": "ff111ff2-33ff-4ff4-ffff-111f111f111f",
    "version": 1
  },
  "spec": {
    "grpcRoute": null,
    "http2Route": {
      "action": {
        "target": {
          "virtualService": {
            "virtualServiceName": "myservicea.svc.cluster.local"
          }
        }
      }
    }
  }
}
```

```
    },  
    "match": {  
      "prefix": "/"  
    },  
  },  
  "httpRoute": null  
},  
"status": {  
  "status": "ACTIVE"  
},  
"virtualGatewayName": "myVirtualGateway"  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeMesh

Describes an existing service mesh.

Request Syntax

```
GET /v20190125/meshes/meshName?meshOwner=meshOwner HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

meshName

The name of the service mesh to describe.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then it's the ID of the account that shared the mesh with your account. For more information about mesh sharing, see [Working with shared meshes](#).

Length Constraints: Fixed length of 12.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "meshName": "string",
  "metadata": {
```

```
    "arn": "string",
    "createdAt": number,
    "lastUpdatedAt": number,
    "meshOwner": "string",
    "resourceOwner": "string",
    "uid": "string",
    "version": number
  },
  "spec": {
    "egressFilter": {
      "type": "string"
    },
    "serviceDiscovery": {
      "ipPreference": "string"
    }
  },
  "status": {
    "status": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

meshName

The name of the service mesh.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

metadata

The associated metadata for the service mesh.

Type: [ResourceMetadata](#) object

spec

The associated specification for the service mesh.

Type: [MeshSpec](#) object

[status](#)

The status of the service mesh.

Type: [MeshStatus](#) object

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You need to learn how to sign HTTP requests only if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example describes a service mesh named `ecs-mesh`.

Sample Request

```
GET /v20190125/meshes HTTP/1.1
Host: appmesh.us-east-1.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.16.56 Python/3.7.0 Darwin/17.7.0 botocore/1.12.46
X-Amz-Date: 20190227T235715Z
Authorization: AUTHPARAMS
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-requestid: 572dcc56-18d6-4f86-b596-8e182f81afce
content-type: application/json
content-length: 114
date: Wed, 27 Feb 2019 23:57:15 GMT
x-envoy-upstream-service-time: 67
server: envoy
Connection: keep-alive

{
  "meshes": [{
    "arn": "arn:aws:appmesh:us-east-1:123456789012:mesh/ecs-mesh",
    "meshName": "ecs-mesh"
  }],
```

```
"nextToken": null
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeRoute

Describes an existing route.

Request Syntax

```
GET /v20190125/meshes/meshName/virtualRouter/virtualRouterName/routes/routeName?  
meshOwner=meshOwner HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

meshName

The name of the service mesh that the route resides in.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then it's the ID of the account that shared the mesh with your account. For more information about mesh sharing, see [Working with shared meshes](#).

Length Constraints: Fixed length of 12.

routeName

The name of the route to describe.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

virtualRouterName

The name of the virtual router that the route is associated with.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "meshName": "string",
  "metadata": {
    "arn": "string",
    "createdAt": number,
    "lastUpdatedAt": number,
    "meshOwner": "string",
    "resourceOwner": "string",
    "uid": "string",
    "version": number
  },
  "routeName": "string",
  "spec": {
    "grpcRoute": {
      "action": {
        "weightedTargets": [
          {
            "port": number,
            "virtualNode": "string",
            "weight": number
          }
        ]
      },
      "match": {
        "metadata": [
          {
            "invert": boolean,
            "match": { ... },
            "name": "string"
          }
        ],
        "methodName": "string",
        "port": number,
        "serviceName": "string"
      }
    }
  }
}
```

```

    },
    "retryPolicy": {
      "grpcRetryEvents": [ "string" ],
      "httpRetryEvents": [ "string" ],
      "maxRetries": number,
      "perRetryTimeout": {
        "unit": "string",
        "value": number
      },
    },
    "tcpRetryEvents": [ "string" ]
  },
  "timeout": {
    "idle": {
      "unit": "string",
      "value": number
    },
    "perRequest": {
      "unit": "string",
      "value": number
    }
  }
},
"http2Route": {
  "action": {
    "weightedTargets": [
      {
        "port": number,
        "virtualNode": "string",
        "weight": number
      }
    ]
  },
  "match": {
    "headers": [
      {
        "invert": boolean,
        "match": { ... },
        "name": "string"
      }
    ],
    "method": "string",
    "path": {
      "exact": "string",
      "regex": "string"
    }
  }
}

```

```

    },
    "port": number,
    "prefix": "string",
    "queryParameters": [
      {
        "match": {
          "exact": "string"
        },
        "name": "string"
      }
    ],
    "scheme": "string"
  },
  "retryPolicy": {
    "httpRetryEvents": [ "string" ],
    "maxRetries": number,
    "perRetryTimeout": {
      "unit": "string",
      "value": number
    },
    "tcpRetryEvents": [ "string" ]
  },
  "timeout": {
    "idle": {
      "unit": "string",
      "value": number
    },
    "perRequest": {
      "unit": "string",
      "value": number
    }
  }
},
"httpRoute": {
  "action": {
    "weightedTargets": [
      {
        "port": number,
        "virtualNode": "string",
        "weight": number
      }
    ]
  },
  "match": {

```

```

    "headers": [
      {
        "invert": boolean,
        "match": { ... },
        "name": "string"
      }
    ],
    "method": "string",
    "path": {
      "exact": "string",
      "regex": "string"
    },
    "port": number,
    "prefix": "string",
    "queryParameters": [
      {
        "match": {
          "exact": "string"
        },
        "name": "string"
      }
    ],
    "scheme": "string"
  },
  "retryPolicy": {
    "httpRetryEvents": [ "string" ],
    "maxRetries": number,
    "perRetryTimeout": {
      "unit": "string",
      "value": number
    },
    "tcpRetryEvents": [ "string" ]
  },
  "timeout": {
    "idle": {
      "unit": "string",
      "value": number
    },
    "perRequest": {
      "unit": "string",
      "value": number
    }
  }
},

```

```
"priority": number,
"tcpRoute": {
  "action": {
    "weightedTargets": [
      {
        "port": number,
        "virtualNode": "string",
        "weight": number
      }
    ]
  },
  "match": {
    "port": number
  },
  "timeout": {
    "idle": {
      "unit": "string",
      "value": number
    }
  }
},
"status": {
  "status": "string"
},
"virtualRouterName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

meshName

The name of the service mesh that the route resides in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

metadata

The associated metadata for the route.

Type: [ResourceMetadata](#) object

[routeName](#)

The name of the route.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

[spec](#)

The specifications of the route.

Type: [RouteSpec](#) object

[status](#)

The status of the route.

Type: [RouteStatus](#) object

[virtualRouterName](#)

The virtual router that the route is associated with.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You need to learn how to sign HTTP requests only if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example describes a route named `colorteller-route` for the `colorteller-v1` virtual router in the `ecs-mesh` service mesh.

Sample Request

```
GET /v20190125/meshes/ecs-mesh/virtualRouter/colorteller-vr/routes/colorteller-route
HTTP/1.1
Host: appmesh.us-east-1.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.16.56 Python/3.7.0 Darwin/17.7.0 botocore/1.12.46
X-Amz-Date: 20190228T000038Z
Authorization: AUTHPARAMS
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-requestid: f28c32fe-2d36-4fcf-a64e-01b45a4b034c
content-type: application/json
content-length: 504
date: Thu, 28 Feb 2019 00:00:38 GMT
x-envoy-upstream-service-time: 46
server: envoy
Connection: keep-alive

{
  "meshName": "ecs-mesh",
  "metadata": {
    "arn": "arn:aws:appmesh:us-east-1:123456789012:mesh/ecs-mesh/virtualRouter/colorteller-vr/route/colorteller-route",
    "createdAt": 1.551311817276E9,
    "lastUpdatedAt": 1.551311817276E9,
    "uid": "1cf3109a-0d7f-438c-b17d-a3785f14ff7b",
    "version": 1
  },
  "routeName": "colorteller-route",
  "spec": {
    "httpRoute": {
      "action": {
        "weightedTargets": [{
          "virtualNode": "colorteller-vn",
          "weight": 1
        }]
      },
      "match": {
        "prefix": "/"
      }
    }
  }
}
```

```
    },  
    "tcpRoute": null  
  },  
  "status": {  
    "status": "ACTIVE"  
  },  
  "virtualRouterName": "colorteller-vr"  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeVirtualGateway

Describes an existing virtual gateway.

Request Syntax

```
GET /v20190125/meshes/meshName/virtualGateways/virtualGatewayName?meshOwner=meshOwner
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

meshName

The name of the service mesh that the gateway route resides in.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then it's the ID of the account that shared the mesh with your account. For more information about mesh sharing, see [Working with shared meshes](#).

Length Constraints: Fixed length of 12.

virtualGatewayName

The name of the virtual gateway to describe.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "meshName": "string",
  "metadata": {
    "arn": "string",
    "createdAt": number,
    "lastUpdatedAt": number,
    "meshOwner": "string",
    "resourceOwner": "string",
    "uid": "string",
    "version": number
  },
  "spec": {
    "backendDefaults": {
      "clientPolicy": {
        "tls": {
          "certificate": { ... },
          "enforce": boolean,
          "ports": [ number ],
          "validation": {
            "subjectAlternativeNames": {
              "match": {
                "exact": [ "string" ]
              }
            },
            "trust": { ... }
          }
        }
      }
    },
    "listeners": [
      {
        "connectionPool": { ... },
        "healthCheck": {
          "healthyThreshold": number,
          "intervalMillis": number,
          "path": "string",
          "port": number,
          "protocol": "string",
```

```

        "timeoutMillis": number,
        "unhealthyThreshold": number
    },
    "portMapping": {
        "port": number,
        "protocol": "string"
    },
    "tls": {
        "certificate": { ... },
        "mode": "string",
        "validation": {
            "subjectAlternativeNames": {
                "match": {
                    "exact": [ "string" ]
                }
            },
            "trust": { ... }
        }
    }
},
"logging": {
    "accessLog": { ... }
},
"status": {
    "status": "string"
},
"virtualGatewayName": "string"
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

meshName

The name of the service mesh that the virtual gateway resides in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

metadata

An object that represents metadata for a resource.

Type: [ResourceMetadata](#) object

spec

The specifications of the virtual gateway.

Type: [VirtualGatewaySpec](#) object

status

The current status of the virtual gateway.

Type: [VirtualGatewayStatus](#) object

virtualGatewayName

The name of the virtual gateway.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You need to learn how to sign HTTP requests only if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

The following example describes a virtual gateway named myVirtualGateway that is in the apps service mesh.

Sample Request

```
GET /v20190125/meshes/apps/virtualGateways/myVirtualGateway HTTP/1.1
Host: appmesh.us-west-2.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.16.298 Python/3.6.0 Windows/10 botocore/1.13.34
```

X-Amz-Date: 20200706T145910Z

Authorization: AUTHPARAMS

Sample Response

HTTP/1.1 200 OK

x-amzn-requestid: 52e5ee7c-7434-4ca0-885e-5c9d8a7bbaf8

content-type: application/json

content-length: 513

date: Mon, 06 Jul 2020 14:59:10 GMT

x-envoy-upstream-service-time: 19

server: envoy

Connection: keep-alive

```
{
  "meshName": "apps",
  "metadata": {
    "arn": "arn:aws:appmesh:us-west-2:123456789012:mesh/apps/virtualGateway/myVirtualGateway",
    "createdAt": 1.594046778215E9,
    "lastUpdatedAt": 1.594046778215E9,
    "meshOwner": "123456789012",
    "resourceOwner": "123456789012",
    "uid": "ff111ff2-33ff-4ff4-ffff-111f111f111f",
    "version": 1
  },
  "spec": {
    "backendDefaults": null,
    "listeners": [{
      "healthCheck": null,
      "portMapping": {
        "port": 80,
        "protocol": "http2"
      },
      "tls": null
    }],
    "logging": null
  },
  "status": {
    "status": "ACTIVE"
  },
  "virtualGatewayName": "myVirtualGateway"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeVirtualNode

Describes an existing virtual node.

Request Syntax

```
GET /v20190125/meshes/meshName/virtualNodes/virtualNodeName?meshOwner=meshOwner
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

meshName

The name of the service mesh that the virtual node resides in.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then it's the ID of the account that shared the mesh with your account. For more information about mesh sharing, see [Working with shared meshes](#).

Length Constraints: Fixed length of 12.

virtualNodeName

The name of the virtual node to describe.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "meshName": "string",
  "metadata": {
    "arn": "string",
    "createdAt": number,
    "lastUpdatedAt": number,
    "meshOwner": "string",
    "resourceOwner": "string",
    "uid": "string",
    "version": number
  },
  "spec": {
    "backendDefaults": {
      "clientPolicy": {
        "tls": {
          "certificate": { ... },
          "enforce": boolean,
          "ports": [ number ],
          "validation": {
            "subjectAlternativeNames": {
              "match": {
                "exact": [ "string" ]
              }
            },
            "trust": { ... }
          }
        }
      }
    },
    "backends": [
      { ... }
    ],
    "listeners": [
      {
        "connectionPool": { ... },
        "healthCheck": {
          "healthyThreshold": number,
          "intervalMillis": number,
```

```

        "path": "string",
        "port": number,
        "protocol": "string",
        "timeoutMillis": number,
        "unhealthyThreshold": number
    },
    "outlierDetection": {
        "baseEjectionDuration": {
            "unit": "string",
            "value": number
        },
        "interval": {
            "unit": "string",
            "value": number
        },
        "maxEjectionPercent": number,
        "maxServerErrors": number
    },
    "portMapping": {
        "port": number,
        "protocol": "string"
    },
    "timeout": { ... },
    "tls": {
        "certificate": { ... },
        "mode": "string",
        "validation": {
            "subjectAlternativeNames": {
                "match": {
                    "exact": [ "string" ]
                }
            },
            "trust": { ... }
        }
    }
}
],
"logging": {
    "accessLog": { ... }
},
"serviceDiscovery": { ... }
},
"status": {
    "status": "string"

```

```
  },  
  "virtualNodeName": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[meshName](#)

The name of the service mesh that the virtual node resides in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

[metadata](#)

The associated metadata for the virtual node.

Type: [ResourceMetadata](#) object

[spec](#)

The specifications of the virtual node.

Type: [VirtualNodeSpec](#) object

[status](#)

The current status for the virtual node.

Type: [VirtualNodeStatus](#) object

[virtualNodeName](#)

The name of the virtual node.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You need to learn how to sign HTTP requests only if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example describes a virtual node named `colorteller-vn` in the `ecs-mesh` service mesh.

Sample Request

```
GET /v20190125/meshes/ecs-mesh/virtualNodes/colorteller-vn HTTP/1.1
Host: appmesh.us-east-1.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.16.56 Python/3.7.0 Darwin/17.7.0 botocore/1.12.46
X-Amz-Date: 20190228T000300Z
Authorization: AUTHPARAMS
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-requestid: 083f9376-9799-4142-978b-42f5966192b8
content-type: application/json
content-length: 654
date: Thu, 28 Feb 2019 00:03:00 GMT
x-envoy-upstream-service-time: 60
server: envoy
Connection: keep-alive

{
  "meshName": "ecs-mesh",
  "metadata": {
    "arn": "arn:aws:appmesh:us-east-1:123456789012:mesh/ecs-mesh/virtualNode/colorteller-vn",
    "createdAt": 1.551311799179E9,
    "lastUpdatedAt": 1.551311799179E9,
    "uid": "0999e53a-8e0e-4c4c-8764-ae8ebecc296d",
    "version": 1
  },
  "spec": {
    "backends": [],
```

```
"listeners": [{
  "healthCheck": {
    "healthyThreshold": 2,
    "intervalMillis": 5000,
    "path": "/ping",
    "port": 9080,
    "protocol": "http",
    "timeoutMillis": 2000,
    "unhealthyThreshold": 2
  },
  "portMapping": {
    "port": 9080,
    "protocol": "http"
  }
}],
"logging": null,
"serviceDiscovery": {
  "dns": {
    "hostname": "colorteller.default.svc.cluster.local"
  }
},
"status": {
  "status": "ACTIVE"
},
"virtualNodeName": "colorteller-vn"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeVirtualRouter

Describes an existing virtual router.

Request Syntax

```
GET /v20190125/meshes/meshName/virtualRouters/virtualRouterName?meshOwner=meshOwner
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

meshName

The name of the service mesh that the virtual router resides in.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then it's the ID of the account that shared the mesh with your account. For more information about mesh sharing, see [Working with shared meshes](#).

Length Constraints: Fixed length of 12.

virtualRouterName

The name of the virtual router to describe.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "meshName": "string",
  "metadata": {
    "arn": "string",
    "createdAt": number,
    "lastUpdatedAt": number,
    "meshOwner": "string",
    "resourceOwner": "string",
    "uid": "string",
    "version": number
  },
  "spec": {
    "listeners": [
      {
        "portMapping": {
          "port": number,
          "protocol": "string"
        }
      }
    ]
  },
  "status": {
    "status": "string"
  },
  "virtualRouterName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

meshName

The name of the service mesh that the virtual router resides in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

metadata

The associated metadata for the virtual router.

Type: [ResourceMetadata](#) object

spec

The specifications of the virtual router.

Type: [VirtualRouterSpec](#) object

status

The current status of the virtual router.

Type: [VirtualRouterStatus](#) object

virtualRouterName

The name of the virtual router.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You need to learn how to sign HTTP requests only if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example describes a virtual router named `colorteller-vr` in the `ecs-mesh` service mesh.

Sample Request

```
GET /v20190125/meshes/ecs-mesh/virtualRouters/colorteller-vr HTTP/1.1
Host: appmesh.us-east-1.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.16.56 Python/3.7.0 Darwin/17.7.0 botocore/1.12.46
X-Amz-Date: 20190228T000509Z
Authorization: AUTHPARAMS
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-requestid: e7e0fbe8-2015-429c-bbb5-c736c09b2500
content-type: application/json
content-length: 337
date: Thu, 28 Feb 2019 00:05:10 GMT
x-envoy-upstream-service-time: 68
server: envoy
Connection: keep-alive

{
  "meshName": "ecs-mesh",
  "metadata": {
    "arn": "arn:aws:appmesh:us-east-1:123456789012:mesh/ecs-mesh/virtualRouter/colorteller-vr",
    "createdAt": 1551311805.476,
    "lastUpdatedAt": 1551311805.476,
    "uid": "79628d34-8c17-42ba-83a5-8a42fd17ec5a",
    "version": 1
  },
  "spec": {
    "listeners": [
      {
        "portMapping": {
          "port": 9080,
          "protocol": "http"
        }
      }
    ]
  },
  "status": {
    "status": "ACTIVE"
  },
  "virtualRouterName": "colorteller-vr"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeVirtualService

Describes an existing virtual service.

Request Syntax

```
GET /v20190125/meshes/meshName/virtualServices/virtualServiceName?meshOwner=meshOwner
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

meshName

The name of the service mesh that the virtual service resides in.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then it's the ID of the account that shared the mesh with your account. For more information about mesh sharing, see [Working with shared meshes](#).

Length Constraints: Fixed length of 12.

virtualServiceName

The name of the virtual service to describe.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Content-type: application/json

```
{
  "meshName": "string",
  "metadata": {
    "arn": "string",
    "createdAt": number,
    "lastUpdatedAt": number,
    "meshOwner": "string",
    "resourceOwner": "string",
    "uid": "string",
    "version": number
  },
  "spec": {
    "provider": { ... }
  },
  "status": {
    "status": "string"
  },
  "virtualServiceName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

meshName

The name of the service mesh that the virtual service resides in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

metadata

An object that represents metadata for a resource.

Type: [ResourceMetadata](#) object

spec

The specifications of the virtual service.

Type: [VirtualServiceSpec](#) object

status

The current status of the virtual service.

Type: [VirtualServiceStatus](#) object

virtualServiceName

The name of the virtual service.

Type: String

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You need to learn how to sign HTTP requests only if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example describes a virtual service named `colorgateway.default.svc.cluster.local` in the `ecs-mesh` service mesh.

Sample Request

```
GET /v20190125/meshes/ecs-mesh/virtualServices/colorgateway.default.svc.cluster.local
HTTP/1.1
Host: appmesh.us-east-1.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.16.56 Python/3.7.0 Darwin/17.7.0 botocore/1.12.46
X-Amz-Date: 20190228T000705Z
Authorization: AUTHPARAMS
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-requestid: 3b822acc-bd78-4ea6-9831-8cd989dd37ec
content-type: application/json
content-length: 456
date: Thu, 28 Feb 2019 00:07:04 GMT
```

```
x-envoy-upstream-service-time: 30
server: envoy
Connection: keep-alive

{
  "meshName": "ecs-mesh",
  "metadata": {
    "arn": "arn:aws:appmesh:us-east-1:123456789012:mesh/ecs-mesh/virtualService/colorgateway.default.svc.cluster.local",
    "createdAt": 1.551311807444E9,
    "lastUpdatedAt": 1.551311807444E9,
    "uid": "dd06064b-e542-40a9-bbc7-e381a47ea0e0",
    "version": 1
  },
  "spec": {
    "provider": {
      "virtualNode": {
        "virtualNodeName": "colorgateway-vn"
      },
      "virtualRouter": null
    }
  },
  "status": {
    "status": "ACTIVE"
  },
  "virtualServiceName": "colorgateway.default.svc.cluster.local"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListGatewayRoutes

Returns a list of existing gateway routes that are associated to a virtual gateway.

Request Syntax

```
GET /v20190125/meshes/meshName/virtualGateway/virtualGatewayName/gatewayRoutes?  
limit=limit&meshOwner=meshOwner&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

limit

The maximum number of results returned by ListGatewayRoutes in paginated output. When you use this parameter, ListGatewayRoutes returns only *limit* results in a single page along with a *nextToken* response element. You can see the remaining results of the initial request by sending another ListGatewayRoutes request with the returned *nextToken* value. This value can be between 1 and 100. If you don't use this parameter, ListGatewayRoutes returns up to 100 results and a *nextToken* value if applicable.

Valid Range: Minimum value of 1. Maximum value of 100.

meshName

The name of the service mesh to list gateway routes in.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then it's the ID of the account that shared the mesh with your account. For more information about mesh sharing, see [Working with shared meshes](#).

Length Constraints: Fixed length of 12.

nextToken

The `nextToken` value returned from a previous paginated `ListGatewayRoutes` request where `limit` was used and the results exceeded the value of that parameter. Pagination continues from the end of the previous results that returned the `nextToken` value.

virtualGatewayName

The name of the virtual gateway to list gateway routes in.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "gatewayRoutes": [
    {
      "arn": "string",
      "createdAt": number,
      "gatewayRouteName": "string",
      "lastUpdatedAt": number,
      "meshName": "string",
      "meshOwner": "string",
      "resourceOwner": "string",
      "version": number,
      "virtualGatewayName": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[gatewayRoutes](#)

The list of existing gateway routes for the specified service mesh and virtual gateway.

Type: Array of [GatewayRouteRef](#) objects

[nextToken](#)

The nextToken value to include in a future ListGatewayRoutes request. When the results of a ListGatewayRoutes request exceed limit, you can use this value to retrieve the next page of results. This value is null when there are no more results to return.

Type: String

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You need to learn how to sign HTTP requests only if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

The following example lists gateway routes that are associated with the virtual gateway named myVirtualGateway in the apps service mesh.

Sample Request

```
GET /v20190125/meshes/apps/virtualGateway/myVirtualGateway/gatewayRoutes HTTP/1.1
Host: appmesh.us-west-2.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.16.298 Python/3.6.0 Windows/10 botocore/1.13.34
X-Amz-Date: 20200608T190053Z
Authorization: AUTHPARAMS
```

Sample Response

```
HTTP/1.1 200 OK
```

```
x-amzn-requestid: b82c3691-a7a9-4d99-acf6-0f9a81db9beb
content-type: application/json
content-length: 393
date: Mon, 08 Jun 2020 20:52:25 GMT
x-envoy-upstream-service-time: 26
server: envoy
Connection: keep-alive

{
  "gatewayRoutes": [{
    "arn": "arn:aws:appmesh:us-west-2:123456789012:mesh/apps/virtualGateway/myVirtualGateway/gatewayRoute/myGatewayRoute",
    "createdAt": 1.591642091122E9,
    "gatewayRouteName": "myGatewayRoute",
    "lastUpdatedAt": 1.591642091122E9,
    "meshName": "myApps",
    "meshOwner": "123456789012",
    "resourceOwner": "123456789012",
    "version": 1,
    "virtualGatewayName": "myVirtualGateway"
  }],
  "nextToken": null
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListMeshes

Returns a list of existing service meshes.

Request Syntax

```
GET /v20190125/meshes?limit=limit&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

limit

The maximum number of results returned by ListMeshes in paginated output. When you use this parameter, ListMeshes returns only `limit` results in a single page along with a `nextToken` response element. You can see the remaining results of the initial request by sending another ListMeshes request with the returned `nextToken` value. This value can be between 1 and 100. If you don't use this parameter, ListMeshes returns up to 100 results and a `nextToken` value if applicable.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

The `nextToken` value returned from a previous paginated ListMeshes request where `limit` was used and the results exceeded the value of that parameter. Pagination continues from the end of the previous results that returned the `nextToken` value.

Note

This token should be treated as an opaque identifier that is used only to retrieve the next items in a list and not for other programmatic purposes.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "meshes": [
    {
      "arn": "string",
      "createdAt": number,
      "lastUpdatedAt": number,
      "meshName": "string",
      "meshOwner": "string",
      "resourceOwner": "string",
      "version": number
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

meshes

The list of existing service meshes.

Type: Array of [MeshRef](#) objects

nextToken

The nextToken value to include in a future ListMeshes request. When the results of a ListMeshes request exceed limit, you can use this value to retrieve the next page of results. This value is null when there are no more results to return.

Type: String

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You need to learn how to sign HTTP requests only if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example lists the service meshes for an account in the us-east-1 Region.

Sample Request

```
GET /v20190125/meshes HTTP/1.1
Host: appmesh.us-east-1.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.16.56 Python/3.7.0 Darwin/17.7.0 botocore/1.12.46
X-Amz-Date: 20190227T235715Z
Authorization: AUTHPARAMS
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-requestid: 572dcc56-18d6-4f86-b596-8e182f81afce
content-type: application/json
content-length: 114
date: Wed, 27 Feb 2019 23:57:15 GMT
x-envoy-upstream-service-time: 67
server: envoy
Connection: keep-alive

{
  "meshes": [
    {
      "arn": "arn:aws:appmesh:us-east-1:123456789012:mesh/ecs-mesh",
      "meshName": "ecs-mesh"
    }
  ],
  "nextToken": null
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListRoutes

Returns a list of existing routes in a service mesh.

Request Syntax

```
GET /v20190125/meshes/meshName/virtualRouter/virtualRouterName/routes?  
limit=limit&meshOwner=meshOwner&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

limit

The maximum number of results returned by ListRoutes in paginated output. When you use this parameter, ListRoutes returns only `limit` results in a single page along with a `nextToken` response element. You can see the remaining results of the initial request by sending another ListRoutes request with the returned `nextToken` value. This value can be between 1 and 100. If you don't use this parameter, ListRoutes returns up to 100 results and a `nextToken` value if applicable.

Valid Range: Minimum value of 1. Maximum value of 100.

meshName

The name of the service mesh to list routes in.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then it's the ID of the account that shared the mesh with your account. For more information about mesh sharing, see [Working with shared meshes](#).

Length Constraints: Fixed length of 12.

nextToken

The `nextToken` value returned from a previous paginated `ListRoutes` request where `limit` was used and the results exceeded the value of that parameter. Pagination continues from the end of the previous results that returned the `nextToken` value.

virtualRouterName

The name of the virtual router to list routes in.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "routes": [
    {
      "arn": "string",
      "createdAt": number,
      "lastUpdatedAt": number,
      "meshName": "string",
      "meshOwner": "string",
      "resourceOwner": "string",
      "routeName": "string",
      "version": number,
      "virtualRouterName": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[nextToken](#)

The `nextToken` value to include in a future `ListRoutes` request. When the results of a `ListRoutes` request exceed `limit`, you can use this value to retrieve the next page of results. This value is `null` when there are no more results to return.

Type: String

[routes](#)

The list of existing routes for the specified service mesh and virtual router.

Type: Array of [RouteRef](#) objects

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You need to learn how to sign HTTP requests only if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

The following example lists the routes that are associated with the `colorteller-vr` virtual router in the `ecs-mesh` service mesh.

Sample Request

```
GET /v20190125/meshes/ecs-mesh/virtualRouter/colorteller-vr/routes HTTP/1.1
Host: appmesh.us-east-1.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.16.56 Python/3.7.0 Darwin/17.7.0 botocore/1.12.46
X-Amz-Date: 20190227T235954Z
Authorization: AUTHPARAMS
```

Sample Response

```
HTTP/1.1 200 OK
```

```
x-amzn-requestid: 5a783529-a278-44d2-b450-4e23898cb180
content-type: application/json
content-length: 236
date: Wed, 27 Feb 2019 23:59:54 GMT
x-envoy-upstream-service-time: 56
server: envoy
Connection: keep-alive

{
  "nextToken": null,
  "routes": [
    {
      "arn": "arn:aws:appmesh:us-east-1:123456789012:mesh/ecs-mesh/virtualRouter/colorteller-vr/route/colorteller-route",
      "meshName": "ecs-mesh",
      "routeName": "colorteller-route",
      "virtualRouterName": "colorteller-vr"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

List the tags for an App Mesh resource.

Request Syntax

```
GET /v20190125/tags?limit=limit&nextToken=nextToken&resourceArn=resourceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

limit

The maximum number of tag results returned by ListTagsForResource in paginated output. When this parameter is used, ListTagsForResource returns only limit results in a single page along with a nextToken response element. You can see the remaining results of the initial request by sending another ListTagsForResource request with the returned nextToken value. This value can be between 1 and 100. If you don't use this parameter, ListTagsForResource returns up to 100 results and a nextToken value if applicable.

Valid Range: Minimum value of 1. Maximum value of 50.

nextToken

The nextToken value returned from a previous paginated ListTagsForResource request where limit was used and the results exceeded the value of that parameter. Pagination continues from the end of the previous results that returned the nextToken value.

resourceArn

The Amazon Resource Name (ARN) that identifies the resource to list the tags for.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "tags": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[nextToken](#)

The nextToken value to include in a future ListTagsForResource request. When the results of a ListTagsForResource request exceed limit, you can use this value to retrieve the next page of results. This value is null when there are no more results to return.

Type: String

[tags](#)

The tags for the resource.

Type: Array of [TagRef](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListVirtualGateways

Returns a list of existing virtual gateways in a service mesh.

Request Syntax

```
GET /v20190125/meshes/meshName/virtualGateways?  
limit=limit&meshOwner=meshOwner&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

limit

The maximum number of results returned by ListVirtualGateways in paginated output. When you use this parameter, ListVirtualGateways returns only *limit* results in a single page along with a *nextToken* response element. You can see the remaining results of the initial request by sending another ListVirtualGateways request with the returned *nextToken* value. This value can be between 1 and 100. If you don't use this parameter, ListVirtualGateways returns up to 100 results and a *nextToken* value if applicable.

Valid Range: Minimum value of 1. Maximum value of 100.

meshName

The name of the service mesh to list virtual gateways in.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then it's the ID of the account that shared the mesh with your account. For more information about mesh sharing, see [Working with shared meshes](#).

Length Constraints: Fixed length of 12.

nextToken

The `nextToken` value returned from a previous paginated `ListVirtualGateways` request where `limit` was used and the results exceeded the value of that parameter. Pagination continues from the end of the previous results that returned the `nextToken` value.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "virtualGateways": [
    {
      "arn": "string",
      "createdAt": number,
      "lastUpdatedAt": number,
      "meshName": "string",
      "meshOwner": "string",
      "resourceOwner": "string",
      "version": number,
      "virtualGatewayName": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[nextToken](#)

The `nextToken` value to include in a future `ListVirtualGateways` request. When the results of a `ListVirtualGateways` request exceed `limit`, you can use this value to retrieve the next page of results. This value is `null` when there are no more results to return.

Type: String

[virtualGateways](#)

The list of existing virtual gateways for the specified service mesh.

Type: Array of [VirtualGatewayRef](#) objects

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You need to learn how to sign HTTP requests only if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

The following example lists the virtual gateways that are in the apps service mesh.

Sample Request

```
GET /v20190125/meshes/apps/virtualGateways HTTP/1.1
Host: appmesh.us-west-2.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.16.298 Python/3.6.0 Windows/10 botocore/1.13.34
X-Amz-Date: 20200608T185502Z
Authorization: AUTHPARAMS
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-requestid: 3add7f54-944b-464a-93ed-57589ed5158d
content-type: application/json
content-length: 331
date: Mon, 08 Jun 2020 20:53:50 GMT
x-envoy-upstream-service-time: 24
```

```
server: envoy
Connection: keep-alive

{
  "nextToken": null,
  "virtualGateways": [{
    "arn": "arn:aws:appmesh:us-west-2:123456789012:mesh/apps/virtualGateway/myVirtualGateway",
    "createdAt": 1.591630673505E9,
    "lastUpdatedAt": 1.591630673505E9,
    "meshName": "apps",
    "meshOwner": "123456789012",
    "resourceOwner": "123456789012",
    "version": 1,
    "virtualGatewayName": "myVirtualGateway"
  }]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListVirtualNodes

Returns a list of existing virtual nodes.

Request Syntax

```
GET /v20190125/meshes/meshName/virtualNodes?  
limit=limit&meshOwner=meshOwner&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

limit

The maximum number of results returned by ListVirtualNodes in paginated output. When you use this parameter, ListVirtualNodes returns only limit results in a single page along with a nextToken response element. You can see the remaining results of the initial request by sending another ListVirtualNodes request with the returned nextToken value. This value can be between 1 and 100. If you don't use this parameter, ListVirtualNodes returns up to 100 results and a nextToken value if applicable.

Valid Range: Minimum value of 1. Maximum value of 100.

meshName

The name of the service mesh to list virtual nodes in.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then it's the ID of the account that shared the mesh with your account. For more information about mesh sharing, see [Working with shared meshes](#).

Length Constraints: Fixed length of 12.

nextToken

The `nextToken` value returned from a previous paginated `ListVirtualNodes` request where `limit` was used and the results exceeded the value of that parameter. Pagination continues from the end of the previous results that returned the `nextToken` value.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "virtualNodes": [
    {
      "arn": "string",
      "createdAt": number,
      "lastUpdatedAt": number,
      "meshName": "string",
      "meshOwner": "string",
      "resourceOwner": "string",
      "version": number,
      "virtualNodeName": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

The nextToken value to include in a future ListVirtualNodes request. When the results of a ListVirtualNodes request exceed limit, you can use this value to retrieve the next page of results. This value is null when there are no more results to return.

Type: String

virtualNodes

The list of existing virtual nodes for the specified service mesh.

Type: Array of [VirtualNodeRef](#) objects

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You need to learn how to sign HTTP requests only if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

The following example lists the virtual nodes that reside in the ecs-mesh service mesh.

Sample Request

```
GET /v20190125/meshes/ecs-mesh/virtualNodes HTTP/1.1
Host: appmesh.us-east-1.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.16.56 Python/3.7.0 Darwin/17.7.0 botocore/1.12.46
X-Amz-Date: 20190227T235730Z
Authorization: AUTHPARAMS
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-requestid: 8fbb6448-5519-4f45-97d1-ed4d3238aa69
content-type: application/json
content-length: 941
date: Wed, 27 Feb 2019 23:57:31 GMT
x-envoy-upstream-service-time: 108
server: envoy
```

Connection: keep-alive

```
{
  "nextToken": null,
  "virtualNodes": [
    {
      "arn": "arn:aws:appmesh:us-east-1:123456789012:mesh/ecs-mesh/virtualNode/colorteller-vn",
      "meshName": "ecs-mesh",
      "virtualNodeName": "colorteller-vn"
    },
    {
      "arn": "arn:aws:appmesh:us-east-1:123456789012:mesh/ecs-mesh/virtualNode/tcpecho-vn",
      "meshName": "ecs-mesh",
      "virtualNodeName": "tcpecho-vn"
    },
    {
      "arn": "arn:aws:appmesh:us-east-1:123456789012:mesh/ecs-mesh/virtualNode/colorteller-black-vn",
      "meshName": "ecs-mesh",
      "virtualNodeName": "colorteller-black-vn"
    },
    {
      "arn": "arn:aws:appmesh:us-east-1:123456789012:mesh/ecs-mesh/virtualNode/colorgateway-vn",
      "meshName": "ecs-mesh",
      "virtualNodeName": "colorgateway-vn"
    },
    {
      "arn": "arn:aws:appmesh:us-east-1:123456789012:mesh/ecs-mesh/virtualNode/colorteller-red-vn",
      "meshName": "ecs-mesh",
      "virtualNodeName": "colorteller-red-vn"
    },
    {
      "arn": "arn:aws:appmesh:us-east-1:123456789012:mesh/ecs-mesh/virtualNode/colorteller-blue-vn",
      "meshName": "ecs-mesh",
      "virtualNodeName": "colorteller-blue-vn"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListVirtualRouters

Returns a list of existing virtual routers in a service mesh.

Request Syntax

```
GET /v20190125/meshes/meshName/virtualRouters?  
limit=limit&meshOwner=meshOwner&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

limit

The maximum number of results returned by ListVirtualRouters in paginated output. When you use this parameter, ListVirtualRouters returns only limit results in a single page along with a nextToken response element. You can see the remaining results of the initial request by sending another ListVirtualRouters request with the returned nextToken value. This value can be between 1 and 100. If you don't use this parameter, ListVirtualRouters returns up to 100 results and a nextToken value if applicable.

Valid Range: Minimum value of 1. Maximum value of 100.

meshName

The name of the service mesh to list virtual routers in.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then it's the ID of the account that shared the mesh with your account. For more information about mesh sharing, see [Working with shared meshes](#).

Length Constraints: Fixed length of 12.

nextToken

The `nextToken` value returned from a previous paginated `ListVirtualRouters` request where `limit` was used and the results exceeded the value of that parameter. Pagination continues from the end of the previous results that returned the `nextToken` value.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "virtualRouters": [
    {
      "arn": "string",
      "createdAt": number,
      "lastUpdatedAt": number,
      "meshName": "string",
      "meshOwner": "string",
      "resourceOwner": "string",
      "version": number,
      "virtualRouterName": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[nextToken](#)

The `nextToken` value to include in a future `ListVirtualRouters` request. When the results of a `ListVirtualRouters` request exceed `limit`, you can use this value to retrieve the next page of results. This value is `null` when there are no more results to return.

Type: String

[virtualRouters](#)

The list of existing virtual routers for the specified service mesh.

Type: Array of [VirtualRouterRef](#) objects

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You need to learn how to sign HTTP requests only if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

The following example lists the virtual routers that reside in the `ecs-mesh` service mesh.

Sample Request

```
GET /v20190125/meshes/ecs-mesh/virtualRouters HTTP/1.1
Host: appmesh.us-east-1.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.16.56 Python/3.7.0 Darwin/17.7.0 botocore/1.12.46
X-Amz-Date: 20190227T235738Z
Authorization: AUTHPARAMS
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-requestid: ec2895b6-ffaf-4d0a-b1dd-830901321588
content-type: application/json
content-length: 341
date: Wed, 27 Feb 2019 23:57:38 GMT
x-envoy-upstream-service-time: 43
```

```
server: envoy
Connection: keep-alive

{
  "nextToken": null,
  "virtualRouters": [
    {
      "arn": "arn:aws:appmesh:us-east-1:123456789012:mesh/ecs-mesh/virtualRouter/colorteller-vr",
      "meshName": "ecs-mesh",
      "virtualRouterName": "colorteller-vr"
    },
    {
      "arn": "arn:aws:appmesh:us-east-1:123456789012:mesh/ecs-mesh/virtualRouter/colorgateway-vr",
      "meshName": "ecs-mesh",
      "virtualRouterName": "colorgateway-vr"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListVirtualServices

Returns a list of existing virtual services in a service mesh.

Request Syntax

```
GET /v20190125/meshes/meshName/virtualServices?  
limit=limit&meshOwner=meshOwner&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

limit

The maximum number of results returned by ListVirtualServices in paginated output. When you use this parameter, ListVirtualServices returns only limit results in a single page along with a nextToken response element. You can see the remaining results of the initial request by sending another ListVirtualServices request with the returned nextToken value. This value can be between 1 and 100. If you don't use this parameter, ListVirtualServices returns up to 100 results and a nextToken value if applicable.

Valid Range: Minimum value of 1. Maximum value of 100.

meshName

The name of the service mesh to list virtual services in.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then it's the ID of the account that shared the mesh with your account. For more information about mesh sharing, see [Working with shared meshes](#).

Length Constraints: Fixed length of 12.

nextToken

The `nextToken` value returned from a previous paginated `ListVirtualServices` request where `limit` was used and the results exceeded the value of that parameter. Pagination continues from the end of the previous results that returned the `nextToken` value.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "virtualServices": [
    {
      "arn": "string",
      "createdAt": number,
      "lastUpdatedAt": number,
      "meshName": "string",
      "meshOwner": "string",
      "resourceOwner": "string",
      "version": number,
      "virtualServiceName": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[nextToken](#)

The `nextToken` value to include in a future `ListVirtualServices` request. When the results of a `ListVirtualServices` request exceed `limit`, you can use this value to retrieve the next page of results. This value is `null` when there are no more results to return.

Type: String

[virtualServices](#)

The list of existing virtual services for the specified service mesh.

Type: Array of [VirtualServiceRef](#) objects

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You need to learn how to sign HTTP requests only if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example lists the virtual services in the ecs-mesh service mesh.

Sample Request

```
GET /v20190125/meshes/ecs-mesh/virtualServices HTTP/1.1
Host: appmesh.us-east-1.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.16.56 Python/3.7.0 Darwin/17.7.0 botocore/1.12.46
X-Amz-Date: 20190227T235746Z
Authorization: AUTHPARAMS
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-requestid: 1e2ccc92-46aa-4541-ae10-9790266e7436
content-type: application/json
content-length: 629
date: Wed, 27 Feb 2019 23:57:46 GMT
x-envoy-upstream-service-time: 9
```

```
server: envoy
Connection: keep-alive

{
  "nextToken": null,
  "virtualServices": [
    {
      "arn": "arn:aws:appmesh:us-east-1:123456789012:mesh/ecs-mesh/virtualService/tcpecho.default.svc.cluster.local",
      "meshName": "ecs-mesh",
      "virtualServiceName": "tcpecho.default.svc.cluster.local"
    },
    {
      "arn": "arn:aws:appmesh:us-east-1:123456789012:mesh/ecs-mesh/virtualService/colorteller.default.svc.cluster.local",
      "meshName": "ecs-mesh",
      "virtualServiceName": "colorteller.default.svc.cluster.local"
    },
    {
      "arn": "arn:aws:appmesh:us-east-1:123456789012:mesh/ecs-mesh/virtualService/colorgateway.default.svc.cluster.local",
      "meshName": "ecs-mesh",
      "virtualServiceName": "colorgateway.default.svc.cluster.local"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Associates the specified tags to a resource with the specified `resourceArn`. If existing tags on a resource aren't specified in the request parameters, they aren't changed. When a resource is deleted, the tags associated with that resource are also deleted.

Request Syntax

```
PUT /v20190125/tag?resourceArn=resourceArn HTTP/1.1
Content-type: application/json
```

```
{
  "tags": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The Amazon Resource Name (ARN) of the resource to add tags to.

Required: Yes

Request Body

The request accepts the following data in JSON format.

tags

The tags to add to the resource. A tag is an array of key-value pairs. Tag keys can have a maximum character length of 128 characters, and tag values can have a maximum length of 256 characters.

Type: Array of [TagRef](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

TooManyTagsException

The request exceeds the maximum allowed number of tags allowed per resource. The current limit is 50 user tags per resource. You must reduce the number of tags in the request. None of the tags in this request were applied.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Deletes specified tags from a resource.

Request Syntax

```
PUT /v20190125/untag?resourceArn=resourceArn HTTP/1.1
Content-type: application/json

{
  "tagKeys": [ "string" ]
}
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The Amazon Resource Name (ARN) of the resource to delete tags from.

Required: Yes

Request Body

The request accepts the following data in JSON format.

tagKeys

The keys of the tags to be removed.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateGatewayRoute

Updates an existing gateway route that is associated to a specified virtual gateway in a service mesh.

Request Syntax

```
PUT /v20190125/meshes/meshName/virtualGateway/virtualGatewayName/
gatewayRoutes/gatewayRouteName?meshOwner=meshOwner HTTP/1.1
Content-type: application/json
```

```
{
  "clientToken": "string",
  "spec": {
    "grpcRoute": {
      "action": {
        "rewrite": {
          "hostname": {
            "defaultTargetHostname": "string"
          }
        },
        "target": {
          "port": number,
          "virtualService": {
            "virtualServiceName": "string"
          }
        }
      },
      "match": {
        "hostname": {
          "exact": "string",
          "suffix": "string"
        },
        "metadata": [
          {
            "invert": boolean,
            "match": { ... },
            "name": "string"
          }
        ],
        "port": number,
        "serviceName": "string"
      }
    }
  }
}
```



```

},
"http2Route": {
  "action": {
    "rewrite": {
      "hostname": {
        "defaultTargetHostname": "string"
      },
      "path": {
        "exact": "string"
      },
      "prefix": {
        "defaultPrefix": "string",
        "value": "string"
      }
    },
    "target": {
      "port": number,
      "virtualService": {
        "virtualServiceName": "string"
      }
    }
  },
  "match": {
    "headers": [
      {
        "invert": boolean,
        "match": { ... },
        "name": "string"
      }
    ],
    "hostname": {
      "exact": "string",
      "suffix": "string"
    },
    "method": "string",
    "path": {
      "exact": "string",
      "regex": "string"
    },
    "port": number,
    "prefix": "string",
    "queryParameters": [
      {
        "match": {

```

```

        "exact": "string"
      },
      "name": "string"
    }
  ]
}
},
"httpRoute": {
  "action": {
    "rewrite": {
      "hostname": {
        "defaultTargetHostname": "string"
      },
      "path": {
        "exact": "string"
      },
      "prefix": {
        "defaultPrefix": "string",
        "value": "string"
      }
    },
    "target": {
      "port": number,
      "virtualService": {
        "virtualServiceName": "string"
      }
    }
  },
  "match": {
    "headers": [
      {
        "invert": boolean,
        "match": { ... },
        "name": "string"
      }
    ],
    "hostname": {
      "exact": "string",
      "suffix": "string"
    },
    "method": "string",
    "path": {
      "exact": "string",
      "regex": "string"
    }
  }
}

```

```
    },
    "port": number,
    "prefix": "string",
    "queryParameters": [
      {
        "match": {
          "exact": "string"
        },
        "name": "string"
      }
    ]
  },
  "priority": number
}
```

URI Request Parameters

The request uses the following URI parameters.

gatewayRouteName

The name of the gateway route to update.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshName

The name of the service mesh that the gateway route resides in.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then it's the ID of the account that shared the mesh with your account. For more information about mesh sharing, see [Working with shared meshes](#).

Length Constraints: Fixed length of 12.

virtualGatewayName

The name of the virtual gateway that the gateway route is associated with.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

Request Body

The request accepts the following data in JSON format.

clientToken

Unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Up to 36 letters, numbers, hyphens, and underscores are allowed.

Type: String

Required: No

spec

The new gateway route specification to apply. This overwrites the existing data.

Type: [GatewayRouteSpec](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "gatewayRouteName": "string",
  "meshName": "string",
  "metadata": {
    "arn": "string",
    "createdAt": number,
    "lastUpdatedAt": number,
    "meshOwner": "string",
    "resourceOwner": "string",
```

```

    "uid": "string",
    "version": number
  },
  "spec": {
    "grpcRoute": {
      "action": {
        "rewrite": {
          "hostname": {
            "defaultTargetHostname": "string"
          }
        },
        "target": {
          "port": number,
          "virtualService": {
            "virtualServiceName": "string"
          }
        }
      }
    },
    "match": {
      "hostname": {
        "exact": "string",
        "suffix": "string"
      },
      "metadata": [
        {
          "invert": boolean,
          "match": { ... },
          "name": "string"
        }
      ],
      "port": number,
      "serviceName": "string"
    }
  },
  "http2Route": {
    "action": {
      "rewrite": {
        "hostname": {
          "defaultTargetHostname": "string"
        },
        "path": {
          "exact": "string"
        },
        "prefix": {

```

```

        "defaultPrefix": "string",
        "value": "string"
    }
},
"target": {
    "port": number,
    "virtualService": {
        "virtualServiceName": "string"
    }
}
},
"match": {
    "headers": [
        {
            "invert": boolean,
            "match": { ... },
            "name": "string"
        }
    ],
    "hostname": {
        "exact": "string",
        "suffix": "string"
    },
    "method": "string",
    "path": {
        "exact": "string",
        "regex": "string"
    },
    "port": number,
    "prefix": "string",
    "queryParameters": [
        {
            "match": {
                "exact": "string"
            },
            "name": "string"
        }
    ]
}
},
"httpRoute": {
    "action": {
        "rewrite": {
            "hostname": {

```

```

        "defaultTargetHostname": "string"
    },
    "path": {
        "exact": "string"
    },
    "prefix": {
        "defaultPrefix": "string",
        "value": "string"
    }
},
"target": {
    "port": number,
    "virtualService": {
        "virtualServiceName": "string"
    }
}
},
"match": {
    "headers": [
        {
            "invert": boolean,
            "match": { ... },
            "name": "string"
        }
    ],
    "hostname": {
        "exact": "string",
        "suffix": "string"
    },
    "method": "string",
    "path": {
        "exact": "string",
        "regex": "string"
    },
    "port": number,
    "prefix": "string",
    "queryParameters": [
        {
            "match": {
                "exact": "string"
            },
            "name": "string"
        }
    ]
}
]

```

```
    }  
  },  
  "priority": number  
},  
"status": {  
  "status": "string"  
},  
"virtualGatewayName": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

gatewayRouteName

The name of the gateway route.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

meshName

The name of the service mesh that the resource resides in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

metadata

An object that represents metadata for a resource.

Type: [ResourceMetadata](#) object

spec

The specifications of the gateway route.

Type: [GatewayRouteSpec](#) object

status

The status of the gateway route.

Type: [GatewayRouteStatus](#) object

[virtualGatewayName](#)

The virtual gateway that the gateway route is associated with.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ConflictException

The request contains a client token that was used for a previous update resource call with different specifications. Try the request again with a new client token.

HTTP Status Code: 409

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

LimitExceededException

You have exceeded a service limit for your account. For more information, see [Service Limits](#) in the *AWS App Mesh User Guide*.

HTTP Status Code: 400

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You need to learn how to sign HTTP requests only if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

The following example updates a gateway route named myGatewayRoute that is associated to the myVirtualGateway virtual gateway in the apps service mesh.

Sample Request

```
PUT /v20190125/meshes/apps/virtualGateway/myVirtualGateway/gatewayRoutes/myGatewayRoute
HTTP/1.1
Host: appmesh.us-west-2.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.16.298 Python/3.6.0 Windows/10 botocore/1.13.34
X-Amz-Date: 20200608T192800Z
Authorization: AUTHPARAMS
```

```
{
  "spec": {
    "http2Route": {
      "action": {
        "target": {
          "virtualService": {
            "virtualServiceName": "myserviceb.svc.cluster.local"
          }
        }
      },
      "match": {
        "prefix": "/"
      }
    }
  },
  "clientToken": "1aa1111a-1111-1111-111a-a1a1a1aa111a"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-requestid: 6c253f78-e011-4533-a926-e75416f06641
content-type: application/json
content-length: 617
date: Mon, 08 Jun 2020 19:28:00 GMT
x-envoy-upstream-service-time: 76
server: envoy
Connection: keep-alive

{
  "gatewayRouteName": "myGatewayRoute",
  "meshName": "myApps",
  "metadata": {
    "arn": "arn:aws:appmesh:us-west-2:123456789012:mesh/apps/virtualGateway/myVirtualGateway/gatewayRoute/myGatewayRoute",
    "createdAt": 1.591642091122E9,
    "lastUpdatedAt": 1.591644481211E9,
    "meshOwner": "123456789012",
    "resourceOwner": "123456789012",
    "uid": "ff111ff2-33ff-4ff4-ffff-111f111f111f",
    "version": 2
  },
  "spec": {
```

```
"grpcRoute": null,
"http2Route": {
  "action": {
    "target": {
      "virtualService": {
        "virtualServiceName": "myserviceb.svc.cluster.local"
      }
    }
  },
  "match": {
    "prefix": "/"
  },
  "httpRoute": null
},
"status": {
  "status": "ACTIVE"
},
"virtualGatewayName": "myVirtualGateway"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateMesh

Updates an existing service mesh.

Request Syntax

```
PUT /v20190125/meshes/meshName HTTP/1.1
Content-type: application/json
```

```
{
  "clientToken": "string",
  "spec": {
    "egressFilter": {
      "type": "string"
    },
    "serviceDiscovery": {
      "ipPreference": "string"
    }
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

meshName

The name of the service mesh to update.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

Request Body

The request accepts the following data in JSON format.

clientToken

Unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Up to 36 letters, numbers, hyphens, and underscores are allowed.

Type: String

Required: No

spec

The service mesh specification to apply.

Type: [MeshSpec](#) object

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "meshName": "string",
  "metadata": {
    "arn": "string",
    "createdAt": number,
    "lastUpdatedAt": number,
    "meshOwner": "string",
    "resourceOwner": "string",
    "uid": "string",
    "version": number
  },
  "spec": {
    "egressFilter": {
      "type": "string"
    },
    "serviceDiscovery": {
      "ipPreference": "string"
    }
  },
  "status": {
    "status": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

meshName

The name of the service mesh.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

metadata

The associated metadata for the service mesh.

Type: [ResourceMetadata](#) object

spec

The associated specification for the service mesh.

Type: [MeshSpec](#) object

status

The status of the service mesh.

Type: [MeshStatus](#) object

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ConflictException

The request contains a client token that was used for a previous update resource call with different specifications. Try the request again with a new client token.

HTTP Status Code: 409

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateRoute

Updates an existing route for a specified service mesh and virtual router.

Request Syntax

```
PUT /v20190125/meshes/meshName/virtualRouter/virtualRouterName/routes/routeName?
meshOwner=meshOwner HTTP/1.1
Content-type: application/json
```

```
{
  "clientToken": "string",
  "spec": {
    "grpcRoute": {
      "action": {
        "weightedTargets": [
          {
            "port": number,
            "virtualNode": "string",
            "weight": number
          }
        ]
      },
      "match": {
        "metadata": [
          {
            "invert": boolean,
            "match": { ... },
            "name": "string"
          }
        ],
        "methodName": "string",
        "port": number,
        "serviceName": "string"
      },
      "retryPolicy": {
        "grpcRetryEvents": [ "string" ],
        "httpRetryEvents": [ "string" ],
        "maxRetries": number,
        "perRetryTimeout": {
          "unit": "string",
          "value": number
        }
      }
    }
  }
}
```

```

    "tcpRetryEvents": [ "string" ]
  },
  "timeout": {
    "idle": {
      "unit": "string",
      "value": number
    },
    "perRequest": {
      "unit": "string",
      "value": number
    }
  }
},
"http2Route": {
  "action": {
    "weightedTargets": [
      {
        "port": number,
        "virtualNode": "string",
        "weight": number
      }
    ]
  },
  "match": {
    "headers": [
      {
        "invert": boolean,
        "match": { ... },
        "name": "string"
      }
    ],
    "method": "string",
    "path": {
      "exact": "string",
      "regex": "string"
    },
    "port": number,
    "prefix": "string",
    "queryParameters": [
      {
        "match": {
          "exact": "string"
        },
        "name": "string"
      }
    ]
  }
}

```

```

    }
  ],
  "scheme": "string"
},
"retryPolicy": {
  "httpRetryEvents": [ "string" ],
  "maxRetries": number,
  "perRetryTimeout": {
    "unit": "string",
    "value": number
  },
  "tcpRetryEvents": [ "string" ]
},
"timeout": {
  "idle": {
    "unit": "string",
    "value": number
  },
  "perRequest": {
    "unit": "string",
    "value": number
  }
}
},
"httpRoute": {
  "action": {
    "weightedTargets": [
      {
        "port": number,
        "virtualNode": "string",
        "weight": number
      }
    ]
  },
  "match": {
    "headers": [
      {
        "invert": boolean,
        "match": { ... },
        "name": "string"
      }
    ],
    "method": "string",
    "path": {

```

```

        "exact": "string",
        "regex": "string"
    },
    "port": number,
    "prefix": "string",
    "queryParameters": [
        {
            "match": {
                "exact": "string"
            },
            "name": "string"
        }
    ],
    "scheme": "string"
},
"retryPolicy": {
    "httpRetryEvents": [ "string" ],
    "maxRetries": number,
    "perRetryTimeout": {
        "unit": "string",
        "value": number
    },
    "tcpRetryEvents": [ "string" ]
},
"timeout": {
    "idle": {
        "unit": "string",
        "value": number
    },
    "perRequest": {
        "unit": "string",
        "value": number
    }
}
},
"priority": number,
"tcpRoute": {
    "action": {
        "weightedTargets": [
            {
                "port": number,
                "virtualNode": "string",
                "weight": number
            }
        ]
    }
}

```

```
    ]
  },
  "match": {
    "port": number
  },
  "timeout": {
    "idle": {
      "unit": "string",
      "value": number
    }
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

meshName

The name of the service mesh that the route resides in.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then it's the ID of the account that shared the mesh with your account. For more information about mesh sharing, see [Working with shared meshes](#).

Length Constraints: Fixed length of 12.

routeName

The name of the route to update.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

virtualRouterName

The name of the virtual router that the route is associated with.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

Request Body

The request accepts the following data in JSON format.

clientToken

Unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Up to 36 letters, numbers, hyphens, and underscores are allowed.

Type: String

Required: No

spec

The new route specification to apply. This overwrites the existing data.

Type: [RouteSpec](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "meshName": "string",
  "metadata": {
    "arn": "string",
    "createdAt": number,
    "lastUpdatedAt": number,
    "meshOwner": "string",
    "resourceOwner": "string",
    "uid": "string",
    "version": number
  },
  "routeName": "string",
  "spec": {
```

```

    "grpcRoute": {
      "action": {
        "weightedTargets": [
          {
            "port": number,
            "virtualNode": "string",
            "weight": number
          }
        ]
      },
      "match": {
        "metadata": [
          {
            "invert": boolean,
            "match": { ... },
            "name": "string"
          }
        ],
        "methodName": "string",
        "port": number,
        "serviceName": "string"
      },
      "retryPolicy": {
        "grpcRetryEvents": [ "string" ],
        "httpRetryEvents": [ "string" ],
        "maxRetries": number,
        "perRetryTimeout": {
          "unit": "string",
          "value": number
        },
        "tcpRetryEvents": [ "string" ]
      },
      "timeout": {
        "idle": {
          "unit": "string",
          "value": number
        },
        "perRequest": {
          "unit": "string",
          "value": number
        }
      }
    },
    "http2Route": {

```



```

    "action": {
      "weightedTargets": [
        {
          "port": number,
          "virtualNode": "string",
          "weight": number
        }
      ]
    },
    "match": {
      "headers": [
        {
          "invert": boolean,
          "match": { ... },
          "name": "string"
        }
      ],
      "method": "string",
      "path": {
        "exact": "string",
        "regex": "string"
      },
      "port": number,
      "prefix": "string",
      "queryParameters": [
        {
          "match": {
            "exact": "string"
          },
          "name": "string"
        }
      ],
      "scheme": "string"
    },
    "retryPolicy": {
      "httpRetryEvents": [ "string" ],
      "maxRetries": number,
      "perRetryTimeout": {
        "unit": "string",
        "value": number
      },
      "tcpRetryEvents": [ "string" ]
    },
    "timeout": {

```

```

    "idle": {
      "unit": "string",
      "value": number
    },
    "perRequest": {
      "unit": "string",
      "value": number
    }
  },
  "httpRoute": {
    "action": {
      "weightedTargets": [
        {
          "port": number,
          "virtualNode": "string",
          "weight": number
        }
      ]
    },
    "match": {
      "headers": [
        {
          "invert": boolean,
          "match": { ... },
          "name": "string"
        }
      ],
      "method": "string",
      "path": {
        "exact": "string",
        "regex": "string"
      },
      "port": number,
      "prefix": "string",
      "queryParameters": [
        {
          "match": {
            "exact": "string"
          },
          "name": "string"
        }
      ],
      "scheme": "string"
    }
  }
}

```

```

    },
    "retryPolicy": {
      "httpRetryEvents": [ "string" ],
      "maxRetries": number,
      "perRetryTimeout": {
        "unit": "string",
        "value": number
      },
      "tcpRetryEvents": [ "string" ]
    },
    "timeout": {
      "idle": {
        "unit": "string",
        "value": number
      },
      "perRequest": {
        "unit": "string",
        "value": number
      }
    }
  },
  "priority": number,
  "tcpRoute": {
    "action": {
      "weightedTargets": [
        {
          "port": number,
          "virtualNode": "string",
          "weight": number
        }
      ]
    },
    "match": {
      "port": number
    },
    "timeout": {
      "idle": {
        "unit": "string",
        "value": number
      }
    }
  }
},
"status": {

```

```
    "status": "string",  
  },  
  "virtualRouterName": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

meshName

The name of the service mesh that the route resides in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

metadata

The associated metadata for the route.

Type: [ResourceMetadata](#) object

routeName

The name of the route.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

spec

The specifications of the route.

Type: [RouteSpec](#) object

status

The status of the route.

Type: [RouteStatus](#) object

virtualRouterName

The virtual router that the route is associated with.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ConflictException

The request contains a client token that was used for a previous update resource call with different specifications. Try the request again with a new client token.

HTTP Status Code: 409

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

LimitExceededException

You have exceeded a service limit for your account. For more information, see [Service Limits](#) in the *AWS App Mesh User Guide*.

HTTP Status Code: 400

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You need to learn how to sign HTTP requests only if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

The following example updates a route for the virtual router named `colorteller-vr` in the `ecs-mesh` service mesh. The route directs traffic to two weighted targets: 80% to `colorteller-blue-vn` and 20% to `colorteller-red-vn`.

Sample Request

```
PUT /v20190125/meshes/ecs-mesh/virtualRouter/colorteller-vr/routes/colorteller-route
HTTP/1.1
Host: appmesh.us-east-1.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.16.56 Python/3.7.0 Darwin/17.7.0 botocore/1.12.46
X-Amz-Date: 20190228T001532Z
Authorization: AUTHPARAMS
```

```
{
  "spec": {
    "httpRoute": {
      "action": {
        "weightedTargets": [
          {
            "virtualNode": "colorteller-blue-vn",
            "weight": 8
          },
          {
            "virtualNode": "colorteller-red-vn",
            "weight": 2
          }
        ]
      },
      "match": {
        "prefix": "/"
      }
    }
  },
  "clientToken": "e8bbfdff-5d3a-4e5c-9c32-571bad83b021"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-requestid: 3375b176-77ba-4f76-be44-98ec4a839b8c
content-type: application/json
content-length: 557
date: Thu, 28 Feb 2019 00:15:32 GMT
x-envoy-upstream-service-time: 56
server: envoy
Connection: keep-alive

{
  "meshName": "ecs-mesh",
  "metadata": {
    "arn": "arn:aws:appmesh:us-east-1:123456789012:mesh/ecs-mesh/virtualRouter/colorteller-vr/route/colorteller-route",
    "createdAt": 1.551311817276E9,
    "lastUpdatedAt": 1.551312932979E9,
    "uid": "1cf3109a-0d7f-438c-b17d-a3785f14ff7b",
```

```
{
  "version": 2
},
"routeName": "colorteller-route",
"spec": {
  "httpRoute": {
    "action": {
      "weightedTargets": [{
        "virtualNode": "colorteller-blue-vn",
        "weight": 8
      }, {
        "virtualNode": "colorteller-red-vn",
        "weight": 2
      }]
    },
    "match": {
      "prefix": "/"
    }
  },
  "tcpRoute": null
},
"status": {
  "status": "ACTIVE"
},
"virtualRouterName": "colorteller-vr"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateVirtualGateway

Updates an existing virtual gateway in a specified service mesh.

Request Syntax

```
PUT /v20190125/meshes/meshName/virtualGateways/virtualGatewayName?meshOwner=meshOwner
HTTP/1.1
```

Content-type: application/json

```
{
  "clientToken": "string",
  "spec": {
    "backendDefaults": {
      "clientPolicy": {
        "tls": {
          "certificate": { ... },
          "enforce": boolean,
          "ports": [ number ],
          "validation": {
            "subjectAlternativeNames": {
              "match": {
                "exact": [ "string" ]
              }
            },
            "trust": { ... }
          }
        }
      }
    },
    "listeners": [
      {
        "connectionPool": { ... },
        "healthCheck": {
          "healthyThreshold": number,
          "intervalMillis": number,
          "path": "string",
          "port": number,
          "protocol": "string",
          "timeoutMillis": number,
          "unhealthyThreshold": number
        },
        "portMapping": {
```

```

        "port": number,
        "protocol": "string"
    },
    "tls": {
        "certificate": { ... },
        "mode": "string",
        "validation": {
            "subjectAlternativeNames": {
                "match": {
                    "exact": [ "string" ]
                }
            },
            "trust": { ... }
        }
    }
},
"logging": {
    "accessLog": { ... }
}
}

```

URI Request Parameters

The request uses the following URI parameters.

meshName

The name of the service mesh that the virtual gateway resides in.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then it's the ID of the account that shared the mesh with your account. For more information about mesh sharing, see [Working with shared meshes](#).

Length Constraints: Fixed length of 12.

virtualGatewayName

The name of the virtual gateway to update.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

Request Body

The request accepts the following data in JSON format.

clientToken

Unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Up to 36 letters, numbers, hyphens, and underscores are allowed.

Type: String

Required: No

spec

The new virtual gateway specification to apply. This overwrites the existing data.

Type: [VirtualGatewaySpec](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "meshName": "string",
  "metadata": {
    "arn": "string",
    "createdAt": number,
    "lastUpdatedAt": number,
    "meshOwner": "string",
    "resourceOwner": "string",
    "uid": "string",
```

```

    "version": number
  },
  "spec": {
    "backendDefaults": {
      "clientPolicy": {
        "tls": {
          "certificate": { ... },
          "enforce": boolean,
          "ports": [ number ],
          "validation": {
            "subjectAlternativeNames": {
              "match": {
                "exact": [ "string" ]
              }
            },
            "trust": { ... }
          }
        }
      }
    }
  },
  "listeners": [
    {
      "connectionPool": { ... },
      "healthCheck": {
        "healthyThreshold": number,
        "intervalMillis": number,
        "path": "string",
        "port": number,
        "protocol": "string",
        "timeoutMillis": number,
        "unhealthyThreshold": number
      },
      "portMapping": {
        "port": number,
        "protocol": "string"
      },
      "tls": {
        "certificate": { ... },
        "mode": "string",
        "validation": {
          "subjectAlternativeNames": {
            "match": {
              "exact": [ "string" ]
            }
          }
        }
      }
    }
  ]
}

```

```
    },
    "trust": { ... }
  }
},
"logging": {
  "accessLog": { ... }
},
"status": {
  "status": "string"
},
"virtualGatewayName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

meshName

The name of the service mesh that the virtual gateway resides in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

metadata

An object that represents metadata for a resource.

Type: [ResourceMetadata](#) object

spec

The specifications of the virtual gateway.

Type: [VirtualGatewaySpec](#) object

status

The current status of the virtual gateway.

Type: [VirtualGatewayStatus](#) object

[virtualGatewayName](#)

The name of the virtual gateway.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ConflictException

The request contains a client token that was used for a previous update resource call with different specifications. Try the request again with a new client token.

HTTP Status Code: 409

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

LimitExceededException

You have exceeded a service limit for your account. For more information, see [Service Limits](#) in the *AWS App Mesh User Guide*.

HTTP Status Code: 400

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You need to learn how to sign HTTP requests only if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

The following example updates a virtual gateway named myVirtualGateway in the apps service mesh.

Sample Request

```
PUT /v20190125/meshes/apps/virtualGateways/myVirtualGateway HTTP/1.1
Host: appmesh.us-west-2.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.16.298 Python/3.6.0 Windows/10 botocore/1.13.34
X-Amz-Date: 20200706T151140Z
Authorization: AUTHPARAMS

{
```



```
"spec": {
  "listeners": [{
    "portMapping": {
      "port": 8080,
      "protocol": "http2"
    }
  }]
},
"clientToken": "1aa1111a-1111-1111-111a-a1a1a1aa111a"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-requestid: 009bf6b9-c86a-40ba-b6a4-45cb41badc77
content-type: application/json
content-length: 515
date: Mon, 06 Jul 2020 15:11:40 GMT
x-envoy-upstream-service-time: 34
server: envoy
Connection: keep-alive

{
  "meshName": "apps",
  "metadata": {
    "arn": "arn:aws:appmesh:us-west-2:123456789012:mesh/apps/virtualGateway/myVirtualGateway",
    "createdAt": 1.594048239495E9,
    "lastUpdatedAt": 1.594048300694E9,
    "meshOwner": "123456789012",
    "resourceOwner": "123456789012",
    "uid": "ff111ff2-33ff-4fff-ffff-111f111f111f",
    "version": 2
  },
  "spec": {
    "backendDefaults": null,
    "listeners": [{
      "healthCheck": null,
      "portMapping": {
        "port": 8080,
        "protocol": "http2"
      }
    }],
    "tls": null
  }
}
```

```
    }],  
    "logging": null  
  },  
  "status": {  
    "status": "ACTIVE"  
  },  
  "virtualGatewayName": "myVirtualGateway"  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateVirtualNode

Updates an existing virtual node in a specified service mesh.

Request Syntax

```
PUT /v20190125/meshes/meshName/virtualNodes/virtualNodeName?meshOwner=meshOwner
HTTP/1.1
```

Content-type: application/json

```
{
  "clientToken": "string",
  "spec": {
    "backendDefaults": {
      "clientPolicy": {
        "tls": {
          "certificate": { ... },
          "enforce": boolean,
          "ports": [ number ],
          "validation": {
            "subjectAlternativeNames": {
              "match": {
                "exact": [ "string" ]
              }
            },
            "trust": { ... }
          }
        }
      }
    },
    "backends": [
      { ... }
    ],
    "listeners": [
      {
        "connectionPool": { ... },
        "healthCheck": {
          "healthyThreshold": number,
          "intervalMillis": number,
          "path": "string",
          "port": number,
          "protocol": "string",
          "timeoutMillis": number,

```

```

        "unhealthyThreshold": number
    },
    "outlierDetection": {
        "baseEjectionDuration": {
            "unit": "string",
            "value": number
        },
        "interval": {
            "unit": "string",
            "value": number
        },
        "maxEjectionPercent": number,
        "maxServerErrors": number
    },
    "portMapping": {
        "port": number,
        "protocol": "string"
    },
    "timeout": { ... },
    "tls": {
        "certificate": { ... },
        "mode": "string",
        "validation": {
            "subjectAlternativeNames": {
                "match": {
                    "exact": [ "string" ]
                }
            },
            "trust": { ... }
        }
    }
}
],
"logging": {
    "accessLog": { ... }
},
"serviceDiscovery": { ... }
}
}

```

URI Request Parameters

The request uses the following URI parameters.

meshName

The name of the service mesh that the virtual node resides in.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then it's the ID of the account that shared the mesh with your account. For more information about mesh sharing, see [Working with shared meshes](#).

Length Constraints: Fixed length of 12.

virtualNodeName

The name of the virtual node to update.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

Request Body

The request accepts the following data in JSON format.

clientToken

Unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Up to 36 letters, numbers, hyphens, and underscores are allowed.

Type: String

Required: No

spec

The new virtual node specification to apply. This overwrites the existing data.

Type: [VirtualNodeSpec](#) object

Required: Yes

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "meshName": "string",
  "metadata": {
    "arn": "string",
    "createdAt": number,
    "lastUpdatedAt": number,
    "meshOwner": "string",
    "resourceOwner": "string",
    "uid": "string",
    "version": number
  },
  "spec": {
    "backendDefaults": {
      "clientPolicy": {
        "tls": {
          "certificate": { ... },
          "enforce": boolean,
          "ports": [ number ],
          "validation": {
            "subjectAlternativeNames": {
              "match": {
                "exact": [ "string" ]
              }
            },
            "trust": { ... }
          }
        }
      }
    },
    "backends": [
      { ... }
    ],
    "listeners": [
      {
        "connectionPool": { ... },
        "healthCheck": {
          "healthyThreshold": number,
          "intervalMillis": number,
```

```

        "path": "string",
        "port": number,
        "protocol": "string",
        "timeoutMillis": number,
        "unhealthyThreshold": number
    },
    "outlierDetection": {
        "baseEjectionDuration": {
            "unit": "string",
            "value": number
        },
        "interval": {
            "unit": "string",
            "value": number
        },
        "maxEjectionPercent": number,
        "maxServerErrors": number
    },
    "portMapping": {
        "port": number,
        "protocol": "string"
    },
    "timeout": { ... },
    "tls": {
        "certificate": { ... },
        "mode": "string",
        "validation": {
            "subjectAlternativeNames": {
                "match": {
                    "exact": [ "string" ]
                }
            },
            "trust": { ... }
        }
    }
}
],
"logging": {
    "accessLog": { ... }
},
"serviceDiscovery": { ... }
},
"status": {
    "status": "string"

```

```
  },  
  "virtualNodeName": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[meshName](#)

The name of the service mesh that the virtual node resides in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

[metadata](#)

The associated metadata for the virtual node.

Type: [ResourceMetadata](#) object

[spec](#)

The specifications of the virtual node.

Type: [VirtualNodeSpec](#) object

[status](#)

The current status for the virtual node.

Type: [VirtualNodeStatus](#) object

[virtualNodeName](#)

The name of the virtual node.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ConflictException

The request contains a client token that was used for a previous update resource call with different specifications. Try the request again with a new client token.

HTTP Status Code: 409

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

LimitExceededException

You have exceeded a service limit for your account. For more information, see [Service Limits](#) in the *AWS App Mesh User Guide*.

HTTP Status Code: 400

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You need to learn how to sign HTTP requests only if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

The following example updates a virtual node named `colorteller-vn` in the `ecs-mesh` service mesh.

Sample Request

```
PUT /v20190125/meshes/ecs-mesh/virtualNodes/colorteller-vn HTTP/1.1
Host: appmesh.us-east-1.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.16.56 Python/3.7.0 Darwin/17.7.0 botocore/1.12.46
X-Amz-Date: 20190228T002242Z
Authorization: AUTHPARAMS

{
  "spec": {
    "backends": [],
    "listeners": [
      {
        "healthCheck": {
          "healthyThreshold": 2,
          "intervalMillis": 5000,
```

```
        "path": "/ping",
        "port": 9080,
        "protocol": "http",
        "timeoutMillis": 2000,
        "unhealthyThreshold": 2
    },
    "portMapping": {
        "port": 9080,
        "protocol": "http"
    }
},
"serviceDiscovery": {
    "dns": {
        "hostname": "colorteller-white.default.svc.cluster.local"
    }
},
"clientToken": "xxxxxxxx-xxxx-xxxx-1111-EXAMPLE11111"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-requestid: d6dc2922-f4c0-4077-8107-db673f167a12
content-type: application/json
content-length: 660
date: Thu, 28 Feb 2019 00:22:42 GMT
x-envoy-upstream-service-time: 88
server: envoy
Connection: keep-alive

{
  "meshName": "ecs-mesh",
  "metadata": {
    "arn": "arn:aws:appmesh:us-east-1:123456789012:mesh/ecs-mesh/virtualNode/colorteller-vn",
    "createdAt": 1.551311799179E9,
    "lastUpdatedAt": 1.551313363236E9,
    "uid": "0999e53a-8e0e-4c4c-8764-ae8ebecc296d",
    "version": 2
  },
  "spec": {
```

```
"backends": [],
"listeners": [{
  "healthCheck": {
    "healthyThreshold": 2,
    "intervalMillis": 5000,
    "path": "/ping",
    "port": 9080,
    "protocol": "http",
    "timeoutMillis": 2000,
    "unhealthyThreshold": 2
  },
  "portMapping": {
    "port": 9080,
    "protocol": "http"
  }
}],
"logging": null,
"serviceDiscovery": {
  "dns": {
    "hostname": "colorteller-white.default.svc.cluster.local"
  }
},
"status": {
  "status": "ACTIVE"
},
"virtualNodeName": "colorteller-vn"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateVirtualRouter

Updates an existing virtual router in a specified service mesh.

Request Syntax

```
PUT /v20190125/meshes/meshName/virtualRouters/virtualRouterName?meshOwner=meshOwner
HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "spec": {
    "listeners": [
      {
        "portMapping": {
          "port": number,
          "protocol": "string"
        }
      }
    ]
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

meshName

The name of the service mesh that the virtual router resides in.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then it's the ID of the account that shared the mesh with your account. For more information about mesh sharing, see [Working with shared meshes](#).

Length Constraints: Fixed length of 12.

virtualRouterName

The name of the virtual router to update.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

Request Body

The request accepts the following data in JSON format.

clientToken

Unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Up to 36 letters, numbers, hyphens, and underscores are allowed.

Type: String

Required: No

spec

The new virtual router specification to apply. This overwrites the existing data.

Type: [VirtualRouterSpec](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "meshName": "string",
  "metadata": {
    "arn": "string",
    "createdAt": number,
    "lastUpdatedAt": number,
    "meshOwner": "string",
    "resourceOwner": "string",
```

```
    "uid": "string",
    "version": number
  },
  "spec": {
    "listeners": [
      {
        "portMapping": {
          "port": number,
          "protocol": "string"
        }
      }
    ]
  },
  "status": {
    "status": "string"
  },
  "virtualRouterName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

meshName

The name of the service mesh that the virtual router resides in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

metadata

The associated metadata for the virtual router.

Type: [ResourceMetadata](#) object

spec

The specifications of the virtual router.

Type: [VirtualRouterSpec](#) object

status

The current status of the virtual router.

Type: [VirtualRouterStatus](#) object

virtualRouterName

The name of the virtual router.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ConflictException

The request contains a client token that was used for a previous update resource call with different specifications. Try the request again with a new client token.

HTTP Status Code: 409

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

LimitExceededException

You have exceeded a service limit for your account. For more information, see [Service Limits](#) in the *AWS App Mesh User Guide*.

HTTP Status Code: 400

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You need to learn how to sign HTTP requests only if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

The following example updates a virtual router named `colorteller-vr` in the `ecs-mesh` service mesh.

Sample Request

```
PUT /v20190125/meshes/ecs-mesh/virtualRouters/colorteller-vr HTTP/1.1
Host: appmesh.us-east-1.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.16.56 Python/3.7.0 Darwin/17.7.0 botocore/1.12.46
X-Amz-Date: 20190228T002506Z
```

Authorization: AUTHPARAMS

```
{
  "spec": {},
  "clientToken": "6029e873-0ef2-41b9-957e-2742048c92c3"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-requestid: fba0cb49-d242-46e5-aacd-c4a0fad60413
content-type: application/json
content-length: 336
date: Thu, 28 Feb 2019 00:25:06 GMT
x-envoy-upstream-service-time: 70
server: envoy
Connection: keep-alive

{
  "meshName": "ecs-mesh",
  "metadata": {
    "arn": "arn:aws:appmesh:us-east-1:123456789012:mesh/ecs-mesh/virtualRouter/colorteller-vr",
    "createdAt": 1551311805.476,
    "lastUpdatedAt": 1551313507.39,
    "uid": "79628d34-8c17-42ba-83a5-8a42fd17ec5a",
    "version": 2
  },
  "spec": {
    "listeners": [
      {
        "portMapping": {
          "port": 9080,
          "protocol": "http"
        }
      }
    ]
  },
  "status": {
    "status": "ACTIVE"
  },
  "virtualRouterName": "colorteller-vr"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateVirtualService

Updates an existing virtual service in a specified service mesh.

Request Syntax

```
PUT /v20190125/meshes/meshName/virtualServices/virtualServiceName?meshOwner=meshOwner
HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "spec": {
    "provider": { ... }
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

meshName

The name of the service mesh that the virtual service resides in.

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then it's the ID of the account that shared the mesh with your account. For more information about mesh sharing, see [Working with shared meshes](#).

Length Constraints: Fixed length of 12.

virtualServiceName

The name of the virtual service to update.

Required: Yes

Request Body

The request accepts the following data in JSON format.

clientToken

Unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Up to 36 letters, numbers, hyphens, and underscores are allowed.

Type: String

Required: No

spec

The new virtual service specification to apply. This overwrites the existing data.

Type: [VirtualServiceSpec](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "meshName": "string",
  "metadata": {
    "arn": "string",
    "createdAt": number,
    "lastUpdatedAt": number,
    "meshOwner": "string",
    "resourceOwner": "string",
    "uid": "string",
    "version": number
  },
  "spec": {
    "provider": { ... }
  },
  "status": {
    "status": "string"
  },
}
```

```
"virtualServiceName": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[meshName](#)

The name of the service mesh that the virtual service resides in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

[metadata](#)

An object that represents metadata for a resource.

Type: [ResourceMetadata](#) object

[spec](#)

The specifications of the virtual service.

Type: [VirtualServiceSpec](#) object

[status](#)

The current status of the virtual service.

Type: [VirtualServiceStatus](#) object

[virtualServiceName](#)

The name of the virtual service.

Type: String

Errors

BadRequestException

The request syntax was malformed. Check your request syntax and try again.

HTTP Status Code: 400

ConflictException

The request contains a client token that was used for a previous update resource call with different specifications. Try the request again with a new client token.

HTTP Status Code: 409

ForbiddenException

You don't have permissions to perform this action.

HTTP Status Code: 403

InternalServerErrorException

The request processing has failed because of an unknown error, exception, or failure.

HTTP Status Code: 500

LimitExceededException

You have exceeded a service limit for your account. For more information, see [Service Limits](#) in the *AWS App Mesh User Guide*.

HTTP Status Code: 400

NotFoundException

The specified resource doesn't exist. Check your request syntax and try again.

HTTP Status Code: 404

ServiceUnavailableException

The request has failed due to a temporary failure of the service.

HTTP Status Code: 503

TooManyRequestsException

The maximum request rate permitted by the App Mesh APIs has been exceeded for your account. For best results, use an increasing or variable sleep interval between requests.

HTTP Status Code: 429

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You need to learn how to sign HTTP requests only if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example updates a virtual service named `colorgateway.default.svc.cluster.local` in the `ecs-mesh` service mesh.

Sample Request

```
PUT /v20190125/meshes/ecs-mesh/virtualServices/colorgateway.default.svc.cluster.local
HTTP/1.1
Host: appmesh.us-east-1.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/1.16.56 Python/3.7.0 Darwin/17.7.0 botocore/1.12.46
X-Amz-Date: 20190228T002829Z
Authorization: AUTHPARAMS

{
  "spec": {
    "provider": {
      "virtualNode": {
        "virtualNodeName": "colorgateway-vn"
      }
    }
  },
  "clientToken": "c207a9a1-5828-4d73-9e8e-1d3b9350b2ac"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-requestid: 60d5fb65-ac74-4523-a1df-9e56da84fa84
```

```
content-type: application/json
content-length: 456
date: Thu, 28 Feb 2019 00:28:29 GMT
x-envoy-upstream-service-time: 88
server: envoy
Connection: keep-alive

{
  "meshName": "ecs-mesh",
  "metadata": {
    "arn": "arn:aws:appmesh:us-east-1:123456789012:mesh/ecs-mesh/virtualService/colorgateway.default.svc.cluster.local",
    "createdAt": 1.551311807444E9,
    "lastUpdatedAt": 1.551313709898E9,
    "uid": "dd06064b-e542-40a9-bbc7-e381a47ea0e0",
    "version": 2
  },
  "spec": {
    "provider": {
      "virtualNode": {
        "virtualNodeName": "colorgateway-vn"
      },
      "virtualRouter": null
    }
  },
  "status": {
    "status": "ACTIVE"
  },
  "virtualServiceName": "colorgateway.default.svc.cluster.local"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface V2](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The AWS App Mesh API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AccessLog](#)
- [AwsCloudMapInstanceAttribute](#)
- [AwsCloudMapServiceDiscovery](#)
- [Backend](#)
- [BackendDefaults](#)
- [ClientPolicy](#)
- [ClientPolicyTls](#)
- [ClientTlsCertificate](#)
- [DnsServiceDiscovery](#)
- [Duration](#)
- [EgressFilter](#)
- [FileAccessLog](#)
- [GatewayRouteData](#)
- [GatewayRouteHostnameMatch](#)
- [GatewayRouteHostnameRewrite](#)
- [GatewayRouteRef](#)
- [GatewayRouteSpec](#)
- [GatewayRouteStatus](#)
- [GatewayRouteTarget](#)
- [GatewayRouteVirtualService](#)

- [GrpcGatewayRoute](#)
- [GrpcGatewayRouteAction](#)
- [GrpcGatewayRouteMatch](#)
- [GrpcGatewayRouteMetadata](#)
- [GrpcGatewayRouteRewrite](#)
- [GrpcMetadataMatchMethod](#)
- [GrpcRetryPolicy](#)
- [GrpcRoute](#)
- [GrpcRouteAction](#)
- [GrpcRouteMatch](#)
- [GrpcRouteMetadata](#)
- [GrpcRouteMetadataMatchMethod](#)
- [GrpcTimeout](#)
- [HeaderMatchMethod](#)
- [HealthCheckPolicy](#)
- [HttpGatewayRoute](#)
- [HttpGatewayRouteAction](#)
- [HttpGatewayRouteHeader](#)
- [HttpGatewayRouteMatch](#)
- [HttpGatewayRoutePathRewrite](#)
- [HttpGatewayRoutePrefixRewrite](#)
- [HttpGatewayRouteRewrite](#)
- [HttpPathMatch](#)
- [HttpQueryParameter](#)
- [HttpRetryPolicy](#)
- [HttpRoute](#)
- [HttpRouteAction](#)
- [HttpRouteHeader](#)
- [HttpRouteMatch](#)
- [HttpTimeout](#)

- [JsonFormatRef](#)
- [Listener](#)
- [ListenerTimeout](#)
- [ListenerTls](#)
- [ListenerTlsAcmCertificate](#)
- [ListenerTlsCertificate](#)
- [ListenerTlsFileCertificate](#)
- [ListenerTlsSdsCertificate](#)
- [ListenerTlsValidationContext](#)
- [ListenerTlsValidationContextTrust](#)
- [Logging](#)
- [LoggingFormat](#)
- [MatchRange](#)
- [MeshData](#)
- [MeshRef](#)
- [MeshServiceDiscovery](#)
- [MeshSpec](#)
- [MeshStatus](#)
- [OutlierDetection](#)
- [PortMapping](#)
- [QueryParameterMatch](#)
- [ResourceMetadata](#)
- [RouteData](#)
- [RouteRef](#)
- [RouteSpec](#)
- [RouteStatus](#)
- [ServiceDiscovery](#)
- [SubjectAlternativeNameMatchers](#)
- [SubjectAlternativeNames](#)
- [TagRef](#)

- [TcpRoute](#)
- [TcpRouteAction](#)
- [TcpRouteMatch](#)
- [TcpTimeout](#)
- [TlsValidationContext](#)
- [TlsValidationContextAcmTrust](#)
- [TlsValidationContextFileTrust](#)
- [TlsValidationContextSdsTrust](#)
- [TlsValidationContextTrust](#)
- [VirtualGatewayAccessLog](#)
- [VirtualGatewayBackendDefaults](#)
- [VirtualGatewayClientPolicy](#)
- [VirtualGatewayClientPolicyTls](#)
- [VirtualGatewayClientTlsCertificate](#)
- [VirtualGatewayConnectionPool](#)
- [VirtualGatewayData](#)
- [VirtualGatewayFileAccessLog](#)
- [VirtualGatewayGrpcConnectionPool](#)
- [VirtualGatewayHealthCheckPolicy](#)
- [VirtualGatewayHttp2ConnectionPool](#)
- [VirtualGatewayHttpConnectionPool](#)
- [VirtualGatewayListener](#)
- [VirtualGatewayListenerTls](#)
- [VirtualGatewayListenerTlsAcmCertificate](#)
- [VirtualGatewayListenerTlsCertificate](#)
- [VirtualGatewayListenerTlsFileCertificate](#)
- [VirtualGatewayListenerTlsSdsCertificate](#)
- [VirtualGatewayListenerTlsValidationContext](#)
- [VirtualGatewayListenerTlsValidationContextTrust](#)
- [VirtualGatewayLogging](#)

- [VirtualGatewayPortMapping](#)
- [VirtualGatewayRef](#)
- [VirtualGatewaySpec](#)
- [VirtualGatewayStatus](#)
- [VirtualGatewayTlsValidationContext](#)
- [VirtualGatewayTlsValidationContextAcmTrust](#)
- [VirtualGatewayTlsValidationContextFileTrust](#)
- [VirtualGatewayTlsValidationContextSdsTrust](#)
- [VirtualGatewayTlsValidationContextTrust](#)
- [VirtualNodeConnectionPool](#)
- [VirtualNodeData](#)
- [VirtualNodeGrpcConnectionPool](#)
- [VirtualNodeHttp2ConnectionPool](#)
- [VirtualNodeHttpConnectionPool](#)
- [VirtualNodeRef](#)
- [VirtualNodeServiceProvider](#)
- [VirtualNodeSpec](#)
- [VirtualNodeStatus](#)
- [VirtualNodeTcpConnectionPool](#)
- [VirtualRouterData](#)
- [VirtualRouterListener](#)
- [VirtualRouterRef](#)
- [VirtualRouterServiceProvider](#)
- [VirtualRouterSpec](#)
- [VirtualRouterStatus](#)
- [VirtualServiceBackend](#)
- [VirtualServiceData](#)
- [VirtualServiceProvider](#)
- [VirtualServiceRef](#)
- [VirtualServiceSpec](#)

- [VirtualServiceStatus](#)
- [WeightedTarget](#)

AccessLog

An object that represents the access logging information for a virtual node.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

file

The file object to send virtual node access logs to.

Type: [FileAccessLog](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AwsCloudMapInstanceAttribute

An object that represents the AWS Cloud Map attribute information for your virtual node.

Note

AWS Cloud Map is not available in the eu-south-1 Region.

Contents

key

The name of an AWS Cloud Map service instance attribute key. Any AWS Cloud Map service instance that contains the specified key and value is returned.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `[a-zA-Z0-9!-~]+`

Required: Yes

value

The value of an AWS Cloud Map service instance attribute key. Any AWS Cloud Map service instance that contains the specified key and value is returned.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `([a-zA-Z0-9!-~][a-zA-Z0-9!-~]*){0,1}[a-zA-Z0-9!-~]{0,1}`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AwsCloudMapServiceDiscovery

An object that represents the AWS Cloud Map service discovery information for your virtual node.

Note

AWS Cloud Map is not available in the eu-south-1 Region.

Contents

namespaceName

The HTTP name of the AWS Cloud Map namespace to use.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

serviceName

The name of the AWS Cloud Map service to use.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

attributes

A string map that contains attributes with values that you can use to filter instances by any custom attribute that you specified when you registered the instance. Only instances that match all of the specified key/value pairs will be returned.

Type: Array of [AwsCloudMapInstanceAttribute](#) objects

Required: No

ipPreference

The preferred IP version that this virtual node uses. Setting the IP preference on the virtual node only overrides the IP preference set for the mesh on this specific node.

Type: String

Valid Values: IPv6_PREFERRED | IPv4_PREFERRED | IPv4_ONLY | IPv6_ONLY

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Backend

An object that represents the backends that a virtual node is expected to send outbound traffic to.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

virtualService

Specifies a virtual service to use as a backend.

Type: [VirtualServiceBackend](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BackendDefaults

An object that represents the default properties for a backend.

Contents

clientPolicy

A reference to an object that represents a client policy.

Type: [ClientPolicy](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ClientPolicy

An object that represents a client policy.

Contents

tls

A reference to an object that represents a Transport Layer Security (TLS) client policy.

Type: [ClientPolicyTls](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ClientPolicyTls

A reference to an object that represents a Transport Layer Security (TLS) client policy.

Contents

validation

A reference to an object that represents a TLS validation context.

Type: [TlsValidationContext](#) object

Required: Yes

certificate

A reference to an object that represents a client's TLS certificate.

Type: [ClientTlsCertificate](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

enforce

Whether the policy is enforced. The default is `True`, if a value isn't specified.

Type: Boolean

Required: No

ports

One or more ports that the policy is enforced for.

Type: Array of integers

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ClientTlsCertificate

An object that represents the client's certificate.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

file

An object that represents a local file certificate. The certificate must meet specific requirements and you must have proxy authorization enabled. For more information, see [Transport Layer Security \(TLS\)](#).

Type: [ListenerTlsFileCertificate](#) object

Required: No

sds

A reference to an object that represents a client's TLS Secret Discovery Service certificate.

Type: [ListenerTlsSdsCertificate](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DnsServiceDiscovery

An object that represents the DNS service discovery information for your virtual node.

Contents

hostname

Specifies the DNS service discovery hostname for the virtual node.

Type: String

Required: Yes

ipPreference

The preferred IP version that this virtual node uses. Setting the IP preference on the virtual node only overrides the IP preference set for the mesh on this specific node.

Type: String

Valid Values: IPv6_PREFERRED | IPv4_PREFERRED | IPv4_ONLY | IPv6_ONLY

Required: No

responseType

Specifies the DNS response type for the virtual node.

Type: String

Valid Values: LOADBALANCER | ENDPOINTS

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

Duration

An object that represents a duration of time.

Contents

unit

A unit of time.

Type: String

Valid Values: s | ms

Required: No

value

A number of time units.

Type: Long

Valid Range: Minimum value of 0.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EgressFilter

An object that represents the egress filter rules for a service mesh.

Contents

type

The egress filter type. By default, the type is `DROP_ALL`, which allows egress only from virtual nodes to other defined resources in the service mesh (and any traffic to `*.amazonaws.com` for AWS API calls). You can set the egress filter type to `ALLOW_ALL` to allow egress to any endpoint inside or outside of the service mesh.

Note

If you specify any backends on a virtual node when using `ALLOW_ALL`, you must specify all egress for that virtual node as backends. Otherwise, `ALLOW_ALL` will no longer work for that virtual node.

Type: String

Valid Values: `ALLOW_ALL` | `DROP_ALL`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FileAccessLog

An object that represents an access log file.

Contents

path

The file path to write access logs to. You can use `/dev/stdout` to send access logs to standard out and configure your Envoy container to use a log driver, such as `awslogs`, to export the access logs to a log storage service such as Amazon CloudWatch Logs. You can also specify a path in the Envoy container's file system to write the files to disk.

Note

The Envoy process must have write permissions to the path that you specify here. Otherwise, Envoy fails to bootstrap properly.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

format

The specified format for the logs. The format is either `json_format` or `text_format`.

Type: [LoggingFormat](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GatewayRouteData

An object that represents a gateway route returned by a describe operation.

Contents

gatewayRouteName

The name of the gateway route.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshName

The name of the service mesh that the resource resides in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

metadata

An object that represents metadata for a resource.

Type: [ResourceMetadata](#) object

Required: Yes

spec

The specifications of the gateway route.

Type: [GatewayRouteSpec](#) object

Required: Yes

status

The status of the gateway route.

Type: [GatewayRouteStatus](#) object

Required: Yes

virtualGatewayName

The virtual gateway that the gateway route is associated with.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GatewayRouteHostnameMatch

An object representing the gateway route host name to match.

Contents

exact

The exact host name to match on.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 253.

Required: No

suffix

The specified ending characters of the host name to match on.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 253.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GatewayRouteHostnameRewrite

An object representing the gateway route host name to rewrite.

Contents

defaultTargetHostname

The default target host name to write to.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GatewayRouteRef

An object that represents a gateway route returned by a list operation.

Contents

arn

The full Amazon Resource Name (ARN) for the gateway route.

Type: String

Required: Yes

createdAt

The Unix epoch timestamp in seconds for when the resource was created.

Type: Timestamp

Required: Yes

gatewayRouteName

The name of the gateway route.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

lastUpdatedAt

The Unix epoch timestamp in seconds for when the resource was last updated.

Type: Timestamp

Required: Yes

meshName

The name of the service mesh that the resource resides in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then it's the ID of the account that shared the mesh with your account. For more information about mesh sharing, see [Working with shared meshes](#).

Type: String

Length Constraints: Fixed length of 12.

Required: Yes

resourceOwner

The AWS IAM account ID of the resource owner. If the account ID is not your own, then it's the ID of the mesh owner or of another account that the mesh is shared with. For more information about mesh sharing, see [Working with shared meshes](#).

Type: String

Length Constraints: Fixed length of 12.

Required: Yes

version

The version of the resource. Resources are created at version 1, and this version is incremented each time that they're updated.

Type: Long

Required: Yes

virtualGatewayName

The virtual gateway that the gateway route is associated with.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GatewayRouteSpec

An object that represents a gateway route specification. Specify one gateway route type.

Contents

grpcRoute

An object that represents the specification of a gRPC gateway route.

Type: [GrpcGatewayRoute](#) object

Required: No

http2Route

An object that represents the specification of an HTTP/2 gateway route.

Type: [HttpGatewayRoute](#) object

Required: No

httpRoute

An object that represents the specification of an HTTP gateway route.

Type: [HttpGatewayRoute](#) object

Required: No

priority

The ordering of the gateway routes spec.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 1000.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GatewayRouteStatus

An object that represents the current status of a gateway route.

Contents

status

The current status for the gateway route.

Type: String

Valid Values: ACTIVE | INACTIVE | DELETED

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GatewayRouteTarget

An object that represents a gateway route target.

Contents

virtualService

An object that represents a virtual service gateway route target.

Type: [GatewayRouteVirtualService](#) object

Required: Yes

port

The port number of the gateway route target.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GatewayRouteVirtualService

An object that represents the virtual service that traffic is routed to.

Contents

virtualServiceName

The name of the virtual service that traffic is routed to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GrpcGatewayRoute

An object that represents a gRPC gateway route.

Contents

action

An object that represents the action to take if a match is determined.

Type: [GrpcGatewayRouteAction](#) object

Required: Yes

match

An object that represents the criteria for determining a request match.

Type: [GrpcGatewayRouteMatch](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GrpcGatewayRouteAction

An object that represents the action to take if a match is determined.

Contents

target

An object that represents the target that traffic is routed to when a request matches the gateway route.

Type: [GatewayRouteTarget](#) object

Required: Yes

rewrite

The gateway route action to rewrite.

Type: [GrpcGatewayRouteRewrite](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GrpcGatewayRouteMatch

An object that represents the criteria for determining a request match.

Contents

hostname

The gateway route host name to be matched on.

Type: [GatewayRouteHostnameMatch](#) object

Required: No

metadata

The gateway route metadata to be matched on.

Type: Array of [GrpcGatewayRouteMetadadata](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: No

port

The gateway route port to be matched on.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: No

serviceName

The fully qualified domain name for the service to match from the request.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GrpcGatewayRouteMetadata

An object representing the metadata of the gateway route.

Contents

name

A name for the gateway route metadata.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: Yes

invert

Specify `True` to match anything except the match criteria. The default value is `False`.

Type: Boolean

Required: No

match

The criteria for determining a metadata match.

Type: [GrpcMetadataMatchMethod](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GrpcGatewayRouteRewrite

An object that represents the gateway route to rewrite.

Contents

hostname

The host name of the gateway route to rewrite.

Type: [GatewayRouteHostnameRewrite](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GrpcMetadataMatchMethod

An object representing the method header to be matched.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

exact

The exact method header to be matched on.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

prefix

The specified beginning characters of the method header to be matched on.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

range

An object that represents the range of values to match on. The first character of the range is included in the range, though the last character is not. For example, if the range specified were 1-100, only values 1-99 would be matched.

Type: [MatchRange](#) object

Required: No

regex

The regex used to match the method header.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

suffix

The specified ending characters of the method header to match on.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GrpcRetryPolicy

An object that represents a retry policy. Specify at least one value for at least one of the types of `RetryEvents`, a value for `maxRetries`, and a value for `perRetryTimeout`. Both `server-error` and `gateway-error` under `httpRetryEvents` include the Envoy reset policy. For more information on the reset policy, see the [Envoy documentation](#).

Contents

maxRetries

The maximum number of retry attempts.

Type: Long

Valid Range: Minimum value of 0.

Required: Yes

perRetryTimeout

The timeout for each retry attempt.

Type: [Duration](#) object

Required: Yes

grpcRetryEvents

Specify at least one of the valid values.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Valid Values: `cancelled` | `deadline-exceeded` | `internal` | `resource-exhausted` | `unavailable`

Required: No

httpRetryEvents

Specify at least one of the following values.

- **server-error** – HTTP status codes 500, 501, 502, 503, 504, 505, 506, 507, 508, 510, and 511

- **gateway-error** – HTTP status codes 502, 503, and 504
- **client-error** – HTTP status code 409
- **stream-error** – Retry on refused stream

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Length Constraints: Minimum length of 1. Maximum length of 25.

Required: No

tcpRetryEvents

Specify a valid value. The event occurs before any processing of a request has started and is encountered when the upstream is temporarily or permanently unavailable.

Type: Array of strings

Array Members: Fixed number of 1 item.

Valid Values: `connection-error`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GrpcRoute

An object that represents a gRPC route type.

Contents

action

An object that represents the action to take if a match is determined.

Type: [GrpcRouteAction](#) object

Required: Yes

match

An object that represents the criteria for determining a request match.

Type: [GrpcRouteMatch](#) object

Required: Yes

retryPolicy

An object that represents a retry policy.

Type: [GrpcRetryPolicy](#) object

Required: No

timeout

An object that represents types of timeouts.

Type: [GrpcTimeout](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GrpcRouteAction

An object that represents the action to take if a match is determined.

Contents

weightedTargets

An object that represents the targets that traffic is routed to when a request matches the route.

Type: Array of [WeightedTarget](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GrpcRouteMatch

An object that represents the criteria for determining a request match.

Contents

metadata

An object that represents the data to match from the request.

Type: Array of [GrpcRouteMetadata](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: No

methodName

The method name to match from the request. If you specify a name, you must also specify a `serviceName`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

port

The port number to match on.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: No

serviceName

The fully qualified domain name for the service to match from the request.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GrpcRouteMetadata

An object that represents the match metadata for the route.

Contents

name

The name of the route.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: Yes

invert

Specify `True` to match anything except the match criteria. The default value is `False`.

Type: Boolean

Required: No

match

An object that represents the data to match from the request.

Type: [GrpcRouteMetadataMatchMethod](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GrpcRouteMetadataMatchMethod

An object that represents the match method. Specify one of the match values.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

exact

The value sent by the client must match the specified value exactly.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

prefix

The value sent by the client must begin with the specified characters.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

range

An object that represents the range of values to match on.

Type: [MatchRange](#) object

Required: No

regex

The value sent by the client must include the specified characters.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

suffix

The value sent by the client must end with the specified characters.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GrpcTimeout

An object that represents types of timeouts.

Contents

idle

An object that represents an idle timeout. An idle timeout bounds the amount of time that a connection may be idle. The default value is none.

Type: [Duration](#) object

Required: No

perRequest

An object that represents a per request timeout. The default value is 15 seconds. If you set a higher timeout, then make sure that the higher value is set for each App Mesh resource in a conversation. For example, if a virtual node backend uses a virtual router provider to route to another virtual node, then the timeout should be greater than 15 seconds for the source and destination virtual node and the route.

Type: [Duration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

HeaderMatchMethod

An object that represents the method and value to match with the header value sent in a request. Specify one match method.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

exact

The value sent by the client must match the specified value exactly.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

prefix

The value sent by the client must begin with the specified characters.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

range

An object that represents the range of values to match on.

Type: [MatchRange](#) object

Required: No

regex

The value sent by the client must include the specified characters.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

suffix

The value sent by the client must end with the specified characters.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

HealthCheckPolicy

An object that represents the health check policy for a virtual node's listener.

Contents

healthyThreshold

The number of consecutive successful health checks that must occur before declaring listener healthy.

Type: Integer

Valid Range: Minimum value of 2. Maximum value of 10.

Required: Yes

intervalMillis

The time period in milliseconds between each health check execution.

Type: Long

Valid Range: Minimum value of 5000. Maximum value of 300000.

Required: Yes

protocol

The protocol for the health check request. If you specify `grpc`, then your service must conform to the [GRPC Health Checking Protocol](#).

Type: String

Valid Values: `http` | `tcp` | `http2` | `grpc`

Required: Yes

timeoutMillis

The amount of time to wait when receiving a response from the health check, in milliseconds.

Type: Long

Valid Range: Minimum value of 2000. Maximum value of 60000.

Required: Yes

unhealthyThreshold

The number of consecutive failed health checks that must occur before declaring a virtual node unhealthy.

Type: Integer

Valid Range: Minimum value of 2. Maximum value of 10.

Required: Yes

path

The destination path for the health check request. This value is only used if the specified protocol is HTTP or HTTP/2. For any other protocol, this value is ignored.

Type: String

Required: No

port

The destination port for the health check request. This port must match the port defined in the [PortMapping](#) for the listener.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

HttpGatewayRoute

An object that represents an HTTP gateway route.

Contents

action

An object that represents the action to take if a match is determined.

Type: [HttpGatewayRouteAction](#) object

Required: Yes

match

An object that represents the criteria for determining a request match.

Type: [HttpGatewayRouteMatch](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

HttpGatewayRouteAction

An object that represents the action to take if a match is determined.

Contents

target

An object that represents the target that traffic is routed to when a request matches the gateway route.

Type: [GatewayRouteTarget](#) object

Required: Yes

rewrite

The gateway route action to rewrite.

Type: [HttpGatewayRouteRewrite](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

HttpGatewayRouteHeader

An object that represents the HTTP header in the gateway route.

Contents

name

A name for the HTTP header in the gateway route that will be matched on.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: Yes

invert

Specify `True` to match anything except the match criteria. The default value is `False`.

Type: Boolean

Required: No

match

An object that represents the method and value to match with the header value sent in a request. Specify one match method.

Type: [HeaderMatchMethod](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

HttpGatewayRouteMatch

An object that represents the criteria for determining a request match.

Contents

headers

The client request headers to match on.

Type: Array of [HttpGatewayRouteHeader](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: No

hostname

The host name to match on.

Type: [GatewayRouteHostnameMatch](#) object

Required: No

method

The method to match on.

Type: String

Valid Values: GET | HEAD | POST | PUT | DELETE | CONNECT | OPTIONS | TRACE | PATCH

Required: No

path

The path to match on.

Type: [HttpPathMatch](#) object

Required: No

port

The port number to match on.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: No

prefix

Specifies the path to match requests with. This parameter must always start with `/`, which by itself matches all requests to the virtual service name. You can also match for path-based routing of requests. For example, if your virtual service name is `my-service.local` and you want the route to match requests to `my-service.local/metrics`, your prefix should be `/metrics`.

Type: String

Required: No

queryParameters

The query parameter to match on.

Type: Array of [HttpQueryParameter](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

HttpGatewayRoutePathRewrite

An object that represents the path to rewrite.

Contents

exact

The exact path to rewrite.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

HttpGatewayRoutePrefixRewrite

An object representing the beginning characters of the route to rewrite.

Contents

defaultPrefix

The default prefix used to replace the incoming route prefix when rewritten.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

value

The value used to replace the incoming route prefix when rewritten.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

HttpGatewayRouteRewrite

An object representing the gateway route to rewrite.

Contents

hostname

The host name to rewrite.

Type: [GatewayRouteHostnameRewrite](#) object

Required: No

path

The path to rewrite.

Type: [HttpGatewayRoutePathRewrite](#) object

Required: No

prefix

The specified beginning characters to rewrite.

Type: [HttpGatewayRoutePrefixRewrite](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

HttpPathMatch

An object representing the path to match in the request.

Contents

exact

The exact path to match on.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

regex

The regex used to match the path.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

HttpQueryParam

An object that represents the query parameter in the request.

Contents

name

A name for the query parameter that will be matched on.

Type: String

Required: Yes

match

The query parameter to match on.

Type: [QueryParamMatch](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

HttpRetryPolicy

An object that represents a retry policy. Specify at least one value for at least one of the types of `RetryEvents`, a value for `maxRetries`, and a value for `perRetryTimeout`. Both `server-error` and `gateway-error` under `httpRetryEvents` include the Envoy reset policy. For more information on the reset policy, see the [Envoy documentation](#).

Contents

`maxRetries`

The maximum number of retry attempts.

Type: Long

Valid Range: Minimum value of 0.

Required: Yes

`perRetryTimeout`

The timeout for each retry attempt.

Type: [Duration](#) object

Required: Yes

`httpRetryEvents`

Specify at least one of the following values.

- **server-error** – HTTP status codes 500, 501, 502, 503, 504, 505, 506, 507, 508, 510, and 511
- **gateway-error** – HTTP status codes 502, 503, and 504
- **client-error** – HTTP status code 409
- **stream-error** – Retry on refused stream

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Length Constraints: Minimum length of 1. Maximum length of 25.

Required: No

tcpRetryEvents

Specify a valid value. The event occurs before any processing of a request has started and is encountered when the upstream is temporarily or permanently unavailable.

Type: Array of strings

Array Members: Fixed number of 1 item.

Valid Values: `connection-error`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

HttpRoute

An object that represents an HTTP or HTTP/2 route type.

Contents

action

An object that represents the action to take if a match is determined.

Type: [HttpRouteAction](#) object

Required: Yes

match

An object that represents the criteria for determining a request match.

Type: [HttpRouteMatch](#) object

Required: Yes

retryPolicy

An object that represents a retry policy.

Type: [HttpRetryPolicy](#) object

Required: No

timeout

An object that represents types of timeouts.

Type: [HttpTimeout](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

HttpRouteAction

An object that represents the action to take if a match is determined.

Contents

weightedTargets

An object that represents the targets that traffic is routed to when a request matches the route.

Type: Array of [WeightedTarget](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

HttpRouteHeader

An object that represents the HTTP header in the request.

Contents

name

A name for the HTTP header in the client request that will be matched on.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: Yes

invert

Specify `True` to match anything except the match criteria. The default value is `False`.

Type: Boolean

Required: No

match

The `HeaderMatchMethod` object.

Type: [HeaderMatchMethod](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

HttpRouteMatch

An object that represents the requirements for a route to match HTTP requests for a virtual router.

Contents

headers

The client request headers to match on.

Type: Array of [HttpRouteHeader](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: No

method

The client request method to match on. Specify only one.

Type: String

Valid Values: GET | HEAD | POST | PUT | DELETE | CONNECT | OPTIONS | TRACE | PATCH

Required: No

path

The client request path to match on.

Type: [HttpPathMatch](#) object

Required: No

port

The port number to match on.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: No

prefix

Specifies the path to match requests with. This parameter must always start with `/`, which by itself matches all requests to the virtual service name. You can also match for path-based routing of requests. For example, if your virtual service name is `my-service.local` and you want the route to match requests to `my-service.local/metrics`, your prefix should be `/metrics`.

Type: String

Required: No

queryParameters

The client request query parameters to match on.

Type: Array of [HttpQueryParameter](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: No

scheme

The client request scheme to match on. Specify only one. Applicable only for HTTP2 routes.

Type: String

Valid Values: `http` | `https`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

HttpTimeout

An object that represents types of timeouts.

Contents

idle

An object that represents an idle timeout. An idle timeout bounds the amount of time that a connection may be idle. The default value is none.

Type: [Duration](#) object

Required: No

perRequest

An object that represents a per request timeout. The default value is 15 seconds. If you set a higher timeout, then make sure that the higher value is set for each App Mesh resource in a conversation. For example, if a virtual node backend uses a virtual router provider to route to another virtual node, then the timeout should be greater than 15 seconds for the source and destination virtual node and the route.

Type: [Duration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

JsonFormatRef

An object that represents the key value pairs for the JSON.

Contents

key

The specified key for the JSON.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

value

The specified value for the JSON.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Listener

An object that represents a listener for a virtual node.

Contents

portMapping

The port mapping information for the listener.

Type: [PortMapping](#) object

Required: Yes

connectionPool

The connection pool information for the listener.

Type: [VirtualNodeConnectionPool](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

healthCheck

The health check information for the listener.

Type: [HealthCheckPolicy](#) object

Required: No

outlierDetection

The outlier detection information for the listener.

Type: [OutlierDetection](#) object

Required: No

timeout

An object that represents timeouts for different protocols.

Type: [ListenerTimeout](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

tls

A reference to an object that represents the Transport Layer Security (TLS) properties for a listener.

Type: [ListenerTls](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListenerTimeout

An object that represents timeouts for different protocols.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

grpc

An object that represents types of timeouts.

Type: [GrpcTimeout](#) object

Required: No

http

An object that represents types of timeouts.

Type: [HttpTimeout](#) object

Required: No

http2

An object that represents types of timeouts.

Type: [HttpTimeout](#) object

Required: No

tcp

An object that represents types of timeouts.

Type: [TcpTimeout](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListenerTls

An object that represents the Transport Layer Security (TLS) properties for a listener.

Contents

certificate

A reference to an object that represents a listener's Transport Layer Security (TLS) certificate.

Type: [ListenerTlsCertificate](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

mode

Specify one of the following modes.

- STRICT – Listener only accepts connections with TLS enabled.
- PERMISSIVE – Listener accepts connections with or without TLS enabled.
- DISABLED – Listener only accepts connections without TLS.

Type: String

Valid Values: STRICT | PERMISSIVE | DISABLED

Required: Yes

validation

A reference to an object that represents a listener's Transport Layer Security (TLS) validation context.

Type: [ListenerTlsValidationContext](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListenerTlsAcmCertificate

An object that represents an AWS Certificate Manager certificate.

Contents

certificateArn

The Amazon Resource Name (ARN) for the certificate. The certificate must meet specific requirements and you must have proxy authorization enabled. For more information, see [Transport Layer Security \(TLS\)](#).

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListenerTlsCertificate

An object that represents a listener's Transport Layer Security (TLS) certificate.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

acm

A reference to an object that represents an AWS Certificate Manager certificate.

Type: [ListenerTlsAcmCertificate](#) object

Required: No

file

A reference to an object that represents a local file certificate.

Type: [ListenerTlsFileCertificate](#) object

Required: No

sds

A reference to an object that represents a listener's Secret Discovery Service certificate.

Type: [ListenerTlsSdsCertificate](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListenerTlsFileCertificate

An object that represents a local file certificate. The certificate must meet specific requirements and you must have proxy authorization enabled. For more information, see [Transport Layer Security \(TLS\)](#).

Contents

certificateChain

The certificate chain for the certificate.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

privateKey

The private key for a certificate stored on the file system of the virtual node that the proxy is running on.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListenerTlsSdsCertificate

An object that represents the listener's Secret Discovery Service certificate. The proxy must be configured with a local SDS provider via a Unix Domain Socket. See App Mesh [TLS documentation](#) for more info.

Contents

secretName

A reference to an object that represents the name of the secret requested from the Secret Discovery Service provider representing Transport Layer Security (TLS) materials like a certificate or certificate chain.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListenerTlsValidationContext

An object that represents a listener's Transport Layer Security (TLS) validation context.

Contents

trust

A reference to where to retrieve the trust chain when validating a peer's Transport Layer Security (TLS) certificate.

Type: [ListenerTlsValidationContextTrust](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

subjectAlternativeNames

A reference to an object that represents the SANs for a listener's Transport Layer Security (TLS) validation context.

Type: [SubjectAlternativeNames](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListenerTlsValidationContextTrust

An object that represents a listener's Transport Layer Security (TLS) validation context trust.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

file

An object that represents a Transport Layer Security (TLS) validation context trust for a local file.

Type: [TlsValidationContextFileTrust](#) object

Required: No

sds

A reference to an object that represents a listener's Transport Layer Security (TLS) Secret Discovery Service validation context trust.

Type: [TlsValidationContextSdsTrust](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Logging

An object that represents the logging information for a virtual node.

Contents

accessLog

The access log configuration for a virtual node.

Type: [AccessLog](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LoggingFormat

An object that represents the format for the logs.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

json

The logging format for JSON.

Type: Array of [JsonFormatRef](#) objects

Required: No

text

The logging format for text.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MatchRange

An object that represents the range of values to match on. The first character of the range is included in the range, though the last character is not. For example, if the range specified were 1-100, only values 1-99 would be matched.

Contents

end

The end of the range.

Type: Long

Required: Yes

start

The start of the range.

Type: Long

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MeshData

An object that represents a service mesh returned by a describe operation.

Contents

meshName

The name of the service mesh.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

metadata

The associated metadata for the service mesh.

Type: [ResourceMetadata](#) object

Required: Yes

spec

The associated specification for the service mesh.

Type: [MeshSpec](#) object

Required: Yes

status

The status of the service mesh.

Type: [MeshStatus](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MeshRef

An object that represents a service mesh returned by a list operation.

Contents

arn

The full Amazon Resource Name (ARN) of the service mesh.

Type: String

Required: Yes

createdAt

The Unix epoch timestamp in seconds for when the resource was created.

Type: Timestamp

Required: Yes

lastUpdatedAt

The Unix epoch timestamp in seconds for when the resource was last updated.

Type: Timestamp

Required: Yes

meshName

The name of the service mesh.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then it's the ID of the account that shared the mesh with your account. For more information about mesh sharing, see [Working with shared meshes](#).

Type: String

Length Constraints: Fixed length of 12.

Required: Yes

resourceOwner

The AWS IAM account ID of the resource owner. If the account ID is not your own, then it's the ID of the mesh owner or of another account that the mesh is shared with. For more information about mesh sharing, see [Working with shared meshes](#).

Type: String

Length Constraints: Fixed length of 12.

Required: Yes

version

The version of the resource. Resources are created at version 1, and this version is incremented each time that they're updated.

Type: Long

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MeshServiceDiscovery

An object that represents the service discovery information for a service mesh.

Contents

ipPreference

The IP version to use to control traffic within the mesh.

Type: String

Valid Values: IPv6_PREFERRED | IPv4_PREFERRED | IPv4_ONLY | IPv6_ONLY

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MeshSpec

An object that represents the specification of a service mesh.

Contents

egressFilter

The egress filter rules for the service mesh.

Type: [EgressFilter](#) object

Required: No

serviceDiscovery

An object that represents the service discovery information for a service mesh.

Type: [MeshServiceDiscovery](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MeshStatus

An object that represents the status of a service mesh.

Contents

status

The current mesh status.

Type: String

Valid Values: ACTIVE | INACTIVE | DELETED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OutlierDetection

An object that represents the outlier detection for a virtual node's listener.

Contents

baseEjectionDuration

The base amount of time for which a host is ejected.

Type: [Duration](#) object

Required: Yes

interval

The time interval between ejection sweep analysis.

Type: [Duration](#) object

Required: Yes

maxEjectionPercent

Maximum percentage of hosts in load balancing pool for upstream service that can be ejected. Will eject at least one host regardless of the value.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: Yes

maxServerErrors

Number of consecutive 5xx errors required for ejection.

Type: Long

Valid Range: Minimum value of 1.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PortMapping

An object that represents a port mapping.

Contents

port

The port used for the port mapping.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: Yes

protocol

The protocol used for the port mapping. Specify one protocol.

Type: String

Valid Values: `http` | `tcp` | `http2` | `grpc`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

QueryParameterMatch

An object representing the query parameter to match.

Contents

exact

The exact query parameter to match on.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceMetadata

An object that represents metadata for a resource.

Contents

arn

The full Amazon Resource Name (ARN) for the resource.

Type: String

Required: Yes

createdAt

The Unix epoch timestamp in seconds for when the resource was created.

Type: Timestamp

Required: Yes

lastUpdatedAt

The Unix epoch timestamp in seconds for when the resource was last updated.

Type: Timestamp

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then it's the ID of the account that shared the mesh with your account. For more information about mesh sharing, see [Working with shared meshes](#).

Type: String

Length Constraints: Fixed length of 12.

Required: Yes

resourceOwner

The AWS IAM account ID of the resource owner. If the account ID is not your own, then it's the ID of the mesh owner or of another account that the mesh is shared with. For more information about mesh sharing, see [Working with shared meshes](#).

Type: String

Length Constraints: Fixed length of 12.

Required: Yes

uid

The unique identifier for the resource.

Type: String

Required: Yes

version

The version of the resource. Resources are created at version 1, and this version is incremented each time that they're updated.

Type: Long

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RouteData

An object that represents a route returned by a describe operation.

Contents

meshName

The name of the service mesh that the route resides in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

metadata

The associated metadata for the route.

Type: [ResourceMetadata](#) object

Required: Yes

routeName

The name of the route.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

spec

The specifications of the route.

Type: [RouteSpec](#) object

Required: Yes

status

The status of the route.

Type: [RouteStatus](#) object

Required: Yes

virtualRouterName

The virtual router that the route is associated with.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RouteRef

An object that represents a route returned by a list operation.

Contents

arn

The full Amazon Resource Name (ARN) for the route.

Type: String

Required: Yes

createdAt

The Unix epoch timestamp in seconds for when the resource was created.

Type: Timestamp

Required: Yes

lastUpdatedAt

The Unix epoch timestamp in seconds for when the resource was last updated.

Type: Timestamp

Required: Yes

meshName

The name of the service mesh that the route resides in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then it's the ID of the account that shared the mesh with your account. For more information about mesh sharing, see [Working with shared meshes](#).

Type: String

Length Constraints: Fixed length of 12.

Required: Yes

resourceOwner

The AWS IAM account ID of the resource owner. If the account ID is not your own, then it's the ID of the mesh owner or of another account that the mesh is shared with. For more information about mesh sharing, see [Working with shared meshes](#).

Type: String

Length Constraints: Fixed length of 12.

Required: Yes

routeName

The name of the route.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

version

The version of the resource. Resources are created at version 1, and this version is incremented each time that they're updated.

Type: Long

Required: Yes

virtualRouterName

The virtual router that the route is associated with.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RouteSpec

An object that represents a route specification. Specify one route type.

Contents

grpcRoute

An object that represents the specification of a gRPC route.

Type: [GrpcRoute](#) object

Required: No

http2Route

An object that represents the specification of an HTTP/2 route.

Type: [HttpRoute](#) object

Required: No

httpRoute

An object that represents the specification of an HTTP route.

Type: [HttpRoute](#) object

Required: No

priority

The priority for the route. Routes are matched based on the specified value, where 0 is the highest priority.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 1000.

Required: No

tcpRoute

An object that represents the specification of a TCP route.

Type: [TcpRoute](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RouteStatus

An object that represents the current status of a route.

Contents

status

The current status for the route.

Type: String

Valid Values: ACTIVE | INACTIVE | DELETED

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceDiscovery

An object that represents the service discovery information for a virtual node.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

awsCloudMap

Specifies any AWS Cloud Map information for the virtual node.

Type: [AwsCloudMapServiceDiscovery](#) object

Required: No

dns

Specifies the DNS information for the virtual node.

Type: [DnsServiceDiscovery](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SubjectAlternativeNameMatchers

An object that represents the methods by which a subject alternative name on a peer Transport Layer Security (TLS) certificate can be matched.

Contents

exact

The values sent must match the specified values exactly.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 254.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SubjectAlternativeNames

An object that represents the subject alternative names secured by the certificate.

Contents

match

An object that represents the criteria for determining a SANs match.

Type: [SubjectAlternativeNameMatchers](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TagRef

Optional metadata that you apply to a resource to assist with categorization and organization. Each tag consists of a key and an optional value, both of which you define. Tag keys can have a maximum character length of 128 characters, and tag values can have a maximum length of 256 characters.

Contents

key

One part of a key-value pair that make up a tag. A key is a general label that acts like a category for more specific tag values.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

value

The optional part of a key-value pair that make up a tag. A value acts as a descriptor within a tag category (key).

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TcpRoute

An object that represents a TCP route type.

Contents

action

The action to take if a match is determined.

Type: [TcpRouteAction](#) object

Required: Yes

match

An object that represents the criteria for determining a request match.

Type: [TcpRouteMatch](#) object

Required: No

timeout

An object that represents types of timeouts.

Type: [TcpTimeout](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TcpRouteAction

An object that represents the action to take if a match is determined.

Contents

weightedTargets

An object that represents the targets that traffic is routed to when a request matches the route.

Type: Array of [WeightedTarget](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TcpRouteMatch

An object representing the TCP route to match.

Contents

port

The port number to match on.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TcpTimeout

An object that represents types of timeouts.

Contents

idle

An object that represents an idle timeout. An idle timeout bounds the amount of time that a connection may be idle. The default value is none.

Type: [Duration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TlsValidationContext

An object that represents how the proxy will validate its peer during Transport Layer Security (TLS) negotiation.

Contents

trust

A reference to where to retrieve the trust chain when validating a peer's Transport Layer Security (TLS) certificate.

Type: [TlsValidationContextTrust](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

subjectAlternativeNames

A reference to an object that represents the SANs for a Transport Layer Security (TLS) validation context. If you don't specify SANs on the *terminating* mesh endpoint, the Envoy proxy for that node doesn't verify the SAN on a peer client certificate. If you don't specify SANs on the *originating* mesh endpoint, the SAN on the certificate provided by the terminating endpoint must match the mesh endpoint service discovery configuration. Since SPIRE vended certificates have a SPIFFE ID as a name, you must set the SAN since the name doesn't match the service discovery name.

Type: [SubjectAlternativeNames](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TlsValidationContextAcmTrust

An object that represents a Transport Layer Security (TLS) validation context trust for an AWS Certificate Manager certificate.

Contents

certificateAuthorityArns

One or more ACM Amazon Resource Name (ARN)s.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 3 items.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TlsValidationContextFileTrust

An object that represents a Transport Layer Security (TLS) validation context trust for a local file.

Contents

certificateChain

The certificate trust chain for a certificate stored on the file system of the virtual node that the proxy is running on.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TlsValidationContextSdsTrust

An object that represents a Transport Layer Security (TLS) Secret Discovery Service validation context trust. The proxy must be configured with a local SDS provider via a Unix Domain Socket. See App Mesh [TLS documentation](#) for more info.

Contents

secretName

A reference to an object that represents the name of the secret for a Transport Layer Security (TLS) Secret Discovery Service validation context trust.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TlsValidationContextTrust

An object that represents a Transport Layer Security (TLS) validation context trust.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

acm

A reference to an object that represents a Transport Layer Security (TLS) validation context trust for an AWS Certificate Manager certificate.

Type: [TlsValidationContextAcmTrust](#) object

Required: No

file

An object that represents a Transport Layer Security (TLS) validation context trust for a local file.

Type: [TlsValidationContextFileTrust](#) object

Required: No

sds

A reference to an object that represents a Transport Layer Security (TLS) Secret Discovery Service validation context trust.

Type: [TlsValidationContextSdsTrust](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualGatewayAccessLog

The access log configuration for a virtual gateway.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

file

The file object to send virtual gateway access logs to.

Type: [VirtualGatewayFileAccessLog](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualGatewayBackendDefaults

An object that represents the default properties for a backend.

Contents

clientPolicy

A reference to an object that represents a client policy.

Type: [VirtualGatewayClientPolicy](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualGatewayClientPolicy

An object that represents a client policy.

Contents

tls

A reference to an object that represents a Transport Layer Security (TLS) client policy.

Type: [VirtualGatewayClientPolicyTls](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualGatewayClientPolicyTls

An object that represents a Transport Layer Security (TLS) client policy.

Contents

validation

A reference to an object that represents a Transport Layer Security (TLS) validation context.

Type: [VirtualGatewayTlsValidationContext](#) object

Required: Yes

certificate

A reference to an object that represents a virtual gateway's client's Transport Layer Security (TLS) certificate.

Type: [VirtualGatewayClientTlsCertificate](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

enforce

Whether the policy is enforced. The default is `True`, if a value isn't specified.

Type: Boolean

Required: No

ports

One or more ports that the policy is enforced for.

Type: Array of integers

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualGatewayClientTlsCertificate

An object that represents the virtual gateway's client's Transport Layer Security (TLS) certificate.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

file

An object that represents a local file certificate. The certificate must meet specific requirements and you must have proxy authorization enabled. For more information, see [Transport Layer Security \(TLS\)](#).

Type: [VirtualGatewayListenerTlsFileCertificate](#) object

Required: No

sds

A reference to an object that represents a virtual gateway's client's Secret Discovery Service certificate.

Type: [VirtualGatewayListenerTlsSdsCertificate](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualGatewayConnectionPool

An object that represents the type of virtual gateway connection pool.

Only one protocol is used at a time and should be the same protocol as the one chosen under port mapping.

If not present the default value for `maxPendingRequests` is 2147483647.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

grpc

An object that represents a type of connection pool.

Type: [VirtualGatewayGrpcConnectionPool](#) object

Required: No

http

An object that represents a type of connection pool.

Type: [VirtualGatewayHttpConnectionPool](#) object

Required: No

http2

An object that represents a type of connection pool.

Type: [VirtualGatewayHttp2ConnectionPool](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualGatewayData

An object that represents a virtual gateway returned by a describe operation.

Contents

meshName

The name of the service mesh that the virtual gateway resides in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

metadata

An object that represents metadata for a resource.

Type: [ResourceMetadata](#) object

Required: Yes

spec

The specifications of the virtual gateway.

Type: [VirtualGatewaySpec](#) object

Required: Yes

status

The current status of the virtual gateway.

Type: [VirtualGatewayStatus](#) object

Required: Yes

virtualGatewayName

The name of the virtual gateway.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualGatewayFileAccessLog

An object that represents an access log file.

Contents

path

The file path to write access logs to. You can use `/dev/stdout` to send access logs to standard out and configure your Envoy container to use a log driver, such as `awslogs`, to export the access logs to a log storage service such as Amazon CloudWatch Logs. You can also specify a path in the Envoy container's file system to write the files to disk.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

format

The specified format for the virtual gateway access logs. It can be either `json_format` or `text_format`.

Type: [LoggingFormat](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualGatewayGrpcConnectionPool

An object that represents a type of connection pool.

Contents

maxRequests

Maximum number of inflight requests Envoy can concurrently support across hosts in upstream cluster.

Type: Integer

Valid Range: Minimum value of 1.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualGatewayHealthCheckPolicy

An object that represents the health check policy for a virtual gateway's listener.

Contents

healthyThreshold

The number of consecutive successful health checks that must occur before declaring the listener healthy.

Type: Integer

Valid Range: Minimum value of 2. Maximum value of 10.

Required: Yes

intervalMillis

The time period in milliseconds between each health check execution.

Type: Long

Valid Range: Minimum value of 5000. Maximum value of 300000.

Required: Yes

protocol

The protocol for the health check request. If you specify `grpc`, then your service must conform to the [GRPC Health Checking Protocol](#).

Type: String

Valid Values: `http` | `http2` | `grpc`

Required: Yes

timeoutMillis

The amount of time to wait when receiving a response from the health check, in milliseconds.

Type: Long

Valid Range: Minimum value of 2000. Maximum value of 60000.

Required: Yes

unhealthyThreshold

The number of consecutive failed health checks that must occur before declaring a virtual gateway unhealthy.

Type: Integer

Valid Range: Minimum value of 2. Maximum value of 10.

Required: Yes

path

The destination path for the health check request. This value is only used if the specified protocol is HTTP or HTTP/2. For any other protocol, this value is ignored.

Type: String

Required: No

port

The destination port for the health check request. This port must match the port defined in the [PortMapping](#) for the listener.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualGatewayHttp2ConnectionPool

An object that represents a type of connection pool.

Contents

maxRequests

Maximum number of inflight requests Envoy can concurrently support across hosts in upstream cluster.

Type: Integer

Valid Range: Minimum value of 1.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualGatewayHttpConnectionPool

An object that represents a type of connection pool.

Contents

maxConnections

Maximum number of outbound TCP connections Envoy can establish concurrently with all hosts in upstream cluster.

Type: Integer

Valid Range: Minimum value of 1.

Required: Yes

maxPendingRequests

Number of overflowing requests after max_connections Envoy will queue to upstream cluster.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualGatewayListener

An object that represents a listener for a virtual gateway.

Contents

portMapping

The port mapping information for the listener.

Type: [VirtualGatewayPortMapping](#) object

Required: Yes

connectionPool

The connection pool information for the virtual gateway listener.

Type: [VirtualGatewayConnectionPool](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

healthCheck

The health check information for the listener.

Type: [VirtualGatewayHealthCheckPolicy](#) object

Required: No

tls

A reference to an object that represents the Transport Layer Security (TLS) properties for the listener.

Type: [VirtualGatewayListenerTls](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualGatewayListenerTls

An object that represents the Transport Layer Security (TLS) properties for a listener.

Contents

certificate

An object that represents a Transport Layer Security (TLS) certificate.

Type: [VirtualGatewayListenerTlsCertificate](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

mode

Specify one of the following modes.

- STRICT – Listener only accepts connections with TLS enabled.
- PERMISSIVE – Listener accepts connections with or without TLS enabled.
- DISABLED – Listener only accepts connections without TLS.

Type: String

Valid Values: STRICT | PERMISSIVE | DISABLED

Required: Yes

validation

A reference to an object that represents a virtual gateway's listener's Transport Layer Security (TLS) validation context.

Type: [VirtualGatewayListenerTlsValidationContext](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualGatewayListenerTlsAcmCertificate

An object that represents an AWS Certificate Manager certificate.

Contents

certificateArn

The Amazon Resource Name (ARN) for the certificate. The certificate must meet specific requirements and you must have proxy authorization enabled. For more information, see [Transport Layer Security \(TLS\)](#).

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualGatewayListenerTlsCertificate

An object that represents a listener's Transport Layer Security (TLS) certificate.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

acm

A reference to an object that represents an AWS Certificate Manager certificate.

Type: [VirtualGatewayListenerTlsAcmCertificate](#) object

Required: No

file

A reference to an object that represents a local file certificate.

Type: [VirtualGatewayListenerTlsFileCertificate](#) object

Required: No

sds

A reference to an object that represents a virtual gateway's listener's Secret Discovery Service certificate.

Type: [VirtualGatewayListenerTlsSdsCertificate](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualGatewayListenerTlsFileCertificate

An object that represents a local file certificate. The certificate must meet specific requirements and you must have proxy authorization enabled. For more information, see [Transport Layer Security \(TLS\)](#).

Contents

certificateChain

The certificate chain for the certificate.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

privateKey

The private key for a certificate stored on the file system of the mesh endpoint that the proxy is running on.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualGatewayListenerTlsSdsCertificate

An object that represents the virtual gateway's listener's Secret Discovery Service certificate. The proxy must be configured with a local SDS provider via a Unix Domain Socket. See App Mesh [TLS documentation](#) for more info.

Contents

secretName

A reference to an object that represents the name of the secret secret requested from the Secret Discovery Service provider representing Transport Layer Security (TLS) materials like a certificate or certificate chain.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualGatewayListenerTlsValidationContext

An object that represents a virtual gateway's listener's Transport Layer Security (TLS) validation context.

Contents

trust

A reference to where to retrieve the trust chain when validating a peer's Transport Layer Security (TLS) certificate.

Type: [VirtualGatewayListenerTlsValidationContextTrust](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

subjectAlternativeNames

A reference to an object that represents the SANs for a virtual gateway listener's Transport Layer Security (TLS) validation context.

Type: [SubjectAlternativeNames](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualGatewayListenerTlsValidationContextTrust

An object that represents a virtual gateway's listener's Transport Layer Security (TLS) validation context trust.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

file

An object that represents a Transport Layer Security (TLS) validation context trust for a local file.

Type: [VirtualGatewayTlsValidationContextFileTrust](#) object

Required: No

sds

A reference to an object that represents a virtual gateway's listener's Transport Layer Security (TLS) Secret Discovery Service validation context trust.

Type: [VirtualGatewayTlsValidationContextSdsTrust](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualGatewayLogging

An object that represents logging information.

Contents

accessLog

The access log configuration.

Type: [VirtualGatewayAccessLog](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualGatewayPortMapping

An object that represents a port mapping.

Contents

port

The port used for the port mapping. Specify one protocol.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: Yes

protocol

The protocol used for the port mapping.

Type: String

Valid Values: http | http2 | grpc

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualGatewayRef

An object that represents a virtual gateway returned by a list operation.

Contents

arn

The full Amazon Resource Name (ARN) for the resource.

Type: String

Required: Yes

createdAt

The Unix epoch timestamp in seconds for when the resource was created.

Type: Timestamp

Required: Yes

lastUpdatedAt

The Unix epoch timestamp in seconds for when the resource was last updated.

Type: Timestamp

Required: Yes

meshName

The name of the service mesh that the resource resides in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then it's the ID of the account that shared the mesh with your account. For more information about mesh sharing, see [Working with shared meshes](#).

Type: String

Length Constraints: Fixed length of 12.

Required: Yes

resourceOwner

The AWS IAM account ID of the resource owner. If the account ID is not your own, then it's the ID of the mesh owner or of another account that the mesh is shared with. For more information about mesh sharing, see [Working with shared meshes](#).

Type: String

Length Constraints: Fixed length of 12.

Required: Yes

version

The version of the resource. Resources are created at version 1, and this version is incremented each time that they're updated.

Type: Long

Required: Yes

virtualGatewayName

The name of the resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

VirtualGatewaySpec

An object that represents the specification of a service mesh resource.

Contents

listeners

The listeners that the mesh endpoint is expected to receive inbound traffic from. You can specify one listener.

Type: Array of [VirtualGatewayListener](#) objects

Required: Yes

backendDefaults

A reference to an object that represents the defaults for backends.

Type: [VirtualGatewayBackendDefaults](#) object

Required: No

logging

An object that represents logging information.

Type: [VirtualGatewayLogging](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualGatewayStatus

An object that represents the status of the mesh resource.

Contents

status

The current status.

Type: String

Valid Values: ACTIVE | INACTIVE | DELETED

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualGatewayTlsValidationContext

An object that represents a Transport Layer Security (TLS) validation context.

Contents

trust

A reference to where to retrieve the trust chain when validating a peer's Transport Layer Security (TLS) certificate.

Type: [VirtualGatewayTlsValidationContextTrust](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

subjectAlternativeNames

A reference to an object that represents the SANs for a virtual gateway's listener's Transport Layer Security (TLS) validation context.

Type: [SubjectAlternativeNames](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualGatewayTlsValidationContextAcmTrust

An object that represents a Transport Layer Security (TLS) validation context trust for an AWS Certificate Manager certificate.

Contents

certificateAuthorityArns

One or more ACM Amazon Resource Name (ARN)s.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 3 items.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualGatewayTlsValidationContextFileTrust

An object that represents a Transport Layer Security (TLS) validation context trust for a local file.

Contents

certificateChain

The certificate trust chain for a certificate stored on the file system of the virtual node that the proxy is running on.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualGatewayTlsValidationContextSdsTrust

An object that represents a virtual gateway's listener's Transport Layer Security (TLS) Secret Discovery Service validation context trust. The proxy must be configured with a local SDS provider via a Unix Domain Socket. See App Mesh [TLS documentation](#) for more info.

Contents

secretName

A reference to an object that represents the name of the secret for a virtual gateway's Transport Layer Security (TLS) Secret Discovery Service validation context trust.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualGatewayTlsValidationContextTrust

An object that represents a Transport Layer Security (TLS) validation context trust.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

acm

A reference to an object that represents a Transport Layer Security (TLS) validation context trust for an AWS Certificate Manager certificate.

Type: [VirtualGatewayTlsValidationContextAcmTrust](#) object

Required: No

file

An object that represents a Transport Layer Security (TLS) validation context trust for a local file.

Type: [VirtualGatewayTlsValidationContextFileTrust](#) object

Required: No

sds

A reference to an object that represents a virtual gateway's Transport Layer Security (TLS) Secret Discovery Service validation context trust.

Type: [VirtualGatewayTlsValidationContextSdsTrust](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualNodeConnectionPool

An object that represents the type of virtual node connection pool.

Only one protocol is used at a time and should be the same protocol as the one chosen under port mapping.

If not present the default value for `maxPendingRequests` is 2147483647.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

grpc

An object that represents a type of connection pool.

Type: [VirtualNodeGrpcConnectionPool](#) object

Required: No

http

An object that represents a type of connection pool.

Type: [VirtualNodeHttpConnectionPool](#) object

Required: No

http2

An object that represents a type of connection pool.

Type: [VirtualNodeHttp2ConnectionPool](#) object

Required: No

tcp

An object that represents a type of connection pool.

Type: [VirtualNodeTcpConnectionPool](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualNodeData

An object that represents a virtual node returned by a describe operation.

Contents

meshName

The name of the service mesh that the virtual node resides in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

metadata

The associated metadata for the virtual node.

Type: [ResourceMetadata](#) object

Required: Yes

spec

The specifications of the virtual node.

Type: [VirtualNodeSpec](#) object

Required: Yes

status

The current status for the virtual node.

Type: [VirtualNodeStatus](#) object

Required: Yes

virtualNodeName

The name of the virtual node.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualNodeGrpcConnectionPool

An object that represents a type of connection pool.

Contents

maxRequests

Maximum number of inflight requests Envoy can concurrently support across hosts in upstream cluster.

Type: Integer

Valid Range: Minimum value of 1.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualNodeHttp2ConnectionPool

An object that represents a type of connection pool.

Contents

maxRequests

Maximum number of inflight requests Envoy can concurrently support across hosts in upstream cluster.

Type: Integer

Valid Range: Minimum value of 1.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualNodeHttpConnectionPool

An object that represents a type of connection pool.

Contents

maxConnections

Maximum number of outbound TCP connections Envoy can establish concurrently with all hosts in upstream cluster.

Type: Integer

Valid Range: Minimum value of 1.

Required: Yes

maxPendingRequests

Number of overflowing requests after max_connections Envoy will queue to upstream cluster.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualNodeRef

An object that represents a virtual node returned by a list operation.

Contents

arn

The full Amazon Resource Name (ARN) for the virtual node.

Type: String

Required: Yes

createdAt

The Unix epoch timestamp in seconds for when the resource was created.

Type: Timestamp

Required: Yes

lastUpdatedAt

The Unix epoch timestamp in seconds for when the resource was last updated.

Type: Timestamp

Required: Yes

meshName

The name of the service mesh that the virtual node resides in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then it's the ID of the account that shared the mesh with your account. For more information about mesh sharing, see [Working with shared meshes](#).

Type: String

Length Constraints: Fixed length of 12.

Required: Yes

resourceOwner

The AWS IAM account ID of the resource owner. If the account ID is not your own, then it's the ID of the mesh owner or of another account that the mesh is shared with. For more information about mesh sharing, see [Working with shared meshes](#).

Type: String

Length Constraints: Fixed length of 12.

Required: Yes

version

The version of the resource. Resources are created at version 1, and this version is incremented each time that they're updated.

Type: Long

Required: Yes

virtualNodeName

The name of the virtual node.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

VirtualNodeServiceProvider

An object that represents a virtual node service provider.

Contents

virtualNodeName

The name of the virtual node that is acting as a service provider.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualNodeSpec

An object that represents the specification of a virtual node.

Contents

backendDefaults

A reference to an object that represents the defaults for backends.

Type: [BackendDefaults](#) object

Required: No

backends

The backends that the virtual node is expected to send outbound traffic to.

Important

App Mesh doesn't validate the existence of those virtual services specified in backends. This is to prevent a cyclic dependency between virtual nodes and virtual services creation. Make sure the virtual service name is correct. The virtual service can be created afterwards if it doesn't already exist.

Type: Array of [Backend](#) objects

Required: No

listeners

The listener that the virtual node is expected to receive inbound traffic from. You can specify one listener.

Type: Array of [Listener](#) objects

Required: No

logging

The inbound and outbound access logging information for the virtual node.

Type: [Logging](#) object

Required: No

serviceDiscovery

The service discovery information for the virtual node. If your virtual node does not expect ingress traffic, you can omit this parameter. If you specify a `listener`, then you must specify service discovery information.

Type: [ServiceDiscovery](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualNodeStatus

An object that represents the current status of the virtual node.

Contents

status

The current status of the virtual node.

Type: String

Valid Values: ACTIVE | INACTIVE | DELETED

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualNodeTcpConnectionPool

An object that represents a type of connection pool.

Contents

maxConnections

Maximum number of outbound TCP connections Envoy can establish concurrently with all hosts in upstream cluster.

Type: Integer

Valid Range: Minimum value of 1.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualRouterData

An object that represents a virtual router returned by a describe operation.

Contents

meshName

The name of the service mesh that the virtual router resides in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

metadata

The associated metadata for the virtual router.

Type: [ResourceMetadata](#) object

Required: Yes

spec

The specifications of the virtual router.

Type: [VirtualRouterSpec](#) object

Required: Yes

status

The current status of the virtual router.

Type: [VirtualRouterStatus](#) object

Required: Yes

virtualRouterName

The name of the virtual router.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualRouterListener

An object that represents a virtual router listener.

Contents

portMapping

An object that represents a port mapping.

Type: [PortMapping](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualRouterRef

An object that represents a virtual router returned by a list operation.

Contents

arn

The full Amazon Resource Name (ARN) for the virtual router.

Type: String

Required: Yes

createdAt

The Unix epoch timestamp in seconds for when the resource was created.

Type: Timestamp

Required: Yes

lastUpdatedAt

The Unix epoch timestamp in seconds for when the resource was last updated.

Type: Timestamp

Required: Yes

meshName

The name of the service mesh that the virtual router resides in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then it's the ID of the account that shared the mesh with your account. For more information about mesh sharing, see [Working with shared meshes](#).

Type: String

Length Constraints: Fixed length of 12.

Required: Yes

resourceOwner

The AWS IAM account ID of the resource owner. If the account ID is not your own, then it's the ID of the mesh owner or of another account that the mesh is shared with. For more information about mesh sharing, see [Working with shared meshes](#).

Type: String

Length Constraints: Fixed length of 12.

Required: Yes

version

The version of the resource. Resources are created at version 1, and this version is incremented each time that they're updated.

Type: Long

Required: Yes

virtualRouterName

The name of the virtual router.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

VirtualRouterServiceProvider

An object that represents a virtual node service provider.

Contents

virtualRouterName

The name of the virtual router that is acting as a service provider.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualRouterSpec

An object that represents the specification of a virtual router.

Contents

listeners

The listeners that the virtual router is expected to receive inbound traffic from.

Type: Array of [VirtualRouterListener](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualRouterStatus

An object that represents the status of a virtual router.

Contents

status

The current status of the virtual router.

Type: String

Valid Values: ACTIVE | INACTIVE | DELETED

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualServiceBackend

An object that represents a virtual service backend for a virtual node.

Contents

virtualServiceName

The name of the virtual service that is acting as a virtual node backend.

Important

App Mesh doesn't validate the existence of those virtual services specified in backends. This is to prevent a cyclic dependency between virtual nodes and virtual services creation. Make sure the virtual service name is correct. The virtual service can be created afterwards if it doesn't already exist.

Type: String

Required: Yes

clientPolicy

A reference to an object that represents the client policy for a backend.

Type: [ClientPolicy](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualServiceData

An object that represents a virtual service returned by a describe operation.

Contents

meshName

The name of the service mesh that the virtual service resides in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

metadata

An object that represents metadata for a resource.

Type: [ResourceMetadata](#) object

Required: Yes

spec

The specifications of the virtual service.

Type: [VirtualServiceSpec](#) object

Required: Yes

status

The current status of the virtual service.

Type: [VirtualServiceStatus](#) object

Required: Yes

virtualServiceName

The name of the virtual service.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualServiceProvider

An object that represents the provider for a virtual service.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

virtualNode

The virtual node associated with a virtual service.

Type: [VirtualNodeServiceProvider](#) object

Required: No

virtualRouter

The virtual router associated with a virtual service.

Type: [VirtualRouterServiceProvider](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualServiceRef

An object that represents a virtual service returned by a list operation.

Contents

arn

The full Amazon Resource Name (ARN) for the virtual service.

Type: String

Required: Yes

createdAt

The Unix epoch timestamp in seconds for when the resource was created.

Type: Timestamp

Required: Yes

lastUpdatedAt

The Unix epoch timestamp in seconds for when the resource was last updated.

Type: Timestamp

Required: Yes

meshName

The name of the service mesh that the virtual service resides in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

meshOwner

The AWS IAM account ID of the service mesh owner. If the account ID is not your own, then it's the ID of the account that shared the mesh with your account. For more information about mesh sharing, see [Working with shared meshes](#).

Type: String

Length Constraints: Fixed length of 12.

Required: Yes

resourceOwner

The AWS IAM account ID of the resource owner. If the account ID is not your own, then it's the ID of the mesh owner or of another account that the mesh is shared with. For more information about mesh sharing, see [Working with shared meshes](#).

Type: String

Length Constraints: Fixed length of 12.

Required: Yes

version

The version of the resource. Resources are created at version 1, and this version is incremented each time that they're updated.

Type: Long

Required: Yes

virtualServiceName

The name of the virtual service.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualServiceSpec

An object that represents the specification of a virtual service.

Contents

provider

The App Mesh object that is acting as the provider for a virtual service. You can specify a single virtual node or virtual router.

Type: [VirtualServiceProvider](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VirtualServiceStatus

An object that represents the status of a virtual service.

Contents

status

The current status of the virtual service.

Type: String

Valid Values: ACTIVE | INACTIVE | DELETED

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

WeightedTarget

An object that represents a target and its relative weight. Traffic is distributed across targets according to their relative weight. For example, a weighted target with a relative weight of 50 receives five times as much traffic as one with a relative weight of 10. The total weight for all targets combined must be less than or equal to 100.

Contents

virtualNode

The virtual node to associate with the weighted target.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: Yes

weight

The relative weight of the weighted target.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: Yes

port

The targeted port of the weighted object.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)