

PostgreSQL Cheat Sheet

PostgreSQL is an open-source relational database management system. Known for its robust features, extensibility, and adherence to standards, it is a powerful and widely used database solution for storing, managing, and processing data across diverse environments.

Check out the official PostgreSQL site here:
<https://www.postgresql.org/>

CONNECTING TO A POSTGRESQL SERVER

Connect to a PostgreSQL server using the PostgreSQL command-line client (psql) and a username. It will prompt you for the password:

```
psql -U username
```

To connect to a specific database on a PostgreSQL server with a username:

```
psql -U username -h host_name -d database_name
```

To exit the client:

```
\q
```

For a full list of commands:

```
\h
```

For a list of psql commands:

```
\?
```

To export data using the pg_dump tool:

```
pg_dump -U username -h host_name -d database_name > data_backup.sql
```

CREATING AND DISPLAYING DATABASES

To create a database:

```
CREATE DATABASE zoo;
```

To delete a specific database:

```
DROP DATABASE zoo;
```

To list all the databases on a server:

```
\l;
```

To connect to a specific database:

```
\c zoo;
```

To list all tables in a database:

```
\dt;
```

To get information about a specific table:

```
\d animal;
```

It outputs column names, data types, default values, and more about the table.

CREATING TABLES

To create a table:

```
CREATE TABLE habitat (  
  id INT,  
  name VARCHAR(64)  
);
```

To increment the ID automatically with each new record, use the SERIAL data type:

```
CREATE TABLE habitat (  
  id INT SERIAL PRIMARY KEY,  
  name VARCHAR(64)  
);
```

To create a table with a foreign key:

```
CREATE TABLE animal (  
  id SERIAL PRIMARY KEY,  
  name VARCHAR(64),  
  species VARCHAR(64),  
  age INT,  
  habitat_id INT,  
  FOREIGN KEY (habitat_id)  
    REFERENCES habitat(id)  
);
```

MODIFYING TABLES

Use the ALTER TABLE to modify a table structure.

To change a table name:

```
ALTER TABLE animal RENAME TO pet;
```

To add a column to the table:

```
ALTER TABLE animal  
ADD COLUMN name VARCHAR(64);
```

To change a column name:

```
ALTER TABLE animal  
RENAME COLUMN id TO identifier;
```

To change a column data type:

```
ALTER TABLE animal  
ALTER COLUMN name TYPE VARCHAR(128);
```

To delete a column:

```
ALTER TABLE animal  
DROP COLUMN name;
```

To delete a table:

```
DROP TABLE animal;
```

QUERYING DATA

To select data from a table, use SELECT.

An example of a single-table query:

```
SELECT species, AVG(age) AS average_age  
FROM animal  
WHERE id != 3  
GROUP BY species  
HAVING AVG(age) > 3  
ORDER BY AVG(age) DESC;
```

An example of a multiple-table query:

```
SELECT city.name, country.name  
FROM city  
[INNER | LEFT | RIGHT | FULL] JOIN country  
  ON city.country_id = country.id;
```

AGGREGATION AND GROUPING

- AVG**(expr) – average value of expr for the group.
- COUNT**(expr) – count of expr values within the group.
- MAX**(expr) – maximum value of expr values within the group.
- MIN**(expr) – minimum value of expr values within the group.
- SUM**(expr) – sum of expr values within the group.

To count the rows in the table:

```
SELECT COUNT(*)  
FROM animal;
```

To count the non-NULL values in a column:

```
SELECT COUNT(name)  
FROM animal;
```

To count unique values in a column:

```
SELECT COUNT(DISTINCT name)  
FROM animal;
```

GROUP BY

To count the animals by species:

```
SELECT species, COUNT(id)  
FROM animal  
GROUP BY species;
```

To get the average, minimum, and maximum ages by habitat:

```
SELECT habitat_id, AVG(age),  
  MIN(age), MAX(age)  
FROM animal  
GROUP BY habitat_id;
```

INSERTING DATA

To insert data into a table, use INSERT:

```
INSERT INTO habitat VALUES  
(1, 'River'),  
(2, 'Forest');
```

You may specify the columns in which the data is added. The remaining columns are filled with default values or NULLs.

```
INSERT INTO habitat (name)  
VALUES ('Savanna');
```

UPDATING DATA

To update the data in a table, use UPDATE:

```
UPDATE animal  
SET  
  species = 'Duck',  
  name = 'Quack'  
WHERE id = 2;
```

DELETING DATA

To delete data from a table, use DELETE:

```
DELETE FROM animal  
WHERE id = 1;
```

This deletes all rows satisfying the WHERE condition.

To delete all data from a table, use TRUNCATE TABLE:

```
TRUNCATE TABLE animal;
```

COPYING DATA

To import data from a CSV file into a table:

```
\copy animal FROM 'animal.csv' CSV HEADER
```

To export data from a query to a CSV file:

```
\copy (SELECT * FROM animal)  
TO 'animal.csv' CSV HEADER
```

CASTING

To change the type of a value, use the :: operator:

```
SELECT 25.5::INTEGER; -- result: 26
```

You may also use CAST(). This is useful when the name of the type contains spaces, e.g., double precision:

```
SELECT CAST(column AS DOUBLE PRECISION);
```

TEXT FUNCTIONS

FILTERING THE OUTPUT

To fetch the city names that are not Berlin:

```
SELECT name  
FROM city  
WHERE name != 'Berlin';
```

TEXT OPERATORS

To fetch the city names that start with a 'P':

```
SELECT name  
FROM city  
WHERE name LIKE 'P%';
```

To fetch the city names that start with any letter followed by 'ublin' (like Dublin in Ireland or Lublin in Poland):

```
SELECT name  
FROM city  
WHERE name LIKE '_ublin';
```

CONCATENATION

To concatenate two strings, use the || operator or the CONCAT() function:

```
SELECT 'Hi ' || 'there!';  
-- result: Hi there!  
SELECT CONCAT('Hello ', 'there!');  
-- result: Hello there!
```

Note that with ||, the result is NULL if any of the strings is NULL:

```
SELECT 'Great ' || 'day' || NULL;  
-- result: NULL
```

In contrast, CONCAT() ignores NULL:

```
SELECT CONCAT('Good ', 'day', NULL);  
-- result: Good day
```

OTHER USEFUL TEXT FUNCTIONS

To get the count of characters in a string:

```
SELECT LENGTH('LearnSQL.com');  
-- result: 12
```

To convert all letters to lowercase:

```
SELECT LOWER('LEARNSQL.COM');  
-- result: learnsql.com
```

To convert all letters to uppercase:

```
SELECT UPPER('LearnSQL.com');  
-- result: LEARNSQL.COM
```

To capitalize the first letter of each word in a string, use INITCAP():

```
SELECT INITCAP('hello world');  
-- result: 'Hello World'
```

To get a part of a string:

```
SELECT SUBSTRING('LearnSQL.com', 9);  
-- result: .com  
SELECT SUBSTRING('LearnSQL.com', 1, 5);  
-- result: Learn
```

To replace a part of a string:

```
SELECT REPLACE('LearnSQL.com', 'SQL',  
'Python'); -- result: LearnPython.com
```

NUMERIC FUNCTIONS

Use +, -, *, / for basic math.

To get the number of seconds in a week:

```
SELECT 60 * 60 * 24 * 7; -- result: 604800
```

In PostgreSQL, the division operator / performs an integer division on integer arguments. For example:

```
SELECT 25 / 4; -- result 6
```

Avoid integer division by including at least one non-integer argument:

```
SELECT 25::numeric / 4; -- result 6.25  
SELECT 25.0 / 4; -- result 6.25
```

To get the remainder of a division:

```
SELECT MOD(13, 2); -- result: 1  
SELECT 13 % 2; -- result: 1
```

To round a number to its nearest integer:

```
SELECT ROUND(1234.56789); -- result: 1235
```

To round a number to three decimal places (NUMERIC arguments only):

```
SELECT ROUND(1234.56789, 3);  
-- result: 1234.568
```

To get the absolute value of a number:

```
SELECT ABS(-12); -- result: 12
```

To get the square root of a number:

```
SELECT SQRT(9); -- result: 3
```

USEFUL NULL FUNCTIONS

To fetch the names of the cities whose rating values are not missing:

```
SELECT name  
FROM city  
WHERE rating IS NOT NULL;
```

COALESCE(x, y, ...)

To replace NULL in a query with something meaningful:

```
SELECT domain,  
  COALESCE(domain, 'domain missing')  
FROM contacts;  
COALESCE() takes any number of arguments and returns the value of the first non-NULL argument.
```

NULLIF(x, y)

To save yourself from division by 0 errors:

```
SELECT last_month, this_month,  
  this_month * 100.0  
  / NULLIF(last_month, 0)  
  AS better_by_percent  
FROM video_views;  
NULLIF(x, y) returns NULL if x equals y; else it returns the value of x.
```

DATE AND TIME

There are 5 main time-related types in PostgreSQL:

DATE – a date with a resolution of one day; stores the year, month, and day in the YYYY-MM-DD format.

TIME – a time of day with a resolution of one microsecond; stores the hours, minutes, seconds, and fractional seconds in the HH:MM:SS.SSSSSS format.

TIMESTAMP WITH TIME ZONE – a timestamp with the time zone; stores the date and the time along with the corresponding time zone information. The range is from '4713-11-24 00:00:00' BC to '294276-12-31 23:59:59' AD.

TIMESTAMP – a timestamp without the time zone; stores the date and the time. PostgreSQL handles TIMESTAMP values automatically with time zone conversion.

INTERVAL – a duration of time, such as 3 days, 4 hours, and 30 minutes.

WHAT TIME IS IT?

- To answer this question, use:
- CURRENT_TIME – to get the current time.
 - CURRENT_DATE – to get the current date.
 - CURRENT_TIMESTAMP – to get the current timestamp with both of the above.

CREATING DATE/TIME VALUES

To create a date, time, or datetime value, write it as a string and cast it to the desired type.

```
SELECT '2023-12-31'::date;  
SELECT '15:31'::time;  
SELECT '2023-12-31 23:59:29'::timestamp;
```

You may also use CAST() or DATE().

You may skip casting in simple conditions. The database knows what you mean.

```
SELECT airline, flight_number, departure_time  
FROM airport_schedule  
WHERE departure_time < '12:00';
```

INTERVALS

An interval is the duration between two points in time. To define an interval: **INTERVAL '3 days';**

This syntax consists of the INTERVAL keyword, a value, and a time part keyword (YEAR, QUARTER, MONTH, WEEK, DAY, HOUR, MINUTE, SECOND, MICROSECOND).

You may combine different INTERVALs using the + or – operator:

```
INTERVAL '1 year' + INTERVAL '3 months'
```

DATE_TRUNC() in PostgreSQL truncates date or timestamp values to the specified time units.

```
SELECT DATE_TRUNC('hour',  
  '2023-01-15 14:38:00'::TIMESTAMP);  
-- result: '2023-01-15 14:00'  
SELECT DATE_TRUNC('month',  
  '2023-12-30'::DATE);  
-- result: '2023-12-01'
```

DATE_TRUNC() is often used to group by year, month, week, etc.

```
SELECT  
  DATE_TRUNC('month', birth_date) AS month,  
  COUNT(*)  
FROM animal  
GROUP BY DATE_TRUNC('month', birth_date)  
ORDER BY DATE_TRUNC('month', birth_date);
```